```
#|

 Copyright (C) 1994 by Computational Logic, Inc.  All Rights Reserved.

 This script is hereby placed in the public domain, and therefore unlimited
 editing and redistribution is permitted.

 NO WARRANTY

 Computational Logic, Inc. PROVIDES ABSOLUTELY NO WARRANTY.  THE EVENT SCRIPT
 IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED,
 INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND
 FITNESS FOR A PARTICULAR PURPOSE.  THE ENTIRE RISK AS TO THE QUALITY AND
 PERFORMANCE OF THE SCRIPT IS WITH YOU.  SHOULD THE SCRIPT PROVE DEFECTIVE, YOU
 ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

 IN NO EVENT WILL Computational Logic, Inc. BE LIABLE TO YOU FOR ANY DAMAGES,
 ANY LOST PROFITS, LOST MONIES, OR OTHER SPECIAL, INCIDENTAL OR CONSEQUENTIAL
 DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THIS SCRIPT (INCLUDING BUT
 NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES
 SUSTAINED BY THIRD PARTIES), EVEN IF YOU HAVE ADVISED US OF THE POSSIBILITY OF
 SUCH DAMAGES, OR FOR ANY CLAIM BY ANY OTHER PARTY.
|#

; Matt Kaufmann, William R. Bevier, and Matt Wilding
```

EVENT: Start with the library "naturals" using the compiled version.

```
;; from /disk1/wilding/nums/integers.events.

;; 15 January 91 version by Matt Wilding.  Includes all of the
;; Matt Kaufmann's library's functionality, plus various additional
;; facts and numerous tiny changes, mostly having to do with igcd
;; and irem.

;; Several theories are set up:
;; integers  -  general integer strategy
;; integer-defns - integer definitions (does not include igcd)
;; nats-to-ints - rules that rewrite naturals to integers

;; By Matt Kaufmann, modified from earlier integer library of Bill
;; Bevier and Matt Wilding.  A few functions (even ILESSP) have
;; been changed, but I expect the functionality of this library to
```

```
;; include all the functionality of the old one in most or even all
;; cases.

;; Modified from /local/src/nqthm-libs/integers.events to get ILEQ
;; expressed in terms of ILESSP and IDIFFERENCE in terms of INEG and
;; IPLUS.  There are other changes too.  The highlights are the new
;; metalemmas.

;; I'm going to leave the eval$ rules on that are proved here, and
;; leave eval$ off.

;; My intention is that this library be used in a mode in which ILEQ
;; and IDIFFERENCE are left enabled.  Otherwise, the aforementioned
;; meta lemmas may not be very useful, and also a number of additional
;; replacement rules may be needed.

;; There are three theories created by this library.  INTEGER-DEFNS is
;; a list of definitions of all integer functions (not including the
;; cancellation metafunctions and their auxiliaries, though), except
;; that ILEQ and IDIFFERENCE have been omitted.  This is a useful
;; theory for an ENABLE-THEORY hint when one simply wants to blast all
;; integer functions open, and it's also useful if one wants to close
;; them down with a DISABLE-THEORY hint (perhaps to go with an
;; (ENABLE-THEORY T) hint).  Second, ALL-INTEGER-DEFNS is the same as
;; INTEGER-DEFNS except that ILEQ and IDIFFERENCE are included in this
;; one.  Finally, INTEGERS is a list of all events to be "exported as
;; enabled" from this file when working in a mode where everything not
;; enabled by an ENABLE-THEORY hint is to be disabled.  Notice that
;; some rewrite rules have been included that might appear to be
;; unnecessary in light of the metalemmas; that's because metalemmas
;; only work on tame terms.  However, there's no guarantee that the
;; rewrite rules alone will prove very useful (on non-tame terms).
;; Also notice that INTEGER-DEFNS is disjoint from INTEGERS, since we
;; expect the basic definitions (other than ILEQ and IDIFFERENCE) to
;; remain disabled.

;; It's easy to see what I have and haven't placed in INTEGERS, since
;; I'll simply comment out the event names that I want to exclude (see
;; end of this file).

;; One might wish to consider changing (fix-int (minus ...)) in some
;; of the definitions below to (ineg ...).

;; The following meta rules are in this library.
```

```
;; (A little documentation added by Matt Wilding July 90)
;;
;; CORRECTNESS-OF-CANCEL-INEG
;;  cancel the first argument of an iplus term with a member of the second
;;  argument.
;;
;;  ex:  (iplus (ineg y) (iplus (ineg x) (iplus y z)))
;;     -->
;;       (iplus (ineg x) (fix-int z))
;;
;; CORRECTNESS-OF-CANCEL-IPLUS
;;  cancel the sides of an equality of iplus sums
;;
;;  ex:  (equal (iplus x (iplus y z)) (iplus a (iplus z x)))
;;     -->
;;       (equal (fix-int y) (fix-int a))
;;
;; CORRECTNESS-OF-CANCEL-IPLUS-ILESSP
;;  cancel the sides of an ilessp inequality of sums
;;
;;  ex:  (ilessp (iplus x (iplus y z)) (iplus a (iplus z x)))
;;     -->
;;       (ilessp y a)
;;
;; CORRECTNESS-OF-CANCEL-ITIMES
;;  cancel the sides of an equality of itimes products
;;
;;  ex: (equal (itimes x (itimes y z)) (itimes a (itimes z x)))
;;     -->
;;      (if (equal (itimes x z) '0)
;;        t
;;        (equal (fix-int y) (fix-int a)))
;;
;; CORRECTNESS-OF-CANCEL-ITIMES-ILESSP
;;  cancel the sides of an inequality of itimes products
;;
;;  ex: (ilessp (itimes x (itimes y z)) (itimes a (itimes z x)))
;;     -->
;;      (if (ilessp (itimes x z) '0)
;;         (ilessp a y)
;;        (if (ilessp 0 (itimes x z))
;;           (ilessp y a)
;;           f))
;;
```

```
;; CORRECTNESS-OF-CANCEL-ITIMES-FACTORS
;;  cancel factors in equality terms
;;  ex: (equal (iplus (itimes x y) x) (itimes z x))
;;     -->
;;      (if (equal (fix-int x) '0)
;;         t
;;        (equal (fix-int (plus y 1)) (fix-int z)))
;;
;; CORRECTNESS-OF-CANCEL-ITIMES-ILESSP-FACTORS
;;  cancel factors in ilessp terms
;;  ex: (equal (iplus (itimes x y) x) (itimes z x))
;;     -->
;;      (if (ilessp x '0)
;;         (ilessp z (iplus y 1))
;;        (if (ilessp '0 x)
;;           (ilessp (iplus y '1) z)
;;          f))
;;
;; CORRECTNESS-OF-CANCEL-FACTORS-0
;;  factor one side of equality when other side is constant 0
;;
;;  ex: (equal (iplus x (itimes x y)) '0)
;;     -->
;;      (or (equal (fix-int (iplus '1 y)) '0)
;;          (equal (fix-int x) '0))
;;
;; CORRECTNESS-OF-CANCEL-FACTORS-ILESSP-0
;;  factor one side of inequality when other side is constant 0
;;
;;  ex: (ilessp (iplus x (itimes x y)) '0)
;;     -->
;;      (or (and (ilessp (iplus '1 y) '0)
;;               (ilessp '0 x))
;;          (and (ilessp '0 (iplus '1 y))
;;               (ilessp x '0)))
;;
;; CORRECTNESS-OF-CANCEL-INEG-TERMS-FROM-EQUALITY
;;  rewrite equality to remove ineg terms
;;
;;  ex: (equal (iplus (ineg x) (ineg y)) (iplus (ineg z) w))
;;     -->
;;      (equal (fix-int z) (iplus x (iplus y w)))
;;
;; CORRECTNESS-OF-CANCEL-INEG-TERMS-FROM-INEQUALITY
```

```
;;  rewrite inequalities to remove ineg terms
;;
;;  ex: (ilessp (iplus (ineg x) (ineg y)) (iplus (ineg z) w))
;;     -->
;;      (ilessp (fix-int z) (iplus x (iplus y w)))


;;(note-lib "/local/src/nqthm-libs/naturals")

;;(compile-uncompiled-defns "xxx")

; ------------------------------------------------------------------------------
; Integers
; ------------------------------------------------------------------------------


#| The function below has no AND or OR, for efficiency
(defn integerp (x)
  (or (numberp x)
      (and (negativep x)
           (not (zerop (negative-guts x))))))
|#
```

DEFINITION:
integerp (x)
$=$ **if** $x \in \mathbf{N}$ **then t**
elseif negativep (x) **then** negative-guts $(x) \not\simeq 0$
else f endif

DEFINITION:
fix-int (x)
$=$ **if** integerp (x) **then** x
else 0 **endif**

```
;; Even though I'll include a definition for izerop here, I'll
;; often avoid using it.
```

DEFINITION: izerop (i) = (fix-int (i) = 0)

```
#| old version:
(defn izerop (i)
  (if (integerp i)
      (equal i 0)
      t))
```

|#

DEFINITION:
ilessp $(i,\ j)$
$=$ **if** negativep (i)
then if negativep (j) **then** negative-guts $(j) <$ negative-guts (i)
elseif $i = (-\ 0)$ **then** $0 < j$
else t endif
elseif negativep (j) **then f**
else $i < j$ **endif**

DEFINITION: ileq $(i,\ j) = (\neg$ ilessp $(j,\ i))$

DEFINITION:
iplus $(x,\ y)$
$=$ **if** negativep (x)
then if negativep (y)
then if (negative-guts $(x) \simeq 0) \wedge$ (negative-guts $(y) \simeq 0)$ **then** 0
else $-$ (negative-guts $(x) +$ negative-guts (y)) **endif**
elseif $y <$ negative-guts (x) **then** $-$ (negative-guts $(x) - y)$
else $y -$ negative-guts (x) **endif**
elseif negativep (y)
then if $x <$ negative-guts (y) **then** $-$ (negative-guts $(y) - x)$
else $x -$ negative-guts (y) **endif**
else $x + y$ **endif**

DEFINITION:
ineg (x)
$=$ **if** negativep (x) **then** negative-guts (x)
elseif $x \simeq 0$ **then** 0
else $- x$ **endif**

DEFINITION: idifference $(x,\ y) =$ iplus $(x,$ ineg $(y))$

DEFINITION:
iabs (i)
$=$ **if** negativep (i) **then** negative-guts (i)
else fix (i) **endif**

DEFINITION:
itimes $(i,\ j)$
$=$ **if** negativep (i)
then if negativep (j) **then** negative-guts $(i) *$ negative-guts (j)
else fix-int $(-$ (negative-guts $(i) * j))$ **endif**
elseif negativep (j) **then** fix-int $(-$ $(i *$ negative-guts $(j)))$
else $i * j$ **endif**

DEFINITION:
iquotient (i, j)
$=$ **if** fix-int $(j) = 0$ **then** 0
elseif negativep (i)
then if negativep (j)
then if (negative-guts (i) **mod** negative-guts (j)) $= 0$
then negative-guts $(i) \div$ negative-guts (j)
else $1 +$ (negative-guts $(i) \div$ negative-guts (j)) **endif**
elseif (negative-guts (i) **mod** j) $= 0$
then fix-int $(-$ (negative-guts $(i) \div j$))
else fix-int $(-$ $(1 +$ (negative-guts $(i) \div j$))) **endif**
elseif negativep (j) **then** fix-int $(-$ $(i \div$ negative-guts (j)))
else $i \div j$ **endif**

DEFINITION:
iremainder (i, j) = idifference $(i,$ itimes $(j,$ iquotient $(i, j)))$

DEFINITION:
idiv (i, j)
$=$ **if** fix-int $(j) = 0$ **then** 0
elseif negativep (i)
then if negativep (j) **then** negative-guts $(i) \div$ negative-guts (j)
elseif (negative-guts (i) **mod** j) $= 0$
then fix-int $(-$ (negative-guts $(i) \div j$))
else fix-int $(-$ $(1 +$ (negative-guts $(i) \div j$))) **endif**
elseif negativep (j)
then if $(i$ **mod** negative-guts $(j)) = 0$
then fix-int $(-$ $(i \div$ negative-guts (j)))
else fix-int $(-$ $(1 +$ $(i \div$ negative-guts (j))))) **endif**
else $i \div j$ **endif**

DEFINITION:
imod (i, j) = idifference (fix-int (i), itimes $(j,$ idiv $(i, j)))$

DEFINITION:
iquo (i, j)
$=$ **if** fix-int $(j) = 0$ **then** 0
elseif negativep (i)
then if negativep (j) **then** negative-guts $(i) \div$ negative-guts (j)
else fix-int $(-$ (negative-guts $(i) \div j$)) **endif**
elseif negativep (j) **then** fix-int $(-$ $(i \div$ negative-guts (j)))
else $i \div j$ **endif**

DEFINITION:
irem (i, j) = idifference (fix-int (i), itimes $(j,$ iquo $(i, j)))$

```
; ---------- DEFTHEORY events for definitions ----------
```

EVENT: Let us define the theory *integer-defns* to consist of the following events: integerp, fix-int, ilessp, iplus, ineg, iabs, itimes, iquotient, iremainder, idiv, imod, iquo, irem, ileq, idifference, izerop.

EVENT: Disable integerp.

EVENT: Disable fix-int.

EVENT: Disable ilessp.

EVENT: Disable iplus.

EVENT: Disable ineg.

EVENT: Disable iabs.

EVENT: Disable itimes.

```
;; I've disabled the rest later in the file, just because the lemmas
;; about division were (re-)proved with the remaining functions enabled.

; ---------- INTEGERP ----------
```

THEOREM: integerp-fix-int
integerp (fix-int (x))

THEOREM: integerp-iplus
integerp (iplus (x, y))

THEOREM: integerp-idifference
integerp (idifference (x, y))

THEOREM: integerp-ineg
integerp (ineg (x))

THEOREM: integerp-iabs
integerp (iabs (x))

THEOREM: integerp-itimes
integerp (itimes $(x,\ y)$)

```
; ---------- FIX-INT ----------

;; The first of these, FIX-INT-REMOVER, is potentially dangerous from
;; a backchaining point of view, but I believe it's necessary.  At least
;; the lemmas below it should go a long way toward preventing its application.
```

THEOREM: fix-int-remover
integerp $(x) \rightarrow$ (fix-int $(x) = x$)

THEOREM: fix-int-fix-int
fix-int (fix-int (x)) = fix-int (x)

THEOREM: fix-int-iplus
fix-int (iplus $(a,\ b)$) = iplus $(a,\ b)$

THEOREM: fix-int-idifference
fix-int (idifference $(a,\ b)$) = idifference $(a,\ b)$

THEOREM: fix-int-ineg
fix-int (ineg (x)) = ineg (x)

THEOREM: fix-int-iabs
fix-int (iabs (x)) = iabs (x)

THEOREM: fix-int-itimes
fix-int (itimes $(x,\ y)$) = itimes $(x,\ y)$

```
; ---------- INEG ----------
```

THEOREM: ineg-iplus
ineg (iplus $(a,\ b)$) = iplus (ineg (a), ineg (b))

THEOREM: ineg-ineg
ineg (ineg (x)) = fix-int (x)

THEOREM: ineg-fix-int
ineg (fix-int (x)) = ineg (x)

THEOREM: ineg-of-non-integerp
$(\neg$ integerp $(x)) \rightarrow$ (ineg $(x) = 0$)

```
;; I don't want the backchaining to slow down the prover.
```

EVENT: Disable ineg-of-non-integerp.

THEOREM: ineg-0
$\text{ineg}(0) = 0$

```
; ---------- IPLUS ----------

;; The first two of these really aren't necessary, in light
;; of the cancellation metalemma.
```

THEOREM: iplus-left-id
$(\neg\ \text{integerp}(x)) \rightarrow (\text{iplus}(x,\ y) = \text{fix-int}(y))$

```
;; I don't want the backchaining to slow down the prover.
```

EVENT: Disable iplus-left-id.

THEOREM: iplus-right-id
$(\neg\ \text{integerp}(y)) \rightarrow (\text{iplus}(x,\ y) = \text{fix-int}(x))$

```
;; I don't want the backchaining to slow down the prover.
```

EVENT: Disable iplus-right-id.

THEOREM: iplus-0-left
$\text{iplus}(0,\ x) = \text{fix-int}(x)$

THEOREM: iplus-0-right
$\text{iplus}(x,\ 0) = \text{fix-int}(x)$

THEOREM: commutativity2-of-iplus
$\text{iplus}(x,\ \text{iplus}(y,\ z)) = \text{iplus}(y,\ \text{iplus}(x,\ z))$

THEOREM: commutativity-of-iplus
$\text{iplus}(x,\ y) = \text{iplus}(y,\ x)$

THEOREM: associativity-of-iplus
$\text{iplus}(\text{iplus}(x,\ y),\ z) = \text{iplus}(x,\ \text{iplus}(y,\ z))$

THEOREM: iplus-cancellation-1
$(\text{iplus}(a,\ b) = \text{iplus}(a,\ c)) = (\text{fix-int}(b) = \text{fix-int}(c))$

THEOREM: iplus-cancellation-2
$(\text{iplus}(b,\ a) = \text{iplus}(c,\ a)) = (\text{fix-int}(b) = \text{fix-int}(c))$

THEOREM: iplus-ineg1
iplus (ineg (a), a) = 0

THEOREM: iplus-ineg2
iplus (a, ineg (a)) = 0

THEOREM: iplus-fix-int1
iplus (fix-int (a), b) = iplus (a, b)

THEOREM: iplus-fix-int2
iplus (a, fix-int (b)) = iplus (a, b)

```
; ---------- IDIFFERENCE ----------

;; mostly omitted, but I'll keep a few
```

THEOREM: idifference-fix-int1
idifference (fix-int (a), b) = idifference (a, b)

THEOREM: idifference-fix-int2
idifference (a, fix-int (b)) = idifference (a, b)

```
; ------------------------------------------------------------------------------
; Cancel INEG
; ------------------------------------------------------------------------------

;; We assume that the given term (IPLUS x y) has the property that y has already
;; been reduced and x is not an iplus-term.  So, the only question is whether
;; or not the formal negative of x appears in the fringe of y.

#| The function below has no AND or OR, for efficiency
(defn cancel-ineg-aux (x y)
  ;; returns nil or else a new term provably equal to (IPLUS x y)
  (if (and (listp x)
           (equal (car x) 'ineg))
      (cond
       ((equal y (cadr x))
        ''0)
       ((and (listp y)
             (equal (car y) 'iplus))
        (let ((y1 (cadr y)) (y2 (caddr y)))
          (if (equal y1 (cadr x))
              (list 'fix-int y2)
            (let ((z (cancel-ineg-aux x y2)))
```

```
              (if z
                  (list 'iplus y1 z)
                f)))))
        (t f))
    (cond
     ((nlistp y)
      f)
     ((equal (car y) 'ineg)
      (if (equal x (cadr y))
          ''0
        f))
     ((equal (car y) 'iplus)
      (let ((y1 (cadr y)) (y2 (caddr y)))
        (if (and (listp y1)
                 (equal (car y1) 'ineg)
                 (equal x (cadr y1)))
            (list 'fix-int y2)
          (let ((z (cancel-ineg-aux x y2)))
            (if z
                (list 'iplus y1 z)
              f)))))
     (t f))))
|#
```

DEFINITION:

cancel-ineg-aux $(x,\ y)$

```
=   if listp (x)
    then if car (x) = 'ineg
         then if y = cadr (x)  then ''0
              elseif listp (y)
              then if car (y) = 'iplus
                   then if cadr (y) = cadr (x)
                        then list ('fix-int, caddr (y))
                        elseif cancel-ineg-aux (x, caddr (y))
                        then list ('iplus,
                                   cadr (y),
                                   cancel-ineg-aux (x, caddr (y)))
                        else f endif
                   else f endif
              else f endif
         elseif y ≃ nil  then f
         elseif car (y) = 'ineg
         then if x = cadr (y)  then ''0
```

```
            else f endif
        elseif car (y) = 'iplus
        then if listp (cadr (y))
            then if caadr (y) = 'ineg
                then if x = cadadr (y)
                    then list ('fix-int, caddr (y))
                    elseif cancel-ineg-aux (x, caddr (y))
                    then list ('iplus,
                                cadr (y),
                                cancel-ineg-aux (x, caddr (y)))
                    else f endif
                elseif cancel-ineg-aux (x, caddr (y))
                then list ('iplus, cadr (y), cancel-ineg-aux (x, caddr (y)))
                else f endif
            elseif cancel-ineg-aux (x, caddr (y))
            then list ('iplus, cadr (y), cancel-ineg-aux (x, caddr (y)))
            else f endif
        else f endif
    elseif y ≃ nil then f
    elseif car (y) = 'ineg
    then if x = cadr (y) then ''0
        else f endif
    elseif car (y) = 'iplus
    then if listp (cadr (y))
        then if caadr (y) = 'ineg
            then if x = cadadr (y) then list ('fix-int, caddr (y))
                elseif cancel-ineg-aux (x, caddr (y))
                then list ('iplus, cadr (y), cancel-ineg-aux (x, caddr (y)))
                else f endif
            elseif cancel-ineg-aux (x, caddr (y))
            then list ('iplus, cadr (y), cancel-ineg-aux (x, caddr (y)))
            else f endif
        elseif cancel-ineg-aux (x, caddr (y))
        then list ('iplus, cadr (y), cancel-ineg-aux (x, caddr (y)))
        else f endif
    else f endif

#| The function below has no AND or OR, for efficiency
(defn cancel-ineg (x)
  (if (and (listp x)
           (equal (car x) 'iplus))
      (let ((temp (cancel-ineg-aux (cadr x) (caddr x))))
        (if temp
            temp
```

```
            x))
    x))
|#
```

DEFINITION:
cancel-ineg (x)
$=$ **if** listp (x)
then if car (x) $=$ `'iplus`
then if cancel-ineg-aux (cadr (x), caddr (x))
then cancel-ineg-aux (cadr (x), caddr (x))
else x **endif**
else x **endif**
else x **endif**

```
;; It seems a big win to turn off eval$.  I'll leave the recursive step out in
;; hopes that rewrite-eval$ handles it OK.
```

THEOREM: eval$-list-cons
eval$ (`'list`, cons $(x,\ y)$, a) $=$ cons (eval$ (**t**, x, a), eval$ (`'list`, y, a))

THEOREM: eval$-list-nlistp
$(x \simeq$ **nil**$) \rightarrow$ (eval$ (`'list`, x, a) $=$ **nil**)

THEOREM: eval$-litatom
litatom $(x) \rightarrow$ (eval$ (**t**, x, a) $=$ cdr (assoc $(x,\ a)$))

```
#|
(prove-lemma eval$-quotep (rewrite)
  (equal (eval$ t (list 'quote x) a)
         x))
|#

;; In place of the above I'll do the following, from
;; the naturals library.
```

EVENT: Enable eval$-quote.

THEOREM: eval$-other
$((\neg$ litatom $(x)) \wedge (x \simeq$ **nil**$)) \rightarrow$ (eval$ (**t**, x, a) $= x$)

EVENT: Disable eval$.

```
;; What I'd like to do is say what (eval$ t (cancel-ineg-aux x y) a),
;; but a rewrite rule will loop because of the recursion.  So I
;; introduce a silly auxiliary function so that the opening-up
;; heuristics can help me.  The function body has (listp y) tests
;; so that it can be accepted.
```

DEFINITION:
eval$-cancel-ineg-aux-fn $(x,\ y,\ a)$
$=$ **if** listp $(x) \wedge$ (car (x) = `'ineg`)
then if $y =$ cadr (x) **then** `0`
else let *y1* **be** cadr (y),
y2 **be** caddr (y)
in
if *y1* $=$ cadr (x) **then** fix-int (eval$ (**t**, *y2*, a))
elseif listp (y)
then iplus (eval$ (**t**, *y1*, a),
eval$-cancel-ineg-aux-fn $(x,\ y2,\ a)$)
else `0` **endif endlet endif**
else if car (y) = `'ineg` **then** `0`
else let *y1* **be** cadr (y),
y2 **be** caddr (y)
in
if listp (*y1*)
$\wedge$ (car (*y1*) = `'ineg`)
$\wedge$ (x = cadr (*y1*))
then fix-int (eval$ (**t**, *y2*, a))
elseif listp (y)
then iplus (eval$ (**t**, *y1*, a),
eval$-cancel-ineg-aux-fn ($x$,
y2,
a))
else `0` **endif endlet endif endif**

THEOREM: eval$-cancel-ineg-aux-is-its-fn
(cancel-ineg-aux $(x,\ y) \neq$ **f**)
$\rightarrow$ (eval$ (**t**, cancel-ineg-aux $(x,\ y)$, a) $=$ eval$-cancel-ineg-aux-fn $(x,\ y,\ a)$)

THEOREM: iplus-ineg3
iplus (ineg (x), iplus $(x,\ y)$) $=$ fix-int (y)

THEOREM: iplus-ineg4
iplus $(x$, iplus (ineg (x), $y)$) $=$ fix-int (y)

THEOREM: iplus-ineg-promote
iplus $(y$, ineg (x)) $=$ iplus (ineg (x), $y)$

THEOREM: iplus-x-y-ineg-x
iplus $(x,$ iplus $(y,$ ineg $(x))) =$ fix-int (y)

EVENT: Disable iplus-ineg-promote.

THEOREM: correctness-of-cancel-ineg-aux
(cancel-ineg-aux $(x,\ y) \neq$ **f**)
$\rightarrow$ (eval\$-cancel-ineg-aux-fn $(x,\ y,\ a) =$ iplus (eval\$ (**t**, $x,\ a$), eval\$ (**t**, $y,\ a$)))

THEOREM: correctness-of-cancel-ineg
eval\$ (**t**, $x,\ a$) = eval\$ (**t**, cancel-ineg $(x),\ a$)

EVENT: Disable correctness-of-cancel-ineg-aux.

```
; ------------------------------------------------------------------------------
; Cancel IPLUS
; ------------------------------------------------------------------------------

;; All I do here is cancel like terms from both sides.  The problem of handling
;; INEG cancellation IS handled completely separately above.  That hasn't always
;; been the case -- in my first try I attempted to integrate the operations.
;; But now I see that for things like (equal z (iplus x (iplus y (ineg x))))
;; the integrated approach will fail.  Also, thanks to Matt Wilding, for pointing
;; out that the "four squares" example that Bill Pase sent me ran faster with
;; the newer approach (on his previously-implemented version for the rationals).

#| The function below has no AND or OR, for efficiency
(defn iplus-fringe (x)
  (if (and (listp x)
           (equal (car x)
                  (quote iplus)))
      (append (iplus-fringe (cadr x))
              (iplus-fringe (caddr x)))
      (cons x nil)))
|#
```

DEFINITION:
iplus-fringe (x)
= **if** listp (x)
then if car (x) = 'iplus
then append (iplus-fringe (cadr (x)), iplus-fringe (caddr (x)))
else list (x) **endif**
else list (x) **endif**

THEOREM: lessp-count-listp-cdr
listp (cdr (x)) $\rightarrow$ (count (cdr (x)) $<$ count (x))

DEFINITION:
iplus-tree-rec (l)
= **if** cdr (l) $\simeq$ **nil** **then** car (l)
else list (`'iplus`, car (l), iplus-tree-rec (cdr (l))) **endif**

DEFINITION:
iplus-tree (l)
= **if** listp (l)
then **if** listp (cdr (l)) **then** iplus-tree-rec (l)
else list (`'fix-int`, car (l)) **endif**
else `''0` **endif**

DEFINITION:
iplus-list (x)
= **if** listp (x) **then** iplus (car (x), iplus-list (cdr (x)))
else `0` **endif**

THEOREM: integerp-iplus-list
integerp (iplus-list (x))

THEOREM: eval$-iplus-tree-rec
eval$ (**t**, iplus-tree-rec (x), a)
= **if** listp (x)
then **if** listp (cdr (x)) **then** iplus-list (eval$ (`'list`, x, a))
else eval$ (**t**, car (x), a) **endif**
else `0` **endif**

THEOREM: eval$-iplus-tree
eval$ (**t**, iplus-tree (x), a) = iplus-list (eval$ (`'list`, x, a))

THEOREM: eval$-list-append
eval$ (`'list`, append (x, y), a)
= append (eval$ (`'list`, x, a), eval$ (`'list`, y, a))

```
#| The function below has no AND or OR, for efficiency
(defn cancel-iplus (x)
  (if (and (listp x)
           (equal (car x) (quote equal)))
      (if (and (listp (cadr x))
               (equal (caadr x) (quote iplus))
               (listp (caddr x))
               (equal (caaddr x) (quote iplus)))
```

```
          (let ((xs (iplus-fringe (cadr x)))
                (ys (iplus-fringe (caddr x))))
            (let ((bagint (bagint xs ys)))
              (if (listp bagint)
                  (list (quote equal)
                        (iplus-tree (bagdiff xs bagint))
                        (iplus-tree (bagdiff ys bagint)))
                x)))
        (if (and (listp (cadr x))
                 (equal (caadr x) (quote iplus))
                 ;; We don't want to introduce the IF below unless something
                 ;; is "gained", or else we may get into an infinite rewriting loop.
                 (member (caddr x) (iplus-fringe (cadr x))))
            (list (quote if)
                  (list (quote integerp) (caddr x))
                  (list (quote equal)
                        (iplus-tree (delete (caddr x) (iplus-fringe (cadr x))))
                        ''0)
                  (list (quote quote) f))
          (if (and (listp (caddr x))
                   (equal (caaddr x) (quote iplus))
                   (member (cadr x) (iplus-fringe (caddr x))))
              (list (quote if)
                    (list (quote integerp) (cadr x))
                    (list (quote equal)
                          ''0
                          (iplus-tree (delete (cadr x) (iplus-fringe (caddr x)))))
                    (list (quote quote) f))
            x)))
    x))
|#
```

DEFINITION:
cancel-iplus (x)
$=$ **if** listp (x)
then if car (x) = `'equal`
then if listp (cadr (x))
then if caadr (x) = `'iplus`
then if listp (caddr (x))
then if caaddr (x) = `'iplus`
then if listp (bagint (iplus-fringe (cadr (x)),
iplus-fringe (caddr (x))))
then list (`'equal`,

```
                                iplus-tree (bagdiff (iplus-fringe (cadr (x)),
                                                bagint (iplus-fringe (cadr (x)),
                                                        iplus-fringe (caddr (x))))),
                                iplus-tree (bagdiff (iplus-fringe (caddr (x)),
                                                bagint (iplus-fringe (cadr (x)),
                                                        iplus-fringe (caddr (x))))))
                        else x endif
                elseif caddr (x) ∈ iplus-fringe (cadr (x))
                then list ('if,
                        list ('integerp, caddr (x)),
                        cons ('equal,
                                cons (iplus-tree (delete (caddr (x),
                                                        iplus-fringe (cadr (x)))),
                                        '('0))),
                        list ('quote, f))
                else x endif
            elseif caddr (x) ∈ iplus-fringe (cadr (x))
            then list ('if,
                    list ('integerp, caddr (x)),
                    cons ('equal,
                        cons (iplus-tree (delete (caddr (x),
                                                iplus-fringe (cadr (x)))),
                                '('0))),
                    list ('quote, f))
            else x endif
        elseif listp (caddr (x))
        then if caaddr (x) = 'iplus
            then if cadr (x) ∈ iplus-fringe (caddr (x))
                then list ('if,
                        list ('integerp, cadr (x)),
                        list ('equal,
                            ''0,
                            iplus-tree (delete (cadr (x),
                                                iplus-fringe (caddr (x))))),
                        list ('quote, f))
                else x endif
            else x endif
        else x endif
    elseif listp (caddr (x))
    then if caaddr (x) = 'iplus
        then if cadr (x) ∈ iplus-fringe (caddr (x))
            then list ('if,
                    list ('integerp, cadr (x)),
                    list ('equal,
```

```
                                        ''0,
                                        iplus-tree (delete (cadr (x),
                                                            iplus-fringe (caddr (x))))),
                                    list ('quote, f))
                            else x endif
                        else x endif
                    else x endif
                else x endif
        else x endif
```

THEOREM: eval$-cancel-iplus

```
eval$ (t, cancel-iplus (x), a)
=   if listp (x) ∧ (car (x) = 'equal)
    then if listp (cadr (x))
            ∧   (caadr (x) = 'iplus)
            ∧   listp (caddr (x))
            ∧   (caaddr (x) = 'iplus)
         then let xs  be  iplus-fringe (cadr (x)),
                  ys  be  iplus-fringe (caddr (x))
              in
              let bagint  be  bagint (xs, ys)
              in
              if listp (bagint)
              then iplus-list (eval$ ('list,
                                      bagdiff (xs,
                                               bagint (xs, ys)),
                                      a))
                   =   iplus-list (eval$ ('list,
                                          bagdiff (ys,
                                                   bagint (xs,
                                                           ys)),
                                          a))
              else eval$ (t, x, a) endif endlet endlet
         elseif listp (cadr (x))
              ∧   (caadr (x) = 'iplus)
              ∧   (caddr (x) ∈ iplus-fringe (cadr (x)))
         then if integerp (eval$ (t, caddr (x), a))
              then iplus-list (eval$ ('list,
                                      delete (caddr (x), iplus-fringe (cadr (x))),
                                      a))
                   =   0
              else f endif
         elseif listp (caddr (x))
              ∧   (caaddr (x) = 'iplus)
```

```
            ∧   (cadr (x) ∈ iplus-fringe (caddr (x)))
        then if integerp (eval$ (t, cadr (x), a))
            then 0 = iplus-list (eval$ ('list,
                                        delete (cadr (x),
                                                iplus-fringe (caddr (x))),
                                        a))
            else f endif
        else eval$ (t, x, a) endif
    else eval$ (t, x, a) endif
```

EVENT: Disable cancel-iplus.

THEOREM: eval$-iplus-list-delete
$(z \in y)$
$\rightarrow$ (iplus-list (eval$ ('list, delete (z, y), a))
$=$ idifference (iplus-list (eval$ ('list, y, a)), eval$ (t, z, a)))

THEOREM: eval$-iplus-list-bagdiff
subbagp (x, y)
$\rightarrow$ (iplus-list (eval$ ('list, bagdiff (y, x), a))
$=$ idifference (iplus-list (eval$ ('list, y, a)),
iplus-list (eval$ ('list, x, a))))

THEOREM: iplus-list-append
iplus-list (append (x, y)) $=$ iplus (iplus-list (x), iplus-list (y))

EVENT: Disable iplus-tree.

```
;; because we want to use EVAL$-IPLUS-TREE for now
```

THEOREM: not-integerp-implies-not-equal-iplus
$(\neg$ integerp $(a)) \rightarrow ((a =$ iplus $(b, c)) =$ f)

THEOREM: iplus-list-eval$-fringe
iplus-list (eval$ ('list, iplus-fringe (x), a)) $=$ fix-int (eval$ (t, x, a))

```
;; The following two lemmas aren't needed but they sure do
;; shorten the total proof time!!!
```

THEOREM: iplus-ineg5-lemma-1
integerp (x)
$\rightarrow$ $((x =$ iplus $(y,$ iplus (ineg (z), $w)))$
$=$ $(x =$ iplus (ineg (z), iplus $(y, w))))$

THEOREM: iplus-ineg5-lemma-2
(integerp (x) $\wedge$ integerp (v))
$\rightarrow$ $((x = \text{iplus}(\text{ineg}(z), v)) = (\text{iplus}(x, z) = v))$

THEOREM: iplus-ineg5
integerp (x)
$\rightarrow$ $((x = \text{iplus}(y, \text{iplus}(\text{ineg}(z), w))) = (\text{iplus}(x, z) = \text{iplus}(y, w)))$

EVENT: Disable iplus-ineg5-lemma-1.

EVENT: Disable iplus-ineg5-lemma-2.

THEOREM: iplus-ineg6
integerp (x)
$\rightarrow$ $((x = \text{iplus}(y, \text{iplus}(w, \text{ineg}(z)))) = (\text{iplus}(x, z) = \text{iplus}(y, w)))$

THEOREM: eval$-iplus
(listp (x) $\wedge$ (car (x) = `'iplus`))
$\rightarrow$ (eval$ (**t**, x, a) = iplus (eval$ (**t**, cadr (x), a), eval$ (**t**, caddr (x), a)))

THEOREM: iplus-ineg7
(`0` = iplus $(x$, ineg $(y)))$ = (fix-int (y) = fix-int (x))

THEOREM: correctness-of-cancel-iplus
eval$ (**t**, x, a) = eval$ (**t**, cancel-iplus (x), a)

EVENT: Disable iplus-ineg5.

EVENT: Disable iplus-ineg6.

```
; ------------------------------------------------------------------------------
; Cancel IPLUS from ILESSP
; ------------------------------------------------------------------------------

;; This is similar to the cancellation of IPLUS terms from equalities,
;; handled above, and uses many of the same lemmas.  A small but definite
;; difference however is that for ILESSP we don't have to fix integers.

;; By luck we have that iplus-tree-rec is appropriate here, since
;; the lemma eval$-iplus-tree-rec shows that it (accidentally) behaves
;; properly on the empty list.
```

THEOREM: ilessp-fix-int-1
ilessp (fix-int (x), y) = ilessp (x, y)

THEOREM: ilessp-fix-int-2
ilessp (x, fix-int (y)) = ilessp (x, y)

```
;; Perhaps the easiest approach is to do everything with respect to the
;; same IPLUS-TREE function that we used before, and then once the
;; supposed meta-lemma is proved, go back and show that we get the
;; same answer if we use a version that doesn't fix-int singleton fringes.
```

DEFINITION:
make-cancel-iplus-inequality-1 (x, y)
= list ('ilessp,
    iplus-tree (bagdiff (x, bagint (x, y))),
    iplus-tree (bagdiff (y, bagint (x, y))))

```
#| The function below has no AND or OR, for efficiency
(defn cancel-iplus-ilessp-1 (x)
  (if (and (listp x)
           (equal (car x) (quote ilessp)))
      (make-cancel-iplus-inequality-1 (iplus-fringe (cadr x))
                                      (iplus-fringe (caddr x)))
    x))
|#
```

DEFINITION:
cancel-iplus-ilessp-1 (x)
= **if** listp (x)
  then if car (x) = 'ilessp
    then make-cancel-iplus-inequality-1 (iplus-fringe (cadr (x)),
                iplus-fringe (caddr (x)))
    else x **endif**
  else x **endif**

```
;; Notice that IPLUS-TREE-NO-FIX-INT is currently enabled, which is
;; good since we want to use EVAL$-IPLUS-TREE-NO-FIX-INT for now.
```

THEOREM: lessp-difference-plus-arg1
$(w < ((w + y) - x)) = (x < y)$

THEOREM: lessp-difference-plus-arg1-commuted
$(w < ((y + w) - x)) = (x < y)$

THEOREM: iplus-cancellation-1-for-ilessp
ilessp (iplus (a, b), iplus (a, c)) = ilessp (b, c)

THEOREM: iplus-cancellation-2-for-ilessp
ilessp (iplus (b, a), iplus (c, a)) = ilessp (b, c)

THEOREM: correctness-of-cancel-iplus-ilessp-lemma
eval\$ (**t**, x, a) = eval\$ (**t**, cancel-iplus-ilessp-1 (x), a)

DEFINITION:
iplus-tree-no-fix-int (l)
= **if** listp (l) **then** iplus-tree-rec (l)
else ''0 **endif**

THEOREM: eval\$-ilessp-iplus-tree-no-fix-int
ilessp (eval\$ (**t**, iplus-tree-no-fix-int (x), a),
eval\$ (**t**, iplus-tree-no-fix-int (y), a))
= ilessp (eval\$ (**t**, iplus-tree (x), a), eval\$ (**t**, iplus-tree (y), a))

EVENT: Disable iplus-tree-no-fix-int.

THEOREM: make-cancel-iplus-inequality-simplifier
eval\$ (**t**, make-cancel-iplus-inequality-1 (x, y), a)
= eval\$ (**t**,
list ('ilessp,
iplus-tree-no-fix-int (bagdiff (x, bagint (x, y))),
iplus-tree-no-fix-int (bagdiff (y, bagint (x, y)))),
a)

```
#| The function below has no AND or OR, for efficiency
(defn cancel-iplus-ilessp (x)
  (if (and (listp x)
           (equal (car x) (quote ilessp)))
      (let ((x1 (iplus-fringe (cadr x)))
            (y1 (iplus-fringe (caddr x))))
        (let ((bagint (bagint x1 y1)))
          (if (listp bagint)
              ;; I check (listp bagint) only for efficiency
              (list (quote ilessp)
                    (iplus-tree-no-fix-int (bagdiff x1 bagint))
                    (iplus-tree-no-fix-int (bagdiff y1 bagint)))
            x)))
    x))
|#
```

```
;; **** Should perhaps check that some argument of the ILESSP has function
;; symbol IPLUS, or else we may wind up dealing with (ILESSP 0 0).  That should
;; be harmless enough, though, even if *1*IPLUS is disabled; we'll just get the
;; same term back, the hard way.
```

DEFINITION:
cancel-iplus-ilessp (x)
= **if** listp (x)
  then if car (x) = `'ilessp`
    then if listp (bagint (iplus-fringe (cadr (x)),
                iplus-fringe (caddr (x))))
      then list (`'ilessp`,
          iplus-tree-no-fix-int (bagdiff (iplus-fringe (cadr (x)),
                bagint (iplus-fringe (cadr (x)),
                iplus-fringe (caddr (x))))),
          iplus-tree-no-fix-int (bagdiff (iplus-fringe (caddr (x)),
                bagint (iplus-fringe (cadr (x)),
                iplus-fringe (caddr (x))))))
      else x **endif**
    else x **endif**
  else x **endif**

EVENT: Disable make-cancel-iplus-inequality-1.

THEOREM: correctness-of-cancel-iplus-ilessp
eval\$ (**t**, x, a) = eval\$ (**t**, cancel-iplus-ilessp (x), a)

```
; ---------- Multiplication ----------
```

THEOREM: itimes-zero1
(fix-int (x) = 0) → (itimes (x, y) = 0)

THEOREM: itimes-0-left
itimes (0, y) = 0

```
;; I don't want the backchaining to slow down the prover.
```

EVENT: Disable itimes-zero1.

THEOREM: itimes-zero2
(fix-int (y) = 0) → (itimes (x, y) = 0)

THEOREM: itimes-0-right
itimes $(x,\ 0) = 0$

```
;; I don't want the backchaining to slow down the prover.
```

EVENT: Disable itimes-zero2.

THEOREM: itimes-fix-int1
itimes (fix-int $(a),\ b)$ = itimes $(a,\ b)$

THEOREM: itimes-fix-int2
itimes $(a,$ fix-int $(b))$ = itimes $(a,\ b)$

THEOREM: commutativity-of-itimes
itimes $(x,\ y)$ = itimes $(y,\ x)$

THEOREM: itimes-distributes-over-iplus-proof
itimes $(x,$ iplus $(y,\ z))$ = iplus (itimes $(x,\ y)$, itimes $(x,\ z))$

THEOREM: itimes-distributes-over-iplus
(itimes $(x,$ iplus $(y,\ z))$ = iplus (itimes $(x,\ y)$, itimes $(x,\ z)))$
$\wedge$ (itimes (iplus $(x,\ y),\ z)$ = iplus (itimes $(x,\ z)$, itimes $(y,\ z)))$

THEOREM: commutativity2-of-itimes
itimes $(x,$ itimes $(y,\ z))$ = itimes $(y,$ itimes $(x,\ z))$

THEOREM: associativity-of-itimes
itimes (itimes $(x,\ y),\ z)$ = itimes $(x,$ itimes $(y,\ z))$

THEOREM: equal-itimes-0
(itimes $(x,\ y) = 0)$ = ((fix-int $(x) = 0) \vee$ (fix-int $(y) = 0))$

THEOREM: equal-itimes-1
(itimes $(a,\ b) = 1)$
= $(((a = 1) \wedge (b = 1)) \vee ((a = -1) \wedge (b = -1)))$

THEOREM: equal-itimes-minus-1
(itimes $(a,\ b) = -1)$
= $(((a = -1) \wedge (b = 1)) \vee ((a = 1) \wedge (b = -1)))$

THEOREM: itimes-1-arg1
itimes $(1,\ x)$ = fix-int (x)

```
; ---------- Division ----------
```

THEOREM: quotient-remainder-uniqueness
$((a = (r + (b * q))) \wedge (r < b))$
$\rightarrow \quad ((\text{fix}\,(r) = (a \textbf{ mod } b)) \wedge (\text{fix}\,(q) = (a \div b)))$

```
; We want to define IQUOTIENT and IREMAINDER. The standard approach to
; integer division derives from from the following theorem.
;
; Division Theorem:
; For all integers i,j, j not 0, there exist unique integers q and r
; which satisfy  i = jq + r,  0 <= r < |j|.
;
; The functions IQUOTIENT and IREMAINDER are intended to compute q and r.
; Therefore, to be satisfied that we have the right definitions, we must
; prove the above theorem.
```

THEOREM: division-theorem-part1
$\text{integerp}\,(i) \rightarrow (\text{iplus}\,(\text{iremainder}\,(i, j), \text{itimes}\,(j, \text{iquotient}\,(i, j))) = i)$

THEOREM: division-theorem-part2
$(\text{integerp}\,(j) \wedge (j \neq 0)) \rightarrow (\neg\ \text{ilessp}\,(\text{iremainder}\,(i, j), 0))$

THEOREM: division-theorem-part3
$(\text{integerp}\,(j) \wedge (j \neq 0)) \rightarrow \text{ilessp}\,(\text{iremainder}\,(i, j), \text{iabs}\,(j))$

THEOREM: division-theorem
$(\text{integerp}\,(i) \wedge \text{integerp}\,(j) \wedge (j \neq 0))$
$\rightarrow \quad ((\text{iplus}\,(\text{iremainder}\,(i, j), \text{itimes}\,(j, \text{iquotient}\,(i, j))) = i)$
$\quad \wedge \quad (\neg\ \text{ilessp}\,(\text{iremainder}\,(i, j), 0))$
$\quad \wedge \quad \text{ilessp}\,(\text{iremainder}\,(i, j), \text{iabs}\,(j)))$

THEOREM: quotient-difference-lessp-arg2
$(((a \textbf{ mod } c) = 0) \wedge (b < c))$
$\rightarrow \quad (((a - b) \div c)$
$\quad = \quad \textbf{if } b \simeq 0 \textbf{ then } a \div c$
$\quad\quad \textbf{elseif } b < a \textbf{ then } (a \div c) - (1 + (b \div c))$
$\quad\quad \textbf{else } 0 \textbf{ endif})$

THEOREM: iquotient-iremainder-uniqueness
$(\text{integerp}\,(i)$
$\wedge \quad \text{integerp}\,(j)$
$\wedge \quad \text{integerp}\,(r)$
$\wedge \quad \text{integerp}\,(q)$
$\wedge \quad (j \neq 0)$
$\wedge \quad (i = \text{iplus}\,(r, \text{itimes}\,(j, q)))$

$\wedge$ $(\neg$ ilessp $(r, 0))$
$\wedge$ ilessp $(r,$ iabs $(j)))$
$\rightarrow$ $((r =$ iremainder $(i, j)) \wedge (q =$ iquotient $(i, j)))$

```
; It turns out that in computer arithmetic, notions of division other than that
; given by the division theorem are used. Two in particular, called
; "truncate towards negative infinity" and "truncate towards zero" are common.
; We present their definitions here.

; Division Theorem (truncate towards negative infinity variant):
;
; For all integers i,j, j not 0, there exist unique integers q and r
; which satisfy
;                i = jq + r,  0 <= r <  j  (j > 0)
;                             j <  r <= 0  (j < 0)
;
; In this version the integer quotient of two integers is the integer floor
; of the real quotient of the integers. The remainder has the sign of the
; divisor. The functions IDIV and IMOD are intended to compute q and r.
; Therefore, to be satisfied that we have the right definitions, we must
; prove the above theorem.
```

THEOREM: division-theorem-for-truncate-to-neginf-part1
integerp $(i) \rightarrow$ (iplus (imod (i, j), itimes $(j,$ idiv $(i, j))) = i)$

THEOREM: division-theorem-for-truncate-to-neginf-part2
ilessp $(0, j) \rightarrow ((\neg$ ilessp (imod $(i, j), 0)) \wedge$ ilessp (imod $(i, j), j))$

THEOREM: division-theorem-for-truncate-to-neginf-part3
(integerp $(j) \wedge$ ilessp $(j, 0))$
$\rightarrow$ $((\neg$ ilessp $(0,$ imod $(i, j))) \wedge$ ilessp $(j,$ imod $(i, j)))$

THEOREM: division-theorem-for-truncate-to-neginf
(integerp $(i) \wedge$ integerp $(j) \wedge (j \neq 0))$
$\rightarrow$ ((iplus (imod (i, j), itimes $(j,$ idiv $(i, j))) = i)$
$\wedge$ **if** ilessp $(0, j)$
then $(\neg$ ilessp (imod $(i, j), 0)) \wedge$ ilessp (imod $(i, j), j)$
else $(\neg$ ilessp $(0,$ imod $(i, j)))$
$\wedge$ ilessp $(j,$ imod $(i, j))$ **endif**)

THEOREM: idiv-imod-uniqueness
(integerp (i)
$\wedge$ integerp (j)
$\wedge$ integerp (r)

$\wedge$ integerp (q)
$\wedge$ $(j \neq 0)$
$\wedge$ $(i = \text{iplus}(r, \text{itimes}(j, q)))$
$\wedge$ **if** ilessp $(0, j)$ **then** $(\neg$ ilessp $(r, 0)) \wedge$ ilessp (r, j)
else $(\neg$ ilessp $(0, r)) \wedge$ ilessp (j, r) **endif**)
$\rightarrow$ $((r = \text{imod}(i, j)) \wedge (q = \text{idiv}(i, j)))$

```
; Division Theorem (truncate towards zero variant):
;
; For all integers i,j, j not 0, there exist unique integers q and r
; which satisfy
;                i = jq + r,     0 <=  r  <  |j|  (i => 0)
;                             -|j| <   r  <= 0    (i < 0)
;
; In this version (iquo, irem), the integer quotient of two integers is the integer floor
; of the real quotient of the integers, if the real quotient is positive. If the
; real quotient is negative, the integer quotient is the integer ceiling of the
; real quotient. The remainder has the sign of the dividend. The functions IQUO
; and IREM are intended to compute q and r. Therefore, to be satisfied that we
; have the right definitions, we must prove the above theorem.
```

THEOREM: division-theorem-for-truncate-to-zero-part1
integerp $(i) \rightarrow (\text{iplus}(\text{irem}(i, j), \text{itimes}(j, \text{iquo}(i, j))) = i)$

THEOREM: division-theorem-for-truncate-to-zero-part2
(integerp $(i) \wedge$ integerp $(j) \wedge (j \neq 0) \wedge (\neg$ ilessp $(i, 0)))$
$\rightarrow$ $((\neg$ ilessp $(\text{irem}(i, j), 0)) \wedge$ ilessp $(\text{irem}(i, j), \text{iabs}(j)))$

THEOREM: division-theorem-for-truncate-to-zero-part3
(integerp $(i) \wedge$ integerp $(j) \wedge (j \neq 0) \wedge$ ilessp $(i, 0))$
$\rightarrow$ $((\neg$ ilessp $(0, \text{irem}(i, j))) \wedge$ ilessp $(\text{ineg}(\text{iabs}(j)), \text{irem}(i, j)))$

THEOREM: division-theorem-for-truncate-to-zero
(integerp $(i) \wedge$ integerp $(j) \wedge (j \neq 0))$
$\rightarrow$ $((\text{iplus}(\text{irem}(i, j), \text{itimes}(j, \text{iquo}(i, j))) = i)$
$\wedge$ **if** $\neg$ ilessp $(i, 0)$
then $(\neg$ ilessp $(\text{irem}(i, j), 0))$
$\wedge$ ilessp $(\text{irem}(i, j), \text{iabs}(j))$
else $(\neg$ ilessp $(0, \text{irem}(i, j)))$
$\wedge$ ilessp $(\text{ineg}(\text{iabs}(j)), \text{irem}(i, j))$ **endif**)

THEOREM: iquo-irem-uniqueness
(integerp (i)
$\wedge$ integerp (j)

$\wedge$ integerp (r)
$\wedge$ integerp (q)
$\wedge$ $(j \neq 0)$
$\wedge$ $(i = \text{iplus}(r, \text{itimes}(j, q)))$
$\wedge$ **if** $\neg$ ilessp $(i, 0)$ **then** $(\neg$ ilessp $(r, 0)) \wedge$ ilessp $(r,$ iabs $(j))$
else $(\neg$ ilessp $(0, r)) \wedge$ ilessp $(\text{ineg}(\text{iabs}(j)), r)$ **endif**)
$\rightarrow$ $((r = \text{irem}(i, j)) \wedge (q = \text{iquo}(i, j)))$

```
; ---------- Multiplication Facts
```

THEOREM: itimes-ineg-1
itimes (ineg (x), y) = ineg (itimes (x, y))

THEOREM: itimes-ineg-2
itimes $(x,$ ineg $(y))$ = ineg (itimes (x, y))

THEOREM: itimes-cancellation-1
(itimes (a, b) = itimes (a, c))
= ((fix-int $(a) = 0) \vee$ (fix-int (b) = fix-int $(c)))$

THEOREM: itimes-cancellation-2
(itimes (b, a) = itimes (c, a))
= ((fix-int $(a) = 0) \vee$ (fix-int (b) = fix-int $(c)))$

THEOREM: itimes-cancellation-3
(itimes (a, b) = itimes (c, a))
= ((fix-int $(a) = 0) \vee$ (fix-int (b) = fix-int $(c)))$

```
; ---------- Division Facts
```

THEOREM: integerp-iquotient
integerp (iquotient (i, j))

THEOREM: integerp-iremainder
integerp (iremainder (i, j))

THEOREM: integerp-idiv
integerp (idiv (i, j))

THEOREM: integerp-imod
integerp (imod (i, j))

THEOREM: integerp-iquo
integerp (iquo (i, j))

THEOREM: integerp-irem
integerp (irem (i, j))

THEOREM: iquotient-fix-int1
iquotient (fix-int (i), j) = iquotient (i, j)

THEOREM: iquotient-fix-int2
iquotient (i, fix-int (j)) = iquotient (i, j)

THEOREM: iremainder-fix-int1
iremainder (fix-int (i), j) = iremainder (i, j)

THEOREM: iremainder-fix-int2
iremainder (i, fix-int (j)) = iremainder (i, j)

THEOREM: idiv-fix-int1
idiv (fix-int (i), j) = idiv (i, j)

THEOREM: idiv-fix-int2
idiv (i, fix-int (j)) = idiv (i, j)

THEOREM: imod-fix-int1
imod (fix-int (i), j) = imod (i, j)

THEOREM: imod-fix-int2
imod (i, fix-int (j)) = imod (i, j)

THEOREM: iquo-fix-int1
iquo (fix-int (i), j) = iquo (i, j)

THEOREM: iquo-fix-int2
iquo (i, fix-int (j)) = iquo (i, j)

THEOREM: irem-fix-int1
irem (fix-int (i), j) = irem (i, j)

THEOREM: irem-fix-int2
irem (i, fix-int (j)) = irem (i, j)

THEOREM: fix-int-iquotient
fix-int (iquotient (i, j)) = iquotient (i, j)

THEOREM: fix-int-iremainder
fix-int (iremainder (i, j)) = iremainder (i, j)

THEOREM: fix-int-idiv
fix-int (idiv (i, j)) = idiv (i, j)

THEOREM: fix-int-imod
fix-int (imod (i, j)) = imod (i, j)

THEOREM: fix-int-iquo
fix-int (iquo (i, j)) = iquo (i, j)

THEOREM: fix-int-irem
fix-int (irem (i, j)) = irem (i, j)

EVENT: Disable iquotient.

EVENT: Disable iremainder.

EVENT: Disable idiv.

EVENT: Disable imod.

EVENT: Disable iquo.

EVENT: Disable irem.

```
; ---------- Meta lemma for itimes cancellation

;; I tried to adapt this somewhat from corresponding meta lemmas in
;; naturals library, but it seemed to get hairy.  So instead I'll try
;; to parallel the development I gave for IPLUS.  I'll be lazier here
;; about efficiency, so I'll use a completely analogous definition of
;; itimes-tree.  Notice that I've avoided the IZEROP-TREE approach
;; from the naturals version, in that I simply create the appropriate
;; common fringe into a product and say that this product is non-zero
;; when dividing both sides by it.  It can then be up to the user whether
;; or not to enable the (meta or rewrite) rule that says that izerop of a product reduces
;; to the disjunction of izerop of the factors.

#| The function below has no AND or OR, for efficiency
(defn itimes-fringe (x)
  (if (and (listp x)
           (equal (car x)
                  (quote itimes)))
      (append (itimes-fringe (cadr x))
              (itimes-fringe (caddr x)))
```

```
      (cons x nil)))
|#
```

DEFINITION:
itimes-fringe (x)
$=$ **if** listp (x)
then if car (x) $=$ `'itimes`
then append (itimes-fringe (cadr (x)), itimes-fringe (caddr (x)))
else list (x) **endif**
else list (x) **endif**

DEFINITION:
itimes-tree-rec (l)
$=$ **if** cdr (l) $\simeq$ **nil** **then** car (l)
else list (`'itimes`, car (l), itimes-tree-rec (cdr (l))) **endif**

DEFINITION:
itimes-tree (l)
$=$ **if** listp (l)
then if listp (cdr (l)) **then** itimes-tree-rec (l)
else list (`'fix-int`, car (l)) **endif**
else `''1` **endif**

DEFINITION:
itimes-list (x)
$=$ **if** listp (x) **then** itimes (car (x), itimes-list (cdr (x)))
else `1` **endif**

THEOREM: integerp-itimes-list
integerp (itimes-list (x))

THEOREM: eval\$-itimes-tree-rec
listp (x)
$\rightarrow$ (eval\$ (**t**, itimes-tree-rec (x), a)
$=$ **if** listp (cdr (x)) **then** itimes-list (eval\$ (`'list`, x, a))
else eval\$ (**t**, car (x), a) **endif**)

```
;; The following allows us to pretty much ignore itimes-tree forever.  (Notice
;; that it is disabled immediately below.)
```

THEOREM: eval\$-itimes-tree
eval\$ (**t**, itimes-tree (x), a) $=$ itimes-list (eval\$ (`'list`, x, a))

EVENT: Disable itimes-tree.

```
;; because we want to use EVAL$-ITIMES-TREE for now
```

DEFINITION:
make-cancel-itimes-equality (x, y, *in-both*)
= list ('`if`,
list ('`equal`, itimes-tree (*in-both*), ''`0`),
list ('`quote`, **t**),
list ('`equal`,
itimes-tree (bagdiff (x, *in-both*)),
itimes-tree (bagdiff (y, *in-both*))))

```
#| The function below has no AND or OR, for efficiency
(defn cancel-itimes (x)
  (if (and (listp x)
           (equal (car x) (quote equal)))
      (if (and (listp (cadr x))
               (equal (caadr x) (quote itimes))
               (listp (caddr x))
               (equal (caaddr x) (quote itimes)))
          (if (listp (bagint (itimes-fringe (cadr x)) (itimes-fringe (caddr x))))
              (make-cancel-itimes-equality (itimes-fringe (cadr x))
                                           (itimes-fringe (caddr x))
                                           (bagint (itimes-fringe (cadr x)) (itimes-fringe
            x)
        (if (and (listp (cadr x))
                 (equal (caadr x) (quote itimes)))
            ;; We don't want to introduce the IF below unless something
            ;; is "gained", or else we may get into an infinite rewriting loop.
            (if (member (caddr x) (itimes-fringe (cadr x)))
                (list (quote if)
                      (list (quote integerp) (caddr x))
                      (make-cancel-itimes-equality (itimes-fringe (cadr x))
                                                   (list (caddr x))
                                                   (list (caddr x)))
                      (list (quote quote) f))
              x)
          (if (and (listp (caddr x))
                   (equal (caaddr x) (quote itimes)))
              (if (member (cadr x) (itimes-fringe (caddr x)))
                  (list (quote if)
                        (list (quote integerp) (cadr x))
                        (make-cancel-itimes-equality (list (cadr x))
                                                     (itimes-fringe (caddr x))
```

```
                                                        (list (cadr x)))
                        (list (quote quote) f))
                x)
            x)))
    x))
|#
```

DEFINITION:

```
cancel-itimes (x)
=   if listp (x)
    then if car (x) = 'equal
         then if listp (cadr (x))
              then if caadr (x) = 'itimes
                   then if listp (caddr (x))
                        then if caaddr (x) = 'itimes
                             then if listp (bagint (itimes-fringe (cadr (x)),
                                                    itimes-fringe (caddr (x))))
                                  then make-cancel-itimes-equality (itimes-fringe (cadr (x)),
                                                                    itimes-fringe (caddr (x)),
                                                                    bagint (itimes-fringe (cadr (x)),
                                                                            itimes-fringe (caddr (x))))
                                  else x endif
                             elseif caddr (x) ∈ itimes-fringe (cadr (x))
                             then list ('if,
                                        list ('integerp, caddr (x)),
                                        make-cancel-itimes-equality (itimes-fringe (cadr (x)),
                                                                     list (caddr (x)),
                                                                     list (caddr (x))),
                                        list ('quote, f))
                             else x endif
                        elseif caddr (x) ∈ itimes-fringe (cadr (x))
                        then list ('if,
                                   list ('integerp, caddr (x)),
                                   make-cancel-itimes-equality (itimes-fringe (cadr (x)),
                                                                list (caddr (x)),
                                                                list (caddr (x))),
                                   list ('quote, f))
                        else x endif
                   elseif listp (caddr (x))
                   then if caaddr (x) = 'itimes
                        then if cadr (x) ∈ itimes-fringe (caddr (x))
                             then list ('if,
                                        list ('integerp, cadr (x)),
```

```
                                        make-cancel-itimes-equality (list (cadr (x)),
                                                                         itimes-fringe (caddr (x)),
                                                                         list (cadr (x))),
                                        list ('quote, f))
                                else x endif
                            else x endif
                        else x endif
                    elseif listp (caddr (x))
                    then if caaddr (x) = 'itimes
                        then if cadr (x) ∈ itimes-fringe (caddr (x))
                            then list ('if,
                                    list ('integerp, cadr (x)),
                                    make-cancel-itimes-equality (list (cadr (x)),
                                                                     itimes-fringe (caddr (x)),
                                                                     list (cadr (x))),
                                    list ('quote, f))
                            else x endif
                        else x endif
                    else x endif
                else x endif
            else x endif
```

THEOREM: itimes-list-append
itimes-list (append (x, y)) = itimes (itimes-list (x), itimes-list (y))

THEOREM: itimes-list-eval$-fringe
itimes-list (eval$ ('list, itimes-fringe (x), a)) = fix-int (eval$ (t, x, a))

THEOREM: integerp-eval$-itimes
(car (x) = 'itimes) → integerp (eval$ (t, x, a))

THEOREM: not-integerp-implies-not-equal-itimes
(¬ integerp (a)) → ((a = itimes (b, c)) = f)

THEOREM: itimes-list-eval$-delete
(z ∈ y)
→ (itimes-list (eval$ ('list, y, a))
= itimes (eval$ (t, z, a), itimes-list (eval$ ('list, delete (z, y), a))))

THEOREM: itimes-list-bagdiff
subbagp (x, y)
→ (itimes-list (eval$ ('list, y, a))
= itimes (itimes-list (eval$ ('list, bagdiff (y, x), a)),
itimes-list (eval$ ('list, x, a))))

THEOREM: equal-itimes-list-eval$-list-delete
$((c \in y) \wedge (\text{fix-int}\,(\text{eval\$}\,(\mathbf{t},\ c,\ a)) \neq \mathtt{0}))$
$\rightarrow\ ((x = \text{itimes-list}\,(\text{eval\$}\,(\mathtt{'list},\ \text{delete}\,(c,\ y),\ a)))$
$=\ (\text{integerp}\,(x)$
$\wedge\ (\text{itimes}\,(x,\ \text{eval\$}\,(\mathbf{t},\ c,\ a))$
$=\ \text{itimes-list}\,(\text{eval\$}\,(\mathtt{'list},\ y,\ a)))))$

EVENT: Disable itimes-list-eval$-delete.

```
;; I had trouble with the clausifier (thanks, J, for pointing that out
;; as the source of my trouble) in the proof of the meta lemma -- it's
;; getting rid of a case split.  So, I'll proceed by reducing
;; cancel-itimes in each case; see lemma eval$-make-cancel-itimes-equality
;; (and its -1 and -2 versions).
```

THEOREM: member-append
$(a \in \text{append}\,(x,\ y)) = ((a \in x) \vee (a \in y))$

THEOREM: member-izerop-itimes-fringe
$((z \in \text{itimes-fringe}\,(x)) \wedge (\text{fix-int}\,(\text{eval\$}\,(\mathbf{t},\ z,\ a)) = \mathtt{0}))$
$\rightarrow\ (\text{fix-int}\,(\text{eval\$}\,(\mathbf{t},\ x,\ a)) = \mathtt{0})$

THEOREM: correctness-of-cancel-itimes-hack-1
$((w \in \text{itimes-fringe}\,(\text{cons}\,(\mathtt{'itimes},\ \mathit{x1})))$
$\wedge\ (\text{fix-int}\,(\text{eval\$}\,(\mathbf{t},\ w,\ a)) = \mathtt{0})$
$\wedge\ (\text{fix-int}\,(\text{eval\$}\,(\mathbf{t},\ \text{car}\,(\mathit{x1}),\ a)) \neq \mathtt{0}))$
$\rightarrow\ (\text{fix-int}\,(\text{eval\$}\,(\mathbf{t},\ \text{cadr}\,(\mathit{x1}),\ a)) = \mathtt{0})$

EVENT: Enable eval$-equal.

THEOREM: eval$-make-cancel-itimes-equality
$\text{eval\$}\,(\mathbf{t},\ \text{make-cancel-itimes-equality}\,(x,\ y,\ \mathit{in\text{-}both}),\ a)$
$=\ \textbf{if}\ \text{eval\$}\,(\mathbf{t},\ \text{list}\,(\mathtt{'equal},\ \text{itimes-tree}\,(\mathit{in\text{-}both}),\ \mathtt{''0}),\ a)\ \textbf{then t}$
$\textbf{else}\ \text{itimes-list}\,(\text{eval\$}\,(\mathtt{'list},\ \text{bagdiff}\,(x,\ \mathit{in\text{-}both}),\ a))$
$=\ \text{itimes-list}\,(\text{eval\$}\,(\mathtt{'list},\ \text{bagdiff}\,(y,\ \mathit{in\text{-}both}),\ a))\ \textbf{endif}$

EVENT: Disable make-cancel-itimes-equality.

```
;; Here's a special case that I hope helps with the clausifier problem.
;; The lemma above seems necessary for its proof.
```

THEOREM: eval$-make-cancel-itimes-equality-1
eval$ (**t**, make-cancel-itimes-equality (list (x), y, list (x)), a)
= **if** fix-int (eval$ (**t**, x, a)) = `0` **then t**
else `1` = itimes-list (eval$ (`'list`, delete (x, y), a)) **endif**

THEOREM: equal-fix-int
(fix-int (x) = x) = integerp (x)

```
;; Here's another special case that I hope helps with the clausifier problem.
```

THEOREM: eval$-make-cancel-itimes-equality-2
eval$ (**t**, make-cancel-itimes-equality (x, list (y), list (y)), a)
= **if** fix-int (eval$ (**t**, y, a)) = `0` **then t**
else `1` = itimes-list (eval$ (`'list`, delete (y, x), a)) **endif**

THEOREM: eval$-equal-itimes-tree-itimes-fringe-0
(eval$ (**t**, list (`'equal`, itimes-tree (itimes-fringe (x)), `''0`), a)
$\wedge$ (car (x) = `'itimes`))
$\rightarrow$ (eval$ (**t**, x, a) = `0`)

THEOREM: izerop-eval-of-member-implies-itimes-list-0
(($z \in y$) $\wedge$ (fix-int (eval$ (**t**, z, a)) = `0`))
$\rightarrow$ (itimes-list (eval$ (`'list`, y, a)) = `0`)

```
#| The function below has no AND or OR, for efficiency
(defn subsetp (x y)
  (if (nlistp x)
      t
    (and (member (car x) y)
         (subsetp (cdr x) y))))
|#
```

DEFINITION:
subsetp (x, y)
= **if** $x \simeq$ **nil then t**
elseif car (x) $\in y$ **then** subsetp (cdr (x), y)
else f endif

THEOREM: subsetp-implies-itimes-list-eval$-equals-0
(subsetp (x, y) $\wedge$ (itimes-list (eval$ (`'list`, x, a)) = `0`))
$\rightarrow$ (itimes-list (eval$ (`'list`, y, a)) = `0`)

THEOREM: subbagp-subsetp
subbagp (x, y) $\rightarrow$ subsetp (x, y)

THEOREM: equal-0-itimes-list-eval$-bagint-1
(itimes-list (eval$ ('list, bagint (x, y), a)) = 0)
→ (itimes-list (eval$ ('list, x, a)) = 0)

THEOREM: equal-0-itimes-list-eval$-bagint-2
(itimes-list (eval$ ('list, bagint (x, y), a)) = 0)
→ (itimes-list (eval$ ('list, y, a)) = 0)

THEOREM: correctness-of-cancel-itimes-hack-2
(listp (u)
∧ (car (u) = 'itimes)
∧ listp (v)
∧ (car (v) = 'itimes)
∧ (eval$ (t, u, a) ≠ eval$ (t, v, a)))
→ (itimes-list (eval$ ('list,
bagdiff (itimes-fringe (u),
bagint (itimes-fringe (u), itimes-fringe (v))),
a))
≠ itimes-list (eval$ ('list,
bagdiff (itimes-fringe (v),
bagint (itimes-fringe (u),
itimes-fringe (v))),
a)))

THEOREM: correctness-of-cancel-itimes-hack-3-lemma
((u = itimes (a, b)) ∧ (fix-int (a) ≠ 0))
→ ((u = itimes (a, c)) = (fix-int (b) = fix-int (c)))

THEOREM: correctness-of-cancel-itimes-hack-3
(listp (u)
∧ (car (u) = 'itimes)
∧ listp (v)
∧ (car (v) = 'itimes)
∧ (eval$ (t, u, a) = eval$ (t, v, a))
∧ (¬ eval$ (t,
list ('equal,
itimes-tree (bagint (itimes-fringe (u), itimes-fringe (v))),
''0),
a)))
→ ((itimes-list (eval$ ('list,
bagdiff (itimes-fringe (u),
bagint (itimes-fringe (u), itimes-fringe (v))),
a))
= itimes-list (eval$ ('list,
bagdiff (itimes-fringe (v),

bagint (itimes-fringe (u),
itimes-fringe (v))),
a)))
= **t**)

EVENT: Disable correctness-of-cancel-itimes-hack-3-lemma.

THEOREM: correctness-of-cancel-itimes
eval\$ (**t**, x, a) = eval\$ (**t**, cancel-itimes (x), a)

```
; ---------- Meta lemma for itimes cancellation on ilessp terms

;; I'll try to keep this similar to the approach for equalities above,
;; modified as in the iplus case (i.e. no fix-int is necessary).

;; EVAL$-EQUAL is currently enabled, but that's OK.
```

DEFINITION:
itimes-tree-no-fix-int (l)
= **if** listp (l) **then** itimes-tree-rec (l)
else ''1 **endif**

```
;; The following allows us to pretty much ignore
;; itimes-tree-no-fix-int forever.  (Notice that it is disabled
;; immediately below.)
```

THEOREM: eval\$-itimes-tree-no-fix-int-1
ilessp (eval\$ (**t**, itimes-tree-no-fix-int (x), a), y)
= ilessp (eval\$ (**t**, itimes-tree (x), a), y)

THEOREM: eval\$-itimes-tree-no-fix-int-2
ilessp (y, eval\$ (**t**, itimes-tree-no-fix-int (x), a))
= ilessp (y, eval\$ (**t**, itimes-tree (x), a))

EVENT: Disable itimes-tree-no-fix-int.

```
;; We want to use EVAL$-ITIMES-TREE, and ITIMES-TREE is still disabled
;; so we're in good shape.
```

DEFINITION:
make-cancel-itimes-inequality (x, y, *in-both*)

```
=   list ('if,
        list ('ilessp, itimes-tree-no-fix-int (in-both), ''0),
        list ('ilessp,
            itimes-tree-no-fix-int (bagdiff (y, in-both)),
            itimes-tree-no-fix-int (bagdiff (x, in-both))),
        list ('if,
            list ('ilessp, ''0, itimes-tree-no-fix-int (in-both)),
            list ('ilessp,
                itimes-tree-no-fix-int (bagdiff (x, in-both)),
                itimes-tree-no-fix-int (bagdiff (y, in-both))),
            '(false)))
```

```
#| The function below has no AND or OR, for efficiency
(defn cancel-itimes-ilessp (x)
  (if (and (listp x)
           (equal (car x) (quote ilessp))
           (listp (bagint (itimes-fringe (cadr x)) (itimes-fringe (caddr x)))))
      (make-cancel-itimes-inequality (itimes-fringe (cadr x))
                                     (itimes-fringe (caddr x))
                                     (bagint (itimes-fringe (cadr x))
                                             (itimes-fringe (caddr x))))
    x))
|#
```

DEFINITION:

```
cancel-itimes-ilessp (x)
=   if listp (x)
    then if car (x) = 'ilessp
         then if listp (bagint (itimes-fringe (cadr (x)),
                                itimes-fringe (caddr (x))))
              then make-cancel-itimes-inequality (itimes-fringe (cadr (x)),
                                                  itimes-fringe (caddr (x)),
                                                  bagint (itimes-fringe (cadr (x)),
                                                          itimes-fringe (caddr (x))))
              else x endif
         else x endif
    else x endif
```

THEOREM: eval$-make-cancel-itimes-inequality

```
eval$ (t, make-cancel-itimes-inequality (x, y, in-both), a)
=   if eval$ (t, list ('ilessp, itimes-tree-no-fix-int (in-both), ''0), a)
    then ilessp (eval$ (t, itimes-tree-no-fix-int (bagdiff (y, in-both)), a),
                 eval$ (t, itimes-tree-no-fix-int (bagdiff (x, in-both)), a))
    elseif eval$ (t, list ('ilessp, ''0, itimes-tree-no-fix-int (in-both)), a)
```

then ilessp (eval$ (**t**, itimes-tree-no-fix-int (bagdiff (x, *in-both*)), a),
eval$ (**t**, itimes-tree-no-fix-int (bagdiff (y, *in-both*)), a))
else f endif

EVENT: Disable make-cancel-itimes-inequality.

THEOREM: listp-bagint-with-singleton-implies-member
listp (bagint (y, list (z))) $\rightarrow$ ($z \in y$)

THEOREM: itimes-list-eval$-list-0
(0 $\in x$) $\rightarrow$ (itimes-list (eval$ (`'list`, x, a)) = 0)

THEOREM: ilessp-itimes-right-positive
ilessp (0, x) $\rightarrow$ (ilessp (y, z) = ilessp (itimes (y, x), itimes (z, x)))

THEOREM: correctness-of-cancel-itimes-ilessp-hack-1
(subbagp (*bag*, x)
$\wedge$ subbagp (*bag*, y)
$\wedge$ ilessp (0, itimes-list (eval$ (`'list`, *bag*, a))))
$\rightarrow$ (ilessp (itimes-list (eval$ (`'list`, bagdiff (x, *bag*), a)),
itimes-list (eval$ (`'list`, bagdiff (y, *bag*), a)))
= ilessp (itimes-list (eval$ (`'list`, x, a)),
itimes-list (eval$ (`'list`, y, a))))

THEOREM: listp-bagint-with-singleton-member
listp (bagint (y, list (z))) = ($z \in y$)

THEOREM: correctness-of-cancel-itimes-ilessp-hack-2-lemma
(0 $\in$ itimes-fringe (w)) $\rightarrow$ (eval$ (**t**, w, a) = 0)

THEOREM: correctness-of-cancel-itimes-ilessp-hack-2
(0 $\in$ itimes-fringe (w)) $\rightarrow$ ($\neg$ ilessp (eval$ (**t**, w, a), 0))

EVENT: Disable correctness-of-cancel-itimes-ilessp-hack-2-lemma.

```
;;; Now hack-3 and hack-4 below are all that's left to prove before the
;;; main result.
```

THEOREM: ilessp-trichotomy
($\neg$ ilessp (x, y)) $\rightarrow$ (ilessp (y, x) = (fix-int (x) $\neq$ fix-int (y)))

THEOREM: correctness-of-cancel-itimes-ilessp-hack-3-lemma-1
((0 = itimes-list (eval$ (`'list`, *bag*, a))) $\wedge$ subsetp (*bag*, z))
$\rightarrow$ (itimes-list (eval$ (`'list`, z, a)) = 0)

THEOREM: correctness-of-cancel-itimes-ilessp-hack-3-lemma-2
((0 = itimes-list (eval$ ('list, *bag*, *a*))) ∧ subsetp (*bag*, itimes-fringe (*x*)))
→ (fix-int (eval$ (**t**, *x*, *a*)) = 0)

THEOREM: same-fix-int-implies-not-ilessp
(fix-int (*x*) = fix-int (*y*)) → (¬ ilessp (*x*, *y*))

THEOREM: correctness-of-cancel-itimes-ilessp-hack-3
((¬ ilessp (itimes-list (eval$ ('list, *bag*, *a*)), 0))
∧ (¬ ilessp (0, itimes-list (eval$ ('list, *bag*, *a*))))
∧ subbagp (*bag*, itimes-fringe (*w*))
∧ subbagp (*bag*, itimes-fringe (*v*)))
→ (¬ ilessp (eval$ (**t**, *w*, *a*), eval$ (**t**, *v*, *a*)))

THEOREM: ilessp-itimes-right-negative
ilessp (*x*, 0) → (ilessp (*y*, *z*) = ilessp (itimes (*z*, *x*), itimes (*y*, *x*)))

THEOREM: correctness-of-cancel-itimes-ilessp-hack-4
(subbagp (*bag*, *x*)
∧ subbagp (*bag*, *y*)
∧ ilessp (itimes-list (eval$ ('list, *bag*, *a*)), 0))
→ (ilessp (itimes-list (eval$ ('list, bagdiff (*x*, *bag*), *a*)),
itimes-list (eval$ ('list, bagdiff (*y*, *bag*), *a*)))
= ilessp (itimes-list (eval$ ('list, *y*, *a*)),
itimes-list (eval$ ('list, *x*, *a*))))

EVENT: Disable ilessp-trichotomy.

EVENT: Disable same-fix-int-implies-not-ilessp.

THEOREM: correctness-of-cancel-itimes-ilessp
eval$ (**t**, *x*, *a*) = eval$ (**t**, cancel-itimes-ilessp (*x*), *a*)

```
;; I think that the following lemma is safe because it won't be
;; called at all during relieve-hyps.
```

THEOREM: ilessp-strict
ilessp (*x*, *y*) → (¬ ilessp (*y*, *x*))

```
; ---------- Setting up the State ----------

;; I'll close by disabling (or enabling) those rules and definitions
;; whose status as left over from above isn't quite what I'd like.
;; I'm going to leave the eval$ rules on and eval$ off.
```

EVENT: Disable eval$-cancel-iplus.

EVENT: Disable eval$-iplus.

EVENT: Disable lessp-count-listp-cdr.

EVENT: Disable eval$-iplus-tree-rec.

EVENT: Disable eval$-iplus-tree.

```
;;(disable eval$-list-append) ;; Nice rule -- I'll keep it enabled
```

EVENT: Disable iplus-list-eval$-fringe.

EVENT: Disable eval$-iplus-list-bagdiff.

EVENT: Disable lessp-difference-plus-arg1.

EVENT: Disable lessp-difference-plus-arg1-commuted.

EVENT: Disable correctness-of-cancel-iplus-ilessp-lemma.

EVENT: Disable eval$-ilessp-iplus-tree-no-fix-int.

EVENT: Disable make-cancel-iplus-inequality-simplifier.

EVENT: Disable quotient-difference-lessp-arg2.

EVENT: Disable eval$-itimes-tree-rec.

EVENT: Disable eval$-itimes-tree.

EVENT: Disable itimes-list-eval$-fringe.

EVENT: Disable integerp-eval$-itimes.

EVENT: Disable itimes-list-bagdiff.

EVENT: Disable equal-itimes-list-eval$-list-delete.

EVENT: Disable member-izerop-itimes-fringe.

EVENT: Disable correctness-of-cancel-itimes-hack-1.

EVENT: Disable eval$-make-cancel-itimes-equality.

EVENT: Disable eval$-make-cancel-itimes-equality-1.

EVENT: Disable eval$-make-cancel-itimes-equality-2.

EVENT: Disable eval$-equal-itimes-tree-itimes-fringe-0.

EVENT: Disable izerop-eval-of-member-implies-itimes-list-0.

EVENT: Disable subsetp-implies-itimes-list-eval$-equals-0.

EVENT: Disable equal-0-itimes-list-eval$-bagint-1.

EVENT: Disable equal-0-itimes-list-eval$-bagint-2.

EVENT: Disable correctness-of-cancel-itimes-hack-2.

EVENT: Disable correctness-of-cancel-itimes-hack-3-lemma.

EVENT: Disable correctness-of-cancel-itimes-hack-3.

EVENT: Disable eval$-itimes-tree-no-fix-int-1.

EVENT: Disable eval$-itimes-tree-no-fix-int-2.

EVENT: Disable eval$-make-cancel-itimes-inequality.

EVENT: Disable listp-bagint-with-singleton-implies-member.

EVENT: Disable itimes-list-eval$-list-0.

EVENT: Disable correctness-of-cancel-itimes-ilessp-hack-1.

EVENT: Disable listp-bagint-with-singleton-member.

EVENT: Disable correctness-of-cancel-itimes-ilessp-hack-2.

EVENT: Disable correctness-of-cancel-itimes-ilessp-hack-3-lemma-1.

EVENT: Disable correctness-of-cancel-itimes-ilessp-hack-3-lemma-2.

EVENT: Disable correctness-of-cancel-itimes-ilessp-hack-3.

EVENT: Disable correctness-of-cancel-itimes-ilessp-hack-4.

```
;; The last one is a tough call, but I think it's OK.
;; (disable ilessp-strict)

;;;;;; ***** EXTRA META STUFF ***** ;;;;;;

;; The next goal is to improve itimes cancellation so that it looks
;; for common factors, and hence works on equations like
;;    x*y + x = x*z
;; and, for that matter,
;; a*x + -b*x = 0.

;; Rather than changing the existing cancel-itimes function, I'll
;; leave that one but disable its metalemma at the end.  Then if the
;; new version, which I'll call cancel-itimes-factors, is found to be
;; too slow, one can always disable its metalemma and re-enable the
;; metalemma for cancel-itimes.

;; Notice, by the way, that the existing cancel-itimes function is
;; useless for something like the following, since there's no special
;; treatment for INEG.  I'll remedy that in this version.
```

```
#|
(IMPLIES (AND (NOT (IZEROP X))
              (EQUAL (ITIMES A X) (INEG (ITIMES B X))))
         (EQUAL (FIX-INT A) (INEG B)))
|#
```

DEFINITION:
itimes-tree-ineg (l)
= **if** listp (l)
  then if car (l) = list ('quote, -1)
    then if listp (cdr (l)) **then** list ('ineg, itimes-tree-rec (cdr (l)))
      else car (l) **endif**
    else itimes-tree-rec (l) **endif**
  else ''1 **endif**

DEFINITION:
itimes-factors (x)
= **if** listp (x)
  then if car (x) = 'itimes
    then append (itimes-factors (cadr (x)), itimes-factors (caddr (x)))
    elseif car (x) = 'iplus
    then let *bag1* **be** itimes-factors (cadr (x)),
              bag2 **be** itimes-factors (caddr (x))
      in
      let *inboth* **be** bagint (*bag1*, *bag2*)
      in
      if listp (*inboth*)
      then cons (list ('iplus,
                itimes-tree-ineg (bagdiff (*bag1*,
                                inboth)),
                itimes-tree-ineg (bagdiff (*bag2*,
                                inboth))),
              inboth)
      else list (x) **endif endlet endlet**
    elseif car (x) = 'ineg
    then cons (list ('quote, -1), itimes-factors (cadr (x)))
    else list (x) **endif**
  else list (x) **endif**

THEOREM: itimes–1
itimes (-1, x) = ineg (x)

```
;; I'll need the following lemma because it's simplest not to deal with
;; e.g. (equal x x), where x is a variable, in the meta thing.  I'll do
;; the one after it too, simply because I'm thinking of it now.
```

THEOREM: equal-ineg-ineg
(ineg (x) = ineg (y)) = (fix-int (x) = fix-int (y))

THEOREM: ilessp-ineg-ineg
ilessp (ineg (x), ineg (y)) = ilessp (y, x)

THEOREM: fix-int-eval$-itimes-tree-rec
listp (x)
→ (fix-int (eval$ (**t**, itimes-tree-rec (x), a))
= itimes-list (eval$ (`'list`, x, a)))

THEOREM: eval$-itimes-tree-ineg
fix-int (eval$ (**t**, itimes-tree-ineg (x), a)) = itimes-list (eval$ (`'list`, x, a))

```
;; Now I want the above lemma to apply, but it doesn't, so the
;; following three lemmas are used instead.
```

THEOREM: ineg-eval$-itimes-tree-ineg
ineg (eval$ (**t**, itimes-tree-ineg (x), a))
= ineg (itimes-list (eval$ (`'list`, x, a)))

THEOREM: iplus-eval$-itimes-tree-ineg
(iplus (eval$ (**t**, itimes-tree-ineg (x), a), y)
= iplus (itimes-list (eval$ (`'list`, x, a)), y))
∧ (iplus (y, eval$ (**t**, itimes-tree-ineg (x), a))
= iplus (y, itimes-list (eval$ (`'list`, x, a))))

THEOREM: itimes-eval$-itimes-tree-ineg
(itimes (eval$ (**t**, itimes-tree-ineg (x), a), y)
= itimes (itimes-list (eval$ (`'list`, x, a)), y))
∧ (itimes (y, eval$ (**t**, itimes-tree-ineg (x), a))
= itimes (y, itimes-list (eval$ (`'list`, x, a))))

EVENT: Disable itimes-tree-ineg.

```
#| ****** The following definitions are for efficient execution of
   metafunctions.  They should probably be applied to all the metafunctions
   with fns arguments AND and OR.

(defmacro nqthm-macroexpand (defn &rest fns)
  `(nqthm-macroexpand-fn ',defn ',fns))

(defun nqthm-macroexpand-fn (defn fns)
  (iterate for fn in fns
```

```
          when (not (get fn 'sdefn))
          do (er soft (fn) |Sorry| |,| |but| |there| |is| |no| SDEFN
                 |for| (!ppr fn (quote |.|))))
  (let (name args body)
    (match! defn (defn name args body))
    (let ((arity-alist (cons (cons name (length args)) arity-alist)))
      (list 'defn name args
            (untranslate (normalize-ifs
                          (nqthm-macroexpand-term (translate body) fns)
                          nil nil nil))))))

(defun nqthm-macroexpand-term (term fns)
  (cond
   ((or (variablep term) (fquotep term))
    term)
   ((member-eq (ffn-symb term) fns)
    (let ((sdefn (get (ffn-symb term) 'sdefn)))
      (sub-pair-var (cadr sdefn)
                    (iterate for arg in (fargs term)
                             collect (nqthm-macroexpand-term arg fns))
                    (caddr sdefn))))
   (t (fcons-term (ffn-symb term)
                  (iterate for arg in (fargs term)
                           collect (nqthm-macroexpand-term arg fns))))))

|#

;; I "macroexpand" away the following below, so it's not really needed except
;; for the proof.  That is, I use it in the definition of cancel-itimes-factors,
;; but then get rid of it for cancel-itimes-factors-expanded, and although I
;; reason about the former, I USE the latter, for efficiency.
```

DEFINITION:
iplus-or-itimes-term (x)
$=$ **if** listp (x)
then case on car (x):
case $=$ *iplus*
then t
case $=$ *itimes*
then t
case $=$ *ineg*
then if listp (cadr (x)) **then** car (cadr (x)) $=$ 'itimes
else f endif
otherwise f endcase

else f endif

DEFINITION:
cancel-itimes-factors (x)
$=$ **if** listp $(x) \wedge$ (car (x) = `'equal`)
then let *bagint* **be** bagint (itimes-factors (cadr (x)),
itimes-factors (caddr (x)))
in
let *new-equality* **be** make-cancel-itimes-equality (itimes-factors (cadr (x)),
itimes-factors (caddr (x)),
bagint)
in
if iplus-or-itimes-term (cadr (x))
then if listp (*bagint*)
then if iplus-or-itimes-term (caddr (x))
then *new-equality*
else list (`'if`,
list (`'integerp`,
caddr (x)),
new-equality,
list (`'quote`, **f**)) **endif**
else x **endif**
elseif iplus-or-itimes-term (caddr (x))
then if listp (*bagint*)
then list (`'if`,
list (`'integerp`, cadr (x)),
new-equality,
list (`'quote`, **f**))
else x **endif**
else x **endif endlet endlet**
else x **endif**

```
;; The following was generated with the nqthm-macroexpand macro defined above.
```

```
;; The following was generated with the nqthm-macroexpand macro defined above.
(DEFN CANCEL-ITIMES-FACTORS-expanded (X)
  (IF (LISTP X)
      (IF (EQUAL (CAR X) 'EQUAL)
          (COND
           ((LISTP (CADR X))
            (CASE (CAR (CAR (CDR X)))
                  (IPLUS (IF (LISTP (BAGINT (ITIMES-FACTORS (CADR X))
                                            (ITIMES-FACTORS (CADDR X))))
```

```
(IF (LISTP (CADDR X))
    (CASE (CAR (CAR (CDR (CDR X))))
          (IPLUS
           (MAKE-CANCEL-ITIMES-EQUALITY
            (ITIMES-FACTORS (CADR X))
            (ITIMES-FACTORS (CADDR X))
            (BAGINT (ITIMES-FACTORS (CADR X))
                    (ITIMES-FACTORS (CADDR X)))))
          (ITIMES
           (MAKE-CANCEL-ITIMES-EQUALITY
            (ITIMES-FACTORS (CADR X))
            (ITIMES-FACTORS (CADDR X))
            (BAGINT (ITIMES-FACTORS (CADR X))
                    (ITIMES-FACTORS (CADDR X)))))
          (INEG
           (IF (LISTP (CADADDR X))
               (IF (EQUAL (CAADADDR X) 'ITIMES)
                   (MAKE-CANCEL-ITIMES-EQUALITY
                    (ITIMES-FACTORS (CADR X))
                    (ITIMES-FACTORS (CADDR X))
                    (BAGINT
                     (ITIMES-FACTORS (CADR X))
                     (ITIMES-FACTORS (CADDR X))))
                   (LIST 'IF
                         (LIST 'INTEGERP (CADDR X))
                         (MAKE-CANCEL-ITIMES-EQUALITY
                          (ITIMES-FACTORS (CADR X))
                          (ITIMES-FACTORS (CADDR X))
                          (BAGINT
                           (ITIMES-FACTORS (CADR X))
                           (ITIMES-FACTORS (CADDR X))))
                         (LIST 'QUOTE F)))
               (LIST 'IF
                     (LIST 'INTEGERP (CADDR X))
                     (MAKE-CANCEL-ITIMES-EQUALITY
                      (ITIMES-FACTORS (CADR X))
                      (ITIMES-FACTORS (CADDR X))
                      (BAGINT
                       (ITIMES-FACTORS (CADR X))
                       (ITIMES-FACTORS (CADDR X))))
                     (LIST 'QUOTE F))))
          (OTHERWISE
           (LIST 'IF
                 (LIST 'INTEGERP (CADDR X))
```

```
                                    (MAKE-CANCEL-ITIMES-EQUALITY
                                     (ITIMES-FACTORS (CADR X))
                                     (ITIMES-FACTORS (CADDR X))
                                     (BAGINT
                                      (ITIMES-FACTORS (CADR X))
                                      (ITIMES-FACTORS (CADDR X))))
                                    (LIST 'QUOTE F))))
                        (LIST 'IF (LIST 'INTEGERP (CADDR X))
                              (MAKE-CANCEL-ITIMES-EQUALITY
                               (ITIMES-FACTORS (CADR X))
                               (ITIMES-FACTORS (CADDR X))
                               (BAGINT
                                (ITIMES-FACTORS (CADR X))
                                (ITIMES-FACTORS (CADDR X))))
                              (LIST 'QUOTE F)))
                  X))
          (ITIMES (IF (LISTP (BAGINT (ITIMES-FACTORS (CADR X))
                                     (ITIMES-FACTORS (CADDR X))))
                      (IF (LISTP (CADDR X))
                          (CASE (CAR (CAR (CDR (CDR X))))
                                (IPLUS
                                 (MAKE-CANCEL-ITIMES-EQUALITY
                                  (ITIMES-FACTORS (CADR X))
                                  (ITIMES-FACTORS (CADDR X))
                                  (BAGINT
                                   (ITIMES-FACTORS (CADR X))
                                   (ITIMES-FACTORS (CADDR X)))))
                                (ITIMES
                                 (MAKE-CANCEL-ITIMES-EQUALITY
                                  (ITIMES-FACTORS (CADR X))
                                  (ITIMES-FACTORS (CADDR X))
                                  (BAGINT
                                   (ITIMES-FACTORS (CADR X))
                                   (ITIMES-FACTORS (CADDR X)))))
                                (INEG
                                 (IF (LISTP (CADADDR X))
                                     (IF (EQUAL (CAADADDR X) 'ITIMES)
                                         (MAKE-CANCEL-ITIMES-EQUALITY
                                          (ITIMES-FACTORS (CADR X))
                                          (ITIMES-FACTORS (CADDR X))
                                          (BAGINT
                                           (ITIMES-FACTORS (CADR X))
                                           (ITIMES-FACTORS (CADDR X))))
                                         (LIST 'IF
```

```
                                                  (LIST 'INTEGERP (CADDR X))
                                                  (MAKE-CANCEL-ITIMES-EQUALITY
                                                   (ITIMES-FACTORS (CADR X))
                                                   (ITIMES-FACTORS (CADDR X))
                                                   (BAGINT
                                                    (ITIMES-FACTORS (CADR X))
                                                    (ITIMES-FACTORS (CADDR X))))
                                                  (LIST 'QUOTE F)))
                                        (LIST 'IF
                                              (LIST 'INTEGERP (CADDR X))
                                              (MAKE-CANCEL-ITIMES-EQUALITY
                                               (ITIMES-FACTORS (CADR X))
                                               (ITIMES-FACTORS (CADDR X))
                                               (BAGINT
                                                (ITIMES-FACTORS (CADR X))
                                                (ITIMES-FACTORS (CADDR X))))
                                              (LIST 'QUOTE F))))
                                  (OTHERWISE
                                   (LIST 'IF
                                         (LIST 'INTEGERP (CADDR X))
                                         (MAKE-CANCEL-ITIMES-EQUALITY
                                          (ITIMES-FACTORS (CADR X))
                                          (ITIMES-FACTORS (CADDR X))
                                          (BAGINT
                                           (ITIMES-FACTORS (CADR X))
                                           (ITIMES-FACTORS (CADDR X))))
                                         (LIST 'QUOTE F))))
                            (LIST 'IF (LIST 'INTEGERP (CADDR X))
                                  (MAKE-CANCEL-ITIMES-EQUALITY
                                   (ITIMES-FACTORS (CADR X))
                                   (ITIMES-FACTORS (CADDR X))
                                   (BAGINT (ITIMES-FACTORS (CADR X))
                                           (ITIMES-FACTORS (CADDR X))))
                                  (LIST 'QUOTE F)))
                      X))
            (INEG (COND
                   ((LISTP (CADADR X))
                    (COND
                     ((EQUAL (CAADADR X) 'ITIMES)
                      (IF (LISTP
                           (BAGINT (ITIMES-FACTORS (CADR X))
                                   (ITIMES-FACTORS (CADDR X))))
                          (IF (LISTP (CADDR X))
                              (CASE (CAR (CAR (CDR (CDR X))))
```

```
(IPLUS
 (MAKE-CANCEL-ITIMES-EQUALITY
  (ITIMES-FACTORS (CADR X))
  (ITIMES-FACTORS (CADDR X))
  (BAGINT
   (ITIMES-FACTORS (CADR X))
   (ITIMES-FACTORS (CADDR X)))))
(ITIMES
 (MAKE-CANCEL-ITIMES-EQUALITY
  (ITIMES-FACTORS (CADR X))
  (ITIMES-FACTORS (CADDR X))
  (BAGINT
   (ITIMES-FACTORS (CADR X))
   (ITIMES-FACTORS (CADDR X)))))
(INEG
 (IF (LISTP (CADADDR X))
     (IF
      (EQUAL (CAADADDR X) 'ITIMES)
      (MAKE-CANCEL-ITIMES-EQUALITY
       (ITIMES-FACTORS (CADR X))
       (ITIMES-FACTORS (CADDR X))
       (BAGINT
        (ITIMES-FACTORS (CADR X))
        (ITIMES-FACTORS (CADDR X))))
      (LIST 'IF
            (LIST 'INTEGERP (CADDR X))
            (MAKE-CANCEL-ITIMES-EQUALITY
             (ITIMES-FACTORS (CADR X))
             (ITIMES-FACTORS (CADDR X))
             (BAGINT
              (ITIMES-FACTORS (CADR X))
              (ITIMES-FACTORS (CADDR X))))
            (LIST 'QUOTE F)))
     (LIST 'IF
           (LIST 'INTEGERP (CADDR X))
           (MAKE-CANCEL-ITIMES-EQUALITY
            (ITIMES-FACTORS (CADR X))
            (ITIMES-FACTORS (CADDR X))
            (BAGINT
             (ITIMES-FACTORS (CADR X))
             (ITIMES-FACTORS (CADDR X))))
           (LIST 'QUOTE F))))
(OTHERWISE
 (LIST 'IF
```

```
                        (LIST 'INTEGERP (CADDR X))
                        (MAKE-CANCEL-ITIMES-EQUALITY
                         (ITIMES-FACTORS (CADR X))
                         (ITIMES-FACTORS (CADDR X))
                         (BAGINT
                          (ITIMES-FACTORS (CADR X))
                          (ITIMES-FACTORS (CADDR X))))
                        (LIST 'QUOTE F))))
            (LIST 'IF
                  (LIST 'INTEGERP (CADDR X))
                  (MAKE-CANCEL-ITIMES-EQUALITY
                   (ITIMES-FACTORS (CADR X))
                   (ITIMES-FACTORS (CADDR X))
                   (BAGINT (ITIMES-FACTORS (CADR X))
                           (ITIMES-FACTORS (CADDR X))))
                  (LIST 'QUOTE F)))
    X))
((LISTP (CADDR X))
 (CASE (CAR (CAR (CDR (CDR X))))
       (IPLUS (IF
                (LISTP
                 (BAGINT
                  (ITIMES-FACTORS (CADR X))
                  (ITIMES-FACTORS (CADDR X))))
                (LIST 'IF
                      (LIST 'INTEGERP (CADR X))
                      (MAKE-CANCEL-ITIMES-EQUALITY
                       (ITIMES-FACTORS (CADR X))
                       (ITIMES-FACTORS (CADDR X))
                       (BAGINT
                        (ITIMES-FACTORS (CADR X))
                        (ITIMES-FACTORS (CADDR X))))
                      (LIST 'QUOTE F))
                X))
       (ITIMES (IF
                 (LISTP
                  (BAGINT
                   (ITIMES-FACTORS (CADR X))
                   (ITIMES-FACTORS (CADDR X))))
                 (LIST 'IF
                       (LIST 'INTEGERP (CADR X))
                       (MAKE-CANCEL-ITIMES-EQUALITY
                        (ITIMES-FACTORS (CADR X))
                        (ITIMES-FACTORS (CADDR X))
```

```
                                (BAGINT
                                 (ITIMES-FACTORS (CADR X))
                                 (ITIMES-FACTORS (CADDR X))))
                               (LIST 'QUOTE F))
                         X))
                 (INEG (IF (LISTP (CADADDR X))
                           (IF
                            (EQUAL (CAADADDR X) 'ITIMES)
                            (IF
                             (LISTP
                              (BAGINT
                               (ITIMES-FACTORS (CADR X))
                               (ITIMES-FACTORS (CADDR X))))
                             (LIST 'IF
                                   (LIST 'INTEGERP (CADR X))
                                   (MAKE-CANCEL-ITIMES-EQUALITY
                                    (ITIMES-FACTORS (CADR X))
                                    (ITIMES-FACTORS (CADDR X))
                                    (BAGINT
                                     (ITIMES-FACTORS (CADR X))
                                     (ITIMES-FACTORS (CADDR X))))
                                   (LIST 'QUOTE F))
                             X)
                            X)
                           X))
                 (OTHERWISE X)))
        (T X)))
     ((LISTP (CADDR X))
      (CASE (CAR (CAR (CDR (CDR X))))
            (IPLUS (IF
                    (LISTP
                     (BAGINT
                      (ITIMES-FACTORS (CADR X))
                      (ITIMES-FACTORS (CADDR X))))
                    (LIST 'IF
                          (LIST 'INTEGERP (CADR X))
                          (MAKE-CANCEL-ITIMES-EQUALITY
                           (ITIMES-FACTORS (CADR X))
                           (ITIMES-FACTORS (CADDR X))
                           (BAGINT
                            (ITIMES-FACTORS (CADR X))
                            (ITIMES-FACTORS (CADDR X))))
                          (LIST 'QUOTE F))
                    X))
```

```
                    (ITIMES (IF
                             (LISTP
                              (BAGINT
                               (ITIMES-FACTORS (CADR X))
                               (ITIMES-FACTORS (CADDR X))))
                             (LIST 'IF
                                   (LIST 'INTEGERP (CADR X))
                                   (MAKE-CANCEL-ITIMES-EQUALITY
                                    (ITIMES-FACTORS (CADR X))
                                    (ITIMES-FACTORS (CADDR X))
                                    (BAGINT
                                     (ITIMES-FACTORS (CADR X))
                                     (ITIMES-FACTORS (CADDR X))))
                                   (LIST 'QUOTE F))
                             X))
                    (INEG (IF (LISTP (CADADDR X))
                              (IF (EQUAL (CAADADDR X) 'ITIMES)
                                  (IF
                                   (LISTP
                                    (BAGINT
                                     (ITIMES-FACTORS (CADR X))
                                     (ITIMES-FACTORS (CADDR X))))
                                   (LIST 'IF
                                         (LIST 'INTEGERP (CADR X))
                                         (MAKE-CANCEL-ITIMES-EQUALITY
                                          (ITIMES-FACTORS (CADR X))
                                          (ITIMES-FACTORS (CADDR X))
                                          (BAGINT
                                           (ITIMES-FACTORS (CADR X))
                                           (ITIMES-FACTORS (CADDR X))))
                                         (LIST 'QUOTE F))
                                   X)
                                  X)
                              X))
                    (OTHERWISE X)))
            (T X)))
(OTHERWISE
 (IF (LISTP (CADDR X))
     (CASE (CAR (CAR (CDR (CDR X))))
           (IPLUS (IF
                   (LISTP
                    (BAGINT (ITIMES-FACTORS (CADR X))
                            (ITIMES-FACTORS (CADDR X))))
                   (LIST 'IF
```

```
                (LIST 'INTEGERP (CADR X))
                (MAKE-CANCEL-ITIMES-EQUALITY
                 (ITIMES-FACTORS (CADR X))
                 (ITIMES-FACTORS (CADDR X))
                 (BAGINT
                  (ITIMES-FACTORS (CADR X))
                  (ITIMES-FACTORS (CADDR X))))
                (LIST 'QUOTE F))
        X))
(ITIMES (IF
         (LISTP
          (BAGINT
           (ITIMES-FACTORS (CADR X))
           (ITIMES-FACTORS (CADDR X))))
         (LIST 'IF
               (LIST 'INTEGERP (CADR X))
               (MAKE-CANCEL-ITIMES-EQUALITY
                (ITIMES-FACTORS (CADR X))
                (ITIMES-FACTORS (CADDR X))
                (BAGINT
                 (ITIMES-FACTORS (CADR X))
                 (ITIMES-FACTORS (CADDR X))))
               (LIST 'QUOTE F))
         X))
(INEG (IF (LISTP (CADADDR X))
          (IF (EQUAL (CAADADDR X) 'ITIMES)
              (IF
               (LISTP
                (BAGINT
                 (ITIMES-FACTORS (CADR X))
                 (ITIMES-FACTORS (CADDR X))))
               (LIST 'IF
                     (LIST 'INTEGERP (CADR X))
                     (MAKE-CANCEL-ITIMES-EQUALITY
                      (ITIMES-FACTORS (CADR X))
                      (ITIMES-FACTORS (CADDR X))
                      (BAGINT
                       (ITIMES-FACTORS (CADR X))
                       (ITIMES-FACTORS (CADDR X))))
                     (LIST 'QUOTE F))
               X)
              X))
          X))
(OTHERWISE X))
```

```
                X))))
        ((LISTP (CADDR X))
         (CASE (CAR (CAR (CDR (CDR X))))
               (IPLUS (IF (LISTP (BAGINT (ITIMES-FACTORS (CADR X))
                                         (ITIMES-FACTORS (CADDR X))))
                          (LIST 'IF (LIST 'INTEGERP (CADR X))
                                (MAKE-CANCEL-ITIMES-EQUALITY
                                 (ITIMES-FACTORS (CADR X))
                                 (ITIMES-FACTORS (CADDR X))
                                 (BAGINT (ITIMES-FACTORS (CADR X))
                                         (ITIMES-FACTORS (CADDR X))))
                                (LIST 'QUOTE F))
                          X))
               (ITIMES (IF (LISTP (BAGINT (ITIMES-FACTORS (CADR X))
                                          (ITIMES-FACTORS (CADDR X))))
                           (LIST 'IF (LIST 'INTEGERP (CADR X))
                                 (MAKE-CANCEL-ITIMES-EQUALITY
                                  (ITIMES-FACTORS (CADR X))
                                  (ITIMES-FACTORS (CADDR X))
                                  (BAGINT (ITIMES-FACTORS (CADR X))
                                          (ITIMES-FACTORS (CADDR X))))
                                 (LIST 'QUOTE F))
                           X))
               (INEG (IF (LISTP (CADADDR X))
                         (IF (EQUAL (CAADADDR X) 'ITIMES)
                             (IF (LISTP
                                  (BAGINT (ITIMES-FACTORS (CADR X))
                                          (ITIMES-FACTORS (CADDR X))))
                                 (LIST 'IF
                                       (LIST 'INTEGERP (CADR X))
                                       (MAKE-CANCEL-ITIMES-EQUALITY
                                        (ITIMES-FACTORS (CADR X))
                                        (ITIMES-FACTORS (CADDR X))
                                        (BAGINT
                                         (ITIMES-FACTORS (CADR X))
                                         (ITIMES-FACTORS (CADDR X))))
                                       (LIST 'QUOTE F))
                                 X)
                             X))
                         X))
               (OTHERWISE X)))
        (T X))
       X)
  X))
```

THEOREM: cancel-itimes-factors-expanded-cancel-itimes-factors
cancel-itimes-factors-expanded (x) = cancel-itimes-factors (x)

EVENT: Disable cancel-itimes-factors-expanded.

EVENT: Disable iplus-or-itimes-term.

THEOREM: equal-itimes-list-eval$-list-delete-new-1
(fix-int (eval$ (**t**, *elt*, *a*)) $\neq$ 0)
$\rightarrow$ ((*x* = itimes-list (eval$ ('`list`, delete (*elt*, *bag*), *a*)))
= **if** *elt* $\in$ *bag*
then integerp (*x*)
$\wedge$ (itimes (*x*, eval$ (**t**, *elt*, *a*))
= itimes-list (eval$ ('`list`, *bag*, *a*)))
else *x* = itimes-list (eval$ ('`list`, *bag*, *a*)) **endif**)

THEOREM: equal-itimes-list-eval$-list-delete-new-2
(fix-int (eval$ (**t**, *elt*, *a*)) $\neq$ 0)
$\rightarrow$ ((itimes-list (eval$ ('`list`, delete (*elt*, *bag*), *a*)) = *x*)
= **if** *elt* $\in$ *bag*
then integerp (*x*)
$\wedge$ (itimes (*x*, eval$ (**t**, *elt*, *a*))
= itimes-list (eval$ ('`list`, *bag*, *a*)))
else *x* = itimes-list (eval$ ('`list`, *bag*, *a*)) **endif**)

THEOREM: itimes-itimes-list-eval$-list-delete
(*x* $\in$ *bag*)
$\rightarrow$ (itimes (eval$ (**t**, *x*, *a*), itimes-list (eval$ ('`list`, delete (*x*, *bag*), *a*)))
= itimes-list (eval$ ('`list`, *bag*, *a*)))

THEOREM: equal-itimes-list-eval$-list-bagdiff
(subbagp (*in-both*, *bag1*)
$\wedge$ subbagp (*in-both*, *bag2*)
$\wedge$ (itimes-list (eval$ ('`list`, *in-both*, *a*)) $\neq$ 0))
$\rightarrow$ ((itimes-list (eval$ ('`list`, bagdiff (*bag1*, *in-both*), *a*))
= itimes-list (eval$ ('`list`, bagdiff (*bag2*, *in-both*), *a*)))
= (itimes-list (eval$ ('`list`, *bag1*, *a*))
= itimes-list (eval$ ('`list`, *bag2*, *a*))))

THEOREM: membership-of-0-implies-itimes-list-is-0
(0 $\in$ *x*) $\rightarrow$ (itimes-list (*x*) = 0)

THEOREM: member-0-eval$-list
(0 $\in$ *x*) $\rightarrow$ (0 $\in$ eval$ ('`list`, *x*, *a*))

THEOREM: itimes-list-eval$-factors-lemma
itimes (itimes-list (eval$ ('list, bagint (*bag1*, *bag2*), *a*)),
        itimes-list (eval$ ('list, bagdiff (*bag2*, bagint (*bag1*, *bag2*)), *a*)))
= itimes-list (eval$ ('list, *bag2*, *a*))

THEOREM: itimes-list-eval$-factors-lemma-prime
itimes (itimes-list (eval$ ('list, bagint (*bag1*, *bag2*), *a*)),
        itimes-list (eval$ ('list, bagdiff (*bag1*, bagint (*bag1*, *bag2*)), *a*)))
= itimes-list (eval$ ('list, *bag1*, *a*))

THEOREM: itimes-list-eval$-factors
itimes-list (eval$ ('list, itimes-factors (*x*), *a*)) = fix-int (eval$ (**t**, *x*, *a*))

THEOREM: iplus-or-itimes-term-integerp-eval$
iplus-or-itimes-term (*x*) → integerp (eval$ (**t**, *x*, *a*))

THEOREM: eval$-list-bagint-0
(itimes-list (eval$ ('list, bagint (*x*, *y*), *a*)) = 0)
→ ((itimes-list (eval$ ('list, *x*, *a*)) = 0)
  ∧ (itimes-list (eval$ ('list, *y*, *a*)) = 0))

THEOREM: eval$-list-bagint-0-implies-equal
((itimes-list (eval$ ('list, bagint (itimes-factors (*v*), itimes-factors (*w*)), *a*))
  = 0)
∧ integerp (eval$ (**t**, *v*, *a*))
∧ integerp (eval$ (**t**, *w*, *a*)))
→ ((eval$ (**t**, *v*, *a*) = eval$ (**t**, *w*, *a*)) = **t**)

THEOREM: correctness-of-cancel-itimes-factors
eval$ (**t**, *x*, *a*) = eval$ (**t**, cancel-itimes-factors-expanded (*x*), *a*)

```
;; OK -- now, the lessp case, finally.  Ugh!
```

DEFINITION:
cancel-itimes-ilessp-factors (*x*)
= **if** listp (*x*)
  then if car (*x*) = 'ilessp
    then if listp (bagint (itimes-factors (cadr (*x*)),
                itimes-factors (caddr (*x*))))
      then make-cancel-itimes-inequality (itimes-factors (cadr (*x*)),
                itimes-factors (caddr (*x*)),
                bagint (itimes-factors (cadr (*x*)),
                  itimes-factors (caddr (*x*))))
      else *x* **endif**
    else *x* **endif**
  else *x* **endif**

THEOREM: bagint-singleton
bagint $(x,$ list $(y))$
$=$ **if** $y \in x$ **then** list (y)
else nil endif

THEOREM: izerop-ilessp-0-relationship
(fix-int $(x) = 0) = ((\neg$ ilessp $(x, 0)) \wedge (\neg$ ilessp $(0, x)))$

THEOREM: ilessp-itimes-list-eval$-list-delete-helper-1
ilessp $(0, w) \rightarrow$ (ilessp (itimes (x, w), itimes $(w, u)) =$ ilessp $(x, u))$

THEOREM: ilessp-itimes-list-eval$-list-delete-helper-2
ilessp $(w, 0) \rightarrow$ (ilessp (itimes (w, u), itimes $(x, w)) =$ ilessp $(x, u))$

THEOREM: ilessp-itimes-list-eval$-list-delete
$((z \in y) \wedge$ (fix-int (eval$ (**t**, z, a)) $\neq 0))$
$\rightarrow$ (ilessp $(x,$ itimes-list (eval$ (`'list`, delete (z, y), $a)))$
$=$ **if** ilessp $(0,$ eval$ (**t**, z, $a))$
then ilessp (itimes $(x,$ eval$ (**t**, z, $a)),$
itimes-list (eval$ (`'list`, y, $a)))$
elseif ilessp (eval$ (**t**, z, $a)$, $0)$
then ilessp (itimes-list (eval$ (`'list`, y, $a)),$
itimes $(x,$ eval$ (**t**, z, $a)))$
else f endif)

THEOREM: ilessp-itimes-list-eval$-list-delete-prime-helper-1
ilessp $(0, w) \rightarrow$ (ilessp (itimes (w, u), itimes $(x, w)) =$ ilessp $(u, x))$

THEOREM: ilessp-itimes-list-eval$-list-delete-prime-helper-2
ilessp $(w, 0) \rightarrow$ (ilessp (itimes (x, w), itimes $(w, u)) =$ ilessp $(u, x))$

THEOREM: ilessp-itimes-list-eval$-list-delete-prime
$((z \in y) \wedge$ (fix-int (eval$ (**t**, z, a)) $\neq 0))$
$\rightarrow$ (ilessp (itimes-list (eval$ (`'list`, delete (z, y), $a)), x)$
$=$ **if** ilessp $(0,$ eval$ (**t**, z, $a))$
then ilessp (itimes-list (eval$ (`'list`, y, $a)),$
itimes $(x,$ eval$ (**t**, z, $a)))$
elseif ilessp (eval$ (**t**, z, $a)$, $0)$
then ilessp (itimes $(x,$ eval$ (**t**, z, $a)),$
itimes-list (eval$ (`'list`, y, $a)))$
else f endif)

```
;; **** Do I have anything like the following two lemmas for the equality case?
;; Should I?

;;;***** I should also consider if I've dealt with things like 0 = a*x + b*x, and
;;; simlilarly for ilessp.
```

THEOREM: ilessp-0-itimes
ilessp (0, itimes (x, y))
= ((ilessp (0, x) $\wedge$ ilessp (0, y)) $\vee$ (ilessp (x, 0) $\wedge$ ilessp (y, 0)))

THEOREM: ilessp-itimes-0
ilessp (itimes (x, y), 0)
= ((ilessp (0, x) $\wedge$ ilessp (y, 0)) $\vee$ (ilessp (x, 0) $\wedge$ ilessp (0, y)))

THEOREM: ilessp-itimes-list-eval$-list-bagdiff
(subbagp (*in-both*, *bag1*)
$\wedge$ subbagp (*in-both*, *bag2*)
$\wedge$ (itimes-list (eval$ ('list, *in-both*, a)) $\neq$ 0))
$\rightarrow$ (ilessp (itimes-list (eval$ ('list, bagdiff (*bag1*, *in-both*), a)),
itimes-list (eval$ ('list, bagdiff (*bag2*, *in-both*), a)))
= **if** ilessp (0, itimes-list (eval$ ('list, *in-both*, a)))
then ilessp (itimes-list (eval$ ('list, *bag1*, a)),
itimes-list (eval$ ('list, *bag2*, a)))
else ilessp (itimes-list (eval$ ('list, *bag2*, a)),
itimes-list (eval$ ('list, *bag1*, a))) **endif**)

THEOREM: zero-ilessp-implies-not-equal
ilessp (0, x) $\rightarrow$ (0 $\neq$ x)

THEOREM: ilessp-itimes-list-eval$-list-bagdiff-corollary-1
(subbagp (*in-both*, *bag1*)
$\wedge$ subbagp (*in-both*, *bag2*)
$\wedge$ ilessp (0, itimes-list (eval$ ('list, *in-both*, a))))
$\rightarrow$ (ilessp (itimes-list (eval$ ('list, bagdiff (*bag1*, *in-both*), a)),
itimes-list (eval$ ('list, bagdiff (*bag2*, *in-both*), a)))
= ilessp (itimes-list (eval$ ('list, *bag1*, a)),
itimes-list (eval$ ('list, *bag2*, a))))

THEOREM: ilessp-zero-implies-not-equal
ilessp (x, 0) $\rightarrow$ (0 $\neq$ x)

THEOREM: ilessp-itimes-list-eval$-list-bagdiff-corollary-2
(subbagp (*in-both*, *bag1*)
$\wedge$ subbagp (*in-both*, *bag2*)
$\wedge$ ilessp (itimes-list (eval$ ('list, *in-both*, a)), 0))
$\rightarrow$ (ilessp (itimes-list (eval$ ('list, bagdiff (*bag1*, *in-both*), a)),
itimes-list (eval$ ('list, bagdiff (*bag2*, *in-both*), a)))
= ilessp (itimes-list (eval$ ('list, *bag2*, a)),
itimes-list (eval$ ('list, *bag1*, a))))

THEOREM: member-0-itimes-factors-yields-0
(eval$ (**t**, w, a) $\neq$ 0) $\rightarrow$ (0 $\notin$ itimes-factors (w))

THEOREM: member-0-itimes-factors-yields-0-ilessp-consequence-1
ilessp (eval$ (**t**, w, a), 0) $\rightarrow$ (0 $\not\in$ itimes-factors (w))

THEOREM: member-0-itimes-factors-yields-0-ilessp-consequence-2
ilessp (0, eval$ (**t**, w, a)) $\rightarrow$ (0 $\not\in$ itimes-factors (w))

```
#|
(prove-lemma eval$-list-bagint-0 nil
  (implies (equal (itimes-list (eval$ 'list (bagint x y) a)) 0)
           (and (equal (itimes-list (eval$ 'list x a)) 0)
                (equal (itimes-list (eval$ 'list y a)) 0)))
  ((use (subsetp-implies-itimes-list-eval$-equals-0
         (x (bagint x y))
         (y x))
        (subsetp-implies-itimes-list-eval$-equals-0
         (x (bagint x y))
         (y y)))))
|#

#|
(prove-lemma eval$-list-bagint-0-implies-equal (rewrite)
  (implies (and (equal (itimes-list (eval$ 'list (bagint (itimes-factors v) (itimes-factors
                       0)
                (integerp (eval$ t v a))
                (integerp (eval$ t w a)))
           (equal (equal (eval$ t v a) (eval$ t w a))
                  t))
  ((use (eval$-list-bagint-0 (x (itimes-factors v))
                             (y (itimes-factors w))))))
|#

;; At this point I'm going to switch the states of ilessp-trichotomy and
;; izerop-ilessp-0-relationship, for good (or till I change my mind again!).
```

EVENT: Enable ilessp-trichotomy.

EVENT: Disable izerop-ilessp-0-relationship.

THEOREM: eval$-list-bagint-0-for-ilessp
((¬ ilessp (itimes-list (eval$ ('**list**, bagint (x, y), a)), 0))
 $\wedge$ (¬ ilessp (0, itimes-list (eval$ ('**list**, bagint (x, y), a)))))
$\rightarrow$ ((fix-int (itimes-list (eval$ ('**list**, x, a))) = 0)
 $\wedge$ (fix-int (itimes-list (eval$ ('**list**, y, a))) = 0))

THEOREM: eval$-list-bagint-0-implies-equal-for-ilessp-lemma
((¬ ilessp (itimes-list (eval$ ('list,
bagint (itimes-factors (v), itimes-factors (w)),
a)),
0))
∧ (¬ ilessp (0,
itimes-list (eval$ ('list,
bagint (itimes-factors (v),
itimes-factors (w)),
a)))))
→ (fix-int (eval$ (**t**, v, a)) = fix-int (eval$ (**t**, w, a)))

THEOREM: equal-fix-int-to-ilessp
(fix-int (x) = fix-int (y)) → (¬ ilessp (x, y))

THEOREM: eval$-list-bagint-0-implies-equal-for-ilessp
((¬ ilessp (itimes-list (eval$ ('list,
bagint (itimes-factors (v), itimes-factors (w)),
a)),
0))
∧ (¬ ilessp (0,
itimes-list (eval$ ('list,
bagint (itimes-factors (v),
itimes-factors (w)),
a)))))
→ ((¬ ilessp (eval$ (**t**, v, a), eval$ (**t**, w, a)))
∧ (¬ ilessp (eval$ (**t**, w, a), eval$ (**t**, v, a))))

```
;; The rewrite rule ILESSP-TRICHOTOMY seemed to mess up the proof of the following,
;; so I'm just going to leave it disabled.
```

EVENT: Disable ilessp-trichotomy.

THEOREM: correctness-of-cancel-itimes-ilessp-factors
eval$ (**t**, x, a) = eval$ (**t**, cancel-itimes-ilessp-factors (x), a)

```
;; OK -- now, the zero cases.
```

EVENT: Enable lessp-count-listp-cdr.

DEFINITION:
disjoin-equalities-with-0 (*factors*)
= **if** listp (cdr (*factors*))

```
    then list ('or,
               list ('equal, list ('fix-int, car (factors)), ''0),
               disjoin-equalities-with-0 (cdr (factors)))
    else list ('equal, list ('fix-int, car (factors)), ''0) endif
```

EVENT: Disable lessp-count-listp-cdr.

DEFINITION:

```
cancel-factors-0 (x)
=   if listp (x)
    then if car (x) = 'equal
         then if cadr (x) = ''0
              then let factors be itimes-factors (caddr (x))
                   in
                   if listp (cdr (factors))
                   then disjoin-equalities-with-0 (factors)
                   else x endif endlet
              elseif caddr (x) = ''0
              then let factors be itimes-factors (cadr (x))
                   in
                   if listp (cdr (factors))
                   then disjoin-equalities-with-0 (factors)
                   else x endif endlet
              else x endif
         else x endif
    else x endif
```

DEFINITION:

```
some-eval$s-to-0 (x, a)
=   if listp (x)
    then (fix-int (eval$ (t, car (x), a)) = 0)
         ∨  some-eval$s-to-0 (cdr (x), a)
    else f endif
```

THEOREM: eval$-disjoin-equalities-with-0

```
 listp (lst)
 →  (eval$ (t, disjoin-equalities-with-0 (lst), a)
      =  some-eval$s-to-0 (lst, a))
```

THEOREM: some-eval$s-to-0-append

```
 some-eval$s-to-0 (append (x, y), a)
 =  (some-eval$s-to-0 (x, a) ∨ some-eval$s-to-0 (y, a))
```

THEOREM: some-eval$s-to-0-eliminator

```
 some-eval$s-to-0 (x, a) = (itimes-list (eval$ ('list, x, a)) = 0)
```

THEOREM: listp-cdr-factors-implies-integerp
listp (cdr (itimes-factors (v))) $\rightarrow$ integerp (eval\$ (**t**, v, a))

THEOREM: correctness-of-cancel-factors-0
eval\$ (**t**, x, a) = eval\$ (**t**, cancel-factors-0 (x), a)

```
;; and now for inequalities...
```

EVENT: Enable lessp-count-listp-cdr.

DEFINITION:
conjoin-inequalities-with-0 (*factors*, *parity*)

```
=   if listp (cdr (factors))
    then if parity
         then list ('or,
                    list ('and,
                          list ('ilessp, ''0, car (factors)),
                          conjoin-inequalities-with-0 (cdr (factors), t)),
                    list ('and,
                          list ('ilessp, car (factors), ''0),
                          conjoin-inequalities-with-0 (cdr (factors), f)))
         else list ('or,
                    list ('and,
                          list ('ilessp, car (factors), ''0),
                          conjoin-inequalities-with-0 (cdr (factors), t)),
                    list ('and,
                          list ('ilessp, ''0, car (factors)),
                          conjoin-inequalities-with-0 (cdr (factors), f))) endif
    elseif parity then list ('ilessp, ''0, car (factors))
    else list ('ilessp, car (factors), ''0) endif
```

EVENT: Disable lessp-count-listp-cdr.

DEFINITION:
cancel-factors-ilessp-0 (x)

```
=   if listp (x)
    then if car (x) = 'ilessp
         then if cadr (x) = ''0
              then let factors be itimes-factors (caddr (x))
                   in
                   if listp (cdr (factors))
                   then conjoin-inequalities-with-0 (factors, t)
                   else x endif endlet
```

```
            elseif caddr (x) = ''0
            then let factors be itimes-factors (cadr (x))
                 in
                 if listp (cdr (factors))
                 then conjoin-inequalities-with-0 (factors, f)
                 else x endif endlet
            else x endif
        else x endif
    else x endif
```

THEOREM: conjoin-inequalities-with-0-eliminator
listp (x)
$\rightarrow$ (eval\$ (**t**, conjoin-inequalities-with-0 (x, *parity*), a)
= **if** *parity* **then** ilessp (0, itimes-list (eval\$ ('list, x, a)))
else ilessp (itimes-list (eval\$ ('list, x, a)), 0) **endif**)

THEOREM: correctness-of-cancel-factors-ilessp-0
eval\$ (**t**, x, a) = eval\$ (**t**, cancel-factors-ilessp-0 (x), a)

EVENT: Disable equal-itimes-list-eval\$-list-delete-new-1.

EVENT: Disable equal-itimes-list-eval\$-list-delete-new-2.

EVENT: Disable itimes-itimes-list-eval\$-list-delete.

EVENT: Disable equal-itimes-list-eval\$-list-bagdiff.

EVENT: Disable itimes-list-eval\$-factors-lemma.

EVENT: Disable itimes-list-eval\$-factors-lemma-prime.

EVENT: Disable itimes-list-eval\$-factors.

EVENT: Disable iplus-or-itimes-term-integerp-eval\$.

EVENT: Disable eval\$-list-bagint-0.

EVENT: Disable eval\$-list-bagint-0-implies-equal.

EVENT: Disable izerop-ilessp-0-relationship.

EVENT: Disable ilessp-itimes-list-eval$-list-delete-helper-1.

EVENT: Disable ilessp-itimes-list-eval$-list-delete-helper-2.

EVENT: Disable ilessp-itimes-list-eval$-list-delete.

EVENT: Disable ilessp-itimes-list-eval$-list-delete-prime-helper-1.

EVENT: Disable ilessp-itimes-list-eval$-list-delete-prime-helper-2.

EVENT: Disable ilessp-itimes-list-eval$-list-delete-prime.

EVENT: Disable ilessp-0-itimes.

EVENT: Disable ilessp-itimes-0.

EVENT: Disable listp-cdr-factors-implies-integerp.

```
;; We presumably have better meta-lemmas now, but if we want we
;; can disable those (i.e., correctness-of-cancel-itimes-factors,
;; correctness-of-cancel-itimes-ilessp-factors,
;; correctness-of-cancel-factors-0, and
;; correctness-of-cancel-factors-ilessp-0) and enable the two
;; mentioned below:
```

EVENT: Disable correctness-of-cancel-itimes.

EVENT: Disable correctness-of-cancel-itimes-ilessp.

```
;; I'll disable some rules now, finally, that I'd previously thought
;; would be OK but now fear because of potential nasty backchaining.
```

EVENT: Disable not-integerp-implies-not-equal-iplus.

EVENT: Disable not-integerp-implies-not-equal-itimes.

EVENT: Disable subbagp-subsetp.

EVENT: Disable eval$-list-bagint-0-implies-equal-for-ilessp.

```
; ---------- Cancel ineg terms from equalities and inequalities ----------
```

DEFINITION:
split-out-ineg-terms (*x*)
= **if** listp (*x*)
  then let *pair* **be** split-out-ineg-terms (cdr (*x*)),
        a **be** car (*x*)
      in
      if listp (*a*)
      then if car (*a*) = `'ineg`
        then cons (car (*pair*), cons (cadr (*a*), cdr (*pair*)))
        elseif (car (*a*) = `'quote`)
          ∧ negativep (cadr (*a*))
          ∧ (negative-guts (cadr (*a*)) ≠ 0)
        then cons (car (*pair*),
            cons (list (`'quote`, negative-guts (cadr (*a*))),
              cdr (*pair*)))
        else cons (cons (*a*, car (*pair*)), cdr (*pair*)) **endif**
      else cons (cons (*a*, car (*pair*)), cdr (*pair*)) **endif endlet**
  else cons (**nil**, **nil**) **endif**

DEFINITION:
remove-inegs (*x*, *y*)
= **let** *xpair* **be** split-out-ineg-terms (*x*),
    ypair **be** split-out-ineg-terms (*y*)
  in
  if listp (cdr (*xpair*)) ∨ listp (cdr (*ypair*))
  then cons (append (cdr (*ypair*), car (*xpair*)),
          append (cdr (*xpair*), car (*ypair*)))
  else f endif endlet

DEFINITION:
iplus-or-ineg-term (*x*)
= (listp (*x*) ∧ ((car (*x*) = `'ineg`) ∨ (car (*x*) = `'iplus`)))

DEFINITION:
make-cancel-ineg-terms-equality (*x*)
= **let** *new-fringes* **be** remove-inegs (iplus-fringe (cadr (*x*)),
                iplus-fringe (caddr (*x*)))

```
in
if new-fringes
then if iplus-or-ineg-term (cadr (x))
     then if iplus-or-ineg-term (caddr (x))
          then list ('equal,
                     iplus-tree (car (new-fringes)),
                     iplus-tree (cdr (new-fringes)))
          else list ('if,
                     list ('integerp, caddr (x)),
                     list ('equal,
                         iplus-tree (car (new-fringes)),
                         iplus-tree (cdr (new-fringes))),
                     list ('quote, f)) endif
     elseif iplus-or-ineg-term (caddr (x))
     then list ('if,
                list ('integerp, cadr (x)),
                list ('equal,
                    iplus-tree (car (new-fringes)),
                    iplus-tree (cdr (new-fringes))),
                list ('quote, f))
     else x endif
else x endif endlet
```

DEFINITION:

```
cancel-ineg-terms-from-equality (x)
=  if listp (x) ∧ (car (x) = 'equal)
   then make-cancel-ineg-terms-equality (x)
   else x endif
```

```
;; The following was created from nqthm-macroexpand with arguments
;; and or make-cancel-ineg-terms-equality iplus-or-ineg-term
```

DEFINITION:

```
cancel-ineg-terms-from-equality-expanded (x)
=  if listp (x)
   then if car (x) = 'equal
        then if remove-inegs (iplus-fringe (cadr (x)),
                              iplus-fringe (caddr (x)))
             then if listp (cadr (x))
                  then case on car (car (cdr (x))):
                       case = ineg
                       then if listp (caddr (x))
                            then case on car (car (cdr (cdr (x)))):
                                 case = ineg
                                 then list ('equal,
```

```
                    iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                   iplus-fringe (caddr (x))))),
                    iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                   iplus-fringe (caddr (x))))))
            case = iplus
             then list ('equal,
                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))),
                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))))
            otherwise list ('if,
                            list ('integerp,
                                  caddr (x)),
                            list ('equal,
                                  iplus-tree (car (remove-inegs (iplus-fringe (cadr (x
                                                                 iplus-fringe (caddr (
                                  iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x
                                                                 iplus-fringe (caddr (
                            list ('quote, f)) endcase
        else list ('if,
                  list ('integerp, caddr (x)),
                  list ('equal,
                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))),
                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))),
                  list ('quote, f)) endif
case = iplus
 then if listp (caddr (x))
       then case on car (car (cdr (cdr (x)))):
            case = ineg
            then list ('equal,
                       iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                      iplus-fringe (caddr (x))))),
                       iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                      iplus-fringe (caddr (x))))))
            case = iplus
             then list ('equal,
                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))),
                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))))
            otherwise list ('if,
                            list ('integerp,
```

```
                                        caddr (x)),
                                    list ('equal,
                                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (
                                                                        iplus-fringe (caddr
                                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (
                                                                        iplus-fringe (caddr
                                    list ('quote, f)) endcase
            else list ('if,
                    list ('integerp, caddr (x)),
                    list ('equal,
                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                        iplus-fringe (caddr (x))))),
                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                        iplus-fringe (caddr (x))))),
                    list ('quote, f)) endif
    otherwise if listp (caddr (x))
            then case on car (car (cdr (cdr (x)))):
                case = ineg
                then list ('if,
                        list ('integerp,
                            cadr (x)),
                        list ('equal,
                            iplus-tree (car (remove-inegs (iplus-fringe (cadr (x
                                                            iplus-fringe (caddr (
                            iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x
                                                            iplus-fringe (caddr (
                        list ('quote, f))
                case = iplus
                 then list ('if,
                        list ('integerp,
                            cadr (x)),
                        list ('equal,
                            iplus-tree (car (remove-inegs (iplus-fringe (cadr (
                                                            iplus-fringe (caddr
                            iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (
                                                            iplus-fringe (caddr
                        list ('quote, f))
                otherwise x endcase
            else x endif endcase
elseif listp (caddr (x))
then case on car (car (cdr (cdr (x)))):
    case = ineg
    then list ('if,
            list ('integerp, cadr (x)),
```

```
                                    list ('equal,
                                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                                       iplus-fringe (caddr (x))))),
                                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                                       iplus-fringe (caddr (x))))),
                                    list ('quote, f))
                              case = iplus
                               then list ('if,
                                          list ('integerp, cadr (x)),
                                          list ('equal,
                                              iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                                             iplus-fringe (caddr (x))))),
                                              iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                                             iplus-fringe (caddr (x))))),
                                          list ('quote, f))
                              otherwise x endcase
                        else x endif
                  else x endif
            else x endif
      else x endif
```

THEOREM: cancel-ineg-terms-from-equality-cancel-ineg-terms-from-equality-expanded
cancel-ineg-terms-from-equality-expanded (x)
$=$ cancel-ineg-terms-from-equality (x)

EVENT: Disable cancel-ineg-terms-from-equality-expanded.

THEOREM: integerp-eval\$-iplus-or-ineg-term
iplus-or-ineg-term $(x) \rightarrow$ integerp (eval\$ (**t**, x, a))

EVENT: Disable iplus-or-ineg-term.

THEOREM: eval\$-iplus-list-car-remove-inegs
remove-inegs (x, y)
$\rightarrow$ (iplus-list (eval\$ ('list, car (remove-inegs (x, y)), a))
$=$ iplus (iplus-list (eval\$ ('list, car (split-out-ineg-terms (x)), a)),
iplus-list (eval\$ ('list, cdr (split-out-ineg-terms (y)), a))))

THEOREM: eval\$-iplus-list-cdr-remove-inegs
remove-inegs (x, y)
$\rightarrow$ (iplus-list (eval\$ ('list, cdr (remove-inegs (x, y)), a))
$=$ iplus (iplus-list (eval\$ ('list, car (split-out-ineg-terms (y)), a)),
iplus-list (eval\$ ('list, cdr (split-out-ineg-terms (x)), a))))

THEOREM: minus-ineg
$((x \in \mathbf{N}) \wedge (x \neq 0)) \rightarrow ((-\ x) = \text{ineg}(x))$

THEOREM: iplus-list-eval$-car-split-out-ineg-terms
iplus-list (eval$ ('list, car (split-out-ineg-terms (x)), a))
= iplus (iplus-list (eval$ ('list, x, a)),
iplus-list (eval$ ('list, cdr (split-out-ineg-terms (x)), a)))

EVENT: Disable remove-inegs.

THEOREM: correctness-of-cancel-ineg-terms-from-equality
eval$ (**t**, x, a) = eval$ (**t**, cancel-ineg-terms-from-equality-expanded (x), a)

DEFINITION:
make-cancel-ineg-terms-inequality (x)
= **let** *new-fringes* **be** remove-inegs (iplus-fringe (cadr (x)),
iplus-fringe (caddr (x)))
in
if *new-fringes*
then list ('ilessp,
iplus-tree (car (*new-fringes*)),
iplus-tree (cdr (*new-fringes*)))
else x **endif endlet**

DEFINITION:
cancel-ineg-terms-from-inequality (x)
= **if** listp (x) $\wedge$ (car (x) = 'ilessp)
then if iplus-or-ineg-term (cadr (x))
then make-cancel-ineg-terms-inequality (x)
elseif iplus-or-ineg-term (caddr (x))
then make-cancel-ineg-terms-inequality (x)
else x **endif**
else x **endif**

```
;; The following was created from nqthm-macroexpand with arguments
;; and or make-cancel-ineg-terms-inequality iplus-or-ineg-term
```

DEFINITION:
cancel-ineg-terms-from-inequality-expanded (x)
= **if** listp (x)
then if car (x) = 'ilessp
then if listp (cadr (x))
then case on car (car (cdr (x))):
case = *ineg*

```
        then if remove-inegs (iplus-fringe (cadr (x)),
                              iplus-fringe (caddr (x)))
             then list ('ilessp,
                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))),
                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                       iplus-fringe (caddr (x))))))
             else x endif
        case = iplus
         then if remove-inegs (iplus-fringe (cadr (x)),
                               iplus-fringe (caddr (x)))
              then list ('ilessp,
                         iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                        iplus-fringe (caddr (x))))),
                         iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                        iplus-fringe (caddr (x))))))
              else x endif
        otherwise if listp (caddr (x))
                  then case on car (car (cdr (cdr (x)))):
                       case = ineg
                       then if remove-inegs (iplus-fringe (cadr (x)),
                                             iplus-fringe (caddr (x)))
                            then list ('ilessp,
                                       iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                                      iplus-fringe (caddr (x))))
                                       iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                                      iplus-fringe (caddr (x))))
                            else x endif
                       case = iplus
                        then if remove-inegs (iplus-fringe (cadr (x)),
                                              iplus-fringe (caddr (x)))
                             then list ('ilessp,
                                        iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                                       iplus-fringe (caddr (x))
                                        iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                                       iplus-fringe (caddr (x))
                             else x endif
                       otherwise x endcase
                  else x endif endcase
elseif listp (caddr (x))
then case on car (car (cdr (cdr (x)))):
        case = ineg
        then if remove-inegs (iplus-fringe (cadr (x)),
                              iplus-fringe (caddr (x)))
```

```
                    then list ('ilessp,
                               iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                              iplus-fringe (caddr (x))))),
                               iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                              iplus-fringe (caddr (x))))))
                    else x endif
                case = iplus
                 then if remove-inegs (iplus-fringe (cadr (x)),
                                       iplus-fringe (caddr (x)))
                      then list ('ilessp,
                                 iplus-tree (car (remove-inegs (iplus-fringe (cadr (x)),
                                                                iplus-fringe (caddr (x))))),
                                 iplus-tree (cdr (remove-inegs (iplus-fringe (cadr (x)),
                                                                iplus-fringe (caddr (x))))))
                      else x endif
                otherwise x endcase
            else x endif
        else x endif
    else x endif
```

THEOREM: cancel-ineg-terms-from-inequality-cancel-ineg-terms-from-inequality-expanded
cancel-ineg-terms-from-inequality-expanded (x)
$=$ cancel-ineg-terms-from-inequality (x)

EVENT: Disable cancel-ineg-terms-from-inequality-expanded.

THEOREM: correctness-of-cancel-ineg-terms-from-inequality
eval\$ (**t**, x, a) $=$ eval\$ (**t**, cancel-ineg-terms-from-inequality-expanded (x), a)

EVENT: Disable minus-ineg.

EVENT: Disable integerp-eval\$-iplus-or-ineg-term.

```
; ---------- Eliminating constants ----------

;; We want to combine in terms like (iplus 3 (iplus x 7)).  Also, when
;; two iplus terms are equated or in-equated, there should only be a
;; natural number summand on at most one side.  Finally, if one adds 1
;; to the right side of a strict inequality, a stronger inequality (in
;; a certain sense) is obtained by removing the 1 and making a non-strict
;; inequality in the other direction.
```

THEOREM: plus-iplus
$((i \in \mathbf{N}) \wedge (j \in \mathbf{N})) \rightarrow ((i + j) = \text{iplus}(i, j))$

THEOREM: iplus-constants
$\text{iplus}(1 + i, \text{iplus}(1 + j, x)) = \text{iplus}((1 + i) + (1 + j), x)$

THEOREM: numberp-is-integerp
$(w \in \mathbf{N}) \rightarrow \text{integerp}(w)$

THEOREM: difference-idifference
$((x \in \mathbf{N}) \wedge (y \in \mathbf{N}) \wedge (x \leq y)) \rightarrow ((y - x) = \text{idifference}(y, x))$

THEOREM: cancel-constants-equal-lemma
$((m \in \mathbf{N}) \wedge (n \in \mathbf{N}))$
$\rightarrow \quad ((\text{iplus}(m, x) = \text{iplus}(n, y))$
$\quad = \quad \textbf{if } m < n \textbf{ then } \text{fix-int}(x) = \text{iplus}(n - m, y)$
$\quad \quad \textbf{else } \text{iplus}(m - n, x) = \text{fix-int}(y) \textbf{ endif})$

THEOREM: cancel-constants-equal
$(\text{iplus}(1 + i, x) = \text{iplus}(1 + j, y))$
$= \quad \textbf{if } i < j \textbf{ then } \text{fix-int}(x) = \text{iplus}(j - i, y)$
$\quad \textbf{else } \text{iplus}(i - j, x) = \text{fix-int}(y) \textbf{ endif}$

THEOREM: ilessp-add1
$(y \in \mathbf{N}) \rightarrow (\text{ilessp}(x, 1 + y) = (\neg \text{ ilessp}(y, x)))$

THEOREM: ilessp-add1-iplus
$(y \in \mathbf{N}) \rightarrow (\text{ilessp}(x, \text{iplus}(1 + y, z)) = (\neg \text{ ilessp}(\text{iplus}(y, z), x)))$

THEOREM: cancel-constants-ilessp-lemma-1
$((m \in \mathbf{N}) \wedge (n \in \mathbf{N}))$
$\rightarrow \quad (\text{ilessp}(\text{iplus}(m, x), \text{iplus}(n, y))$
$\quad = \quad \textbf{if } m < n \textbf{ then } \text{ilessp}(x, \text{iplus}(n - m, y))$
$\quad \quad \textbf{else } \text{ilessp}(\text{iplus}(m - n, x), y) \textbf{ endif})$

THEOREM: cancel-constants-ilessp-lemma-2
$((m \in \mathbf{N}) \wedge (n \in \mathbf{N}))$
$\rightarrow \quad (\text{ilessp}(\text{iplus}(m, x), \text{iplus}(n, y))$
$\quad = \quad \textbf{if } m < n \textbf{ then } \neg \text{ ilessp}(\text{iplus}((n - m) - 1, y), x)$
$\quad \quad \textbf{else } \text{ilessp}(\text{iplus}(m - n, x), y) \textbf{ endif})$

THEOREM: cancel-constants-ilessp
$\text{ilessp}(\text{iplus}(1 + i, x), \text{iplus}(1 + j, y))$
$= \quad \textbf{if } i < j \textbf{ then } \neg \text{ ilessp}(\text{iplus}((j - i) - 1, y), x)$
$\quad \textbf{else } \text{ilessp}(\text{iplus}(i - j, x), y) \textbf{ endif}$

EVENT: Disable plus-iplus.

EVENT: Disable numberp-is-integerp.

EVENT: Disable difference-idifference.

```
;; new stuff about integers from rationals developement
```

THEOREM: ilessp-irem
ilessp (irem (x, y), y) = (ilessp (0, y) $\vee$ (izerop (y) $\wedge$ ilessp (x, 0)))

THEOREM: irem-noop
ilessp (iabs (a), iabs (b)) $\rightarrow$ (irem (a, b) = fix-int (a))

THEOREM: irem-of-0
((fix-int (a) = 0) $\rightarrow$ (irem (a, x) = 0))
$\wedge$ ((fix-int (a) = 0) $\rightarrow$ (irem (x, a) = fix-int (x)))

THEOREM: iplus-irem-itimes-iquo
iplus (irem (x, y), itimes (y, iquo (x, y))) = fix-int (x)

EVENT: Disable iplus-irem-itimes-iquo.

THEOREM: irem-iquo-elim
integerp (x) $\rightarrow$ (iplus (irem (x, y), itimes (y, iquo (x, y))) = x)

```
;; irem has a tough-to-deal-with definition.  Here's a better
;; one.
```

DEFINITION:
my-irem (x, y)
= **if** fix-int (x) = 0 **then** 0
elseif negativep (x) **then** ineg (negative-guts (x) **mod** iabs (y))
else x **mod** iabs (y) **endif**

THEOREM: irem-is-my-irem
irem (x, y) = my-irem (x, y)

THEOREM: irem-iplus-0-proof
(irem (b, c) = 0) $\rightarrow$ ((irem (iplus (a, b), c) = 0) = (irem (a, c) = 0))

THEOREM: irem-iplus-0
$(\text{irem}\,(b,\ c) = 0)$
$\rightarrow\quad (((\text{irem}\,(\text{iplus}\,(a,\ b),\ c) = 0) = (\text{irem}\,(a,\ c) = 0))$
$\quad\wedge\quad ((\text{irem}\,(\text{iplus}\,(b,\ a),\ c) = 0) = (\text{irem}\,(a,\ c) = 0)))$

DEFINITION: $\text{igcd}\,(x,\ y) = \text{gcd}\,(\text{iabs}\,(x),\ \text{iabs}\,(y))$

THEOREM: integerp-igcd
$\text{integerp}\,(\text{igcd}\,(x,\ y))$

THEOREM: commutativity-of-igcd
$\text{igcd}\,(x,\ y) = \text{igcd}\,(y,\ x)$

THEOREM: igcd-0
$(\text{igcd}\,(0,\ x) = \text{iabs}\,(x)) \wedge (\text{igcd}\,(x,\ 0) = \text{iabs}\,(x))$

THEOREM: igcd-1
$(\text{igcd}\,(1,\ x) = 1) \wedge (\text{igcd}\,(x,\ 1) = 1)$

THEOREM: equal-igcd-0
$(\text{igcd}\,(a,\ b) = 0) = ((\text{fix-int}\,(a) = 0) \wedge (\text{fix-int}\,(b) = 0))$

THEOREM: igcd-non-negative
$\neg\ \text{ilessp}\,(\text{igcd}\,(x,\ y),\ 0)$

THEOREM: ilessp-igcd
$(\text{ilessp}\,(b,\ \text{igcd}\,(a,\ b))$
$\quad =\quad (\text{ilessp}\,(b,\ 0) \vee ((\text{fix-int}\,(a) \neq 0) \wedge (\text{fix-int}\,(b) = 0))))$
$\wedge\quad (\text{ilessp}\,(b,\ \text{igcd}\,(b,\ a))$
$\quad =\quad (\text{ilessp}\,(b,\ 0) \vee ((\text{fix-int}\,(a) \neq 0) \wedge (\text{fix-int}\,(b) = 0))))$

THEOREM: igcd-iplus-instance-proof
$((\text{ilessp}\,(a,\ 0) = \text{ilessp}\,(b,\ 0)) \vee (\neg\ \text{ilessp}\,(\text{iabs}\,(b),\ \text{iabs}\,(a))))$
$\rightarrow\quad (\text{igcd}\,(a,\ \text{iplus}\,(a,\ b)) = \text{igcd}\,(a,\ b))$

THEOREM: igcd-iplus
$((\text{ilessp}\,(a,\ 0) = \text{ilessp}\,(b,\ 0)) \vee (\neg\ \text{ilessp}\,(\text{iabs}\,(b),\ \text{iabs}\,(a))))$
$\rightarrow\quad ((\text{igcd}\,(a,\ \text{iplus}\,(a,\ b)) = \text{igcd}\,(a,\ b))$
$\quad\wedge\quad (\text{igcd}\,(a,\ \text{iplus}\,(b,\ a)) = \text{igcd}\,(a,\ b)))$

EVENT: Disable igcd.

THEOREM: irem-igcd
$(\text{irem}\,(a,\ \text{igcd}\,(a,\ b)) = 0) \wedge (\text{irem}\,(b,\ \text{igcd}\,(a,\ b)) = 0)$

THEOREM: distributivity-of-itimes-over-igcd-proof
igcd (itimes (x, z), itimes (y, z)) = itimes (iabs (z), igcd (x, y))

THEOREM: distributivity-of-itimes-over-igcd
(igcd (itimes (x, z), itimes (y, z)) = itimes (iabs (z), igcd (x, y)))
∧ (igcd (itimes (x, z), itimes (z, y)) = itimes (iabs (z), igcd (x, y)))
∧ (igcd (itimes (z, x), itimes (y, z)) = itimes (iabs (z), igcd (x, y)))
∧ (igcd (itimes (z, x), itimes (z, y)) = itimes (iabs (z), igcd (x, y)))

THEOREM: common-divisor-divides-igcd
((irem (x, z) = 0) ∧ (irem (y, z) = 0)) → (irem (igcd (x, y), z) = 0)

THEOREM: iabs-igcd
iabs (igcd (x, y)) = igcd (x, y)

THEOREM: associativity-of-igcd
igcd (igcd (x, y), z) = igcd (x, igcd (y, z))

THEOREM: commutativity2-of-igcd
igcd (b, igcd (a, c)) = igcd (a, igcd (b, c))

THEOREM: igcd-x-x
igcd (x, x) = iabs (x)

THEOREM: igcd-idempotence
(igcd (x, igcd (x, y)) = igcd (x, y)) ∧ (igcd (y, igcd (x, y)) = igcd (x, y))

THEOREM: iquo-0
(iquo (x, y) = 0) = ((fix-int (y) = 0) ∨ ilessp (iabs (x), iabs (y)))

THEOREM: ilessp-0-iquo
ilessp (0, iquo (x, y))
= ((ilessp (x, 0) = ilessp (y, 0))
∧ (fix-int (x) ≠ 0)
∧ (fix-int (y) ≠ 0)
∧ (¬ ilessp (iabs (x), iabs (y))))

THEOREM: iabs-simplify
(¬ ilessp (x, 0)) → (iabs (x) = fix-int (x))

THEOREM: igcd-iquo-igcd-proof
igcd (iquo (x, igcd (x, y)), iquo (y, igcd (x, y)))
= **if** (fix-int (x) = 0) ∧ (fix-int (y) = 0) **then** 0
else 1 **endif**

THEOREM: ilessp-iquo-0
ilessp (iquo (x, y), 0)
= ((ilessp (x, 0) $\neq$ ilessp (y, 0))
$\wedge$ (fix-int (x) $\neq$ 0)
$\wedge$ (fix-int (y) $\neq$ 0)
$\wedge$ ($\neg$ ilessp (iabs (x), iabs (y))))

THEOREM: iquo-1
iquo (x, 1) = fix-int (x)

THEOREM: ilessp-0-igcd
ilessp (0, igcd (x, y)) = (($\neg$ izerop (x)) $\vee$ ($\neg$ izerop (y)))

THEOREM: igcd-minus
($\neg$ ilessp (x, 0))
$\rightarrow$ ((igcd ($-$ x, y) = igcd (x, y)) $\wedge$ (igcd (y, $-$ x) = igcd (y, x)))

THEOREM: iquo-0-arg
(iquo (0, x) = 0) $\wedge$ (iquo (x, 0) = 0)

THEOREM: itimes-iquo
(irem (x, y) = 0) $\rightarrow$ (itimes (y, iquo (x, y)) = fix-int (x))

THEOREM: itimes-hack1-1
(integerp (a) $\wedge$ integerp (b) $\wedge$ (irem (a, ad) = 0) $\wedge$ (irem (b, cb) = 0))
$\rightarrow$ (itimes (a, b) = itimes (ad, itimes (cb, itimes (iquo (a, ad), iquo (b, cb)))))

THEOREM: itimes-hack1-1-1
(((($\neg$ integerp (a)) $\vee$ ($\neg$ integerp (b)))
$\wedge$ (irem (a, ad) = 0)
$\wedge$ (irem (b, cb) = 0))
$\rightarrow$ (itimes (a, b) = itimes (ad, itimes (cb, itimes (iquo (a, ad), iquo (b, cb)))))

THEOREM: itimes-hack1-2
(integerp (c) $\wedge$ integerp (d) $\wedge$ (irem (c, cb) = 0) $\wedge$ (irem (d, ad) = 0))
$\rightarrow$ (itimes (c, d) = itimes (ad, itimes (cb, itimes (iquo (c, cb), iquo (d, ad)))))

THEOREM: itimes-hack1-2-1
(((($\neg$ integerp (c)) $\vee$ ($\neg$ integerp (d)))
$\wedge$ (irem (c, cb) = 0)
$\wedge$ (irem (d, ad) = 0))
$\rightarrow$ (itimes (c, d) = itimes (ad, itimes (cb, itimes (iquo (c, cb), iquo (d, ad)))))

THEOREM: itimes-hack1
((irem (a, ad) = 0)
$\wedge$ (irem (b, cb) = 0)

$\wedge$ (irem $(c,\ cb) = 0$)
$\wedge$ (irem $(d,\ ad) = 0$)
$\wedge$ (iquo $(a,\ ad)$ = iquo $(c,\ cb)$)
$\wedge$ (iquo $(d,\ ad)$ = iquo $(b,\ cb)$))
$\rightarrow$ ((itimes $(a,\ b)$ = itimes $(c,\ d)$) = **t**)

THEOREM: iquo-x-x
iquo $(x,\ x)$
= **if** izerop (x) **then** 0
else 1 **endif**

THEOREM: iquo-0-arg-better
(fix-int $(z) = 0$) $\rightarrow$ ((iquo $(z,\ x) = 0$) $\wedge$ (iquo $(x,\ z) = 0$))

THEOREM: itimes-hack2
((iquo $(a,$ igcd $(a,\ d))$ = iquo $(c,$ igcd $(c,\ b)))$
$\wedge$ (iquo $(d,$ igcd $(a,\ d))$ = iquo $(b,$ igcd $(c,\ b))))$
$\rightarrow$ ((itimes $(a,\ b)$ = itimes $(c,\ d)$) = **t**)

```
;;;;;;
;;;;; Following until gcd-remainder-times-fact1-proof based on something
;;;;; originally suggested by matt kaufmann
;;;;;;
```

THEOREM: gcd-factors-accept
ordinalp (cons $(1 + x,$ fix $(y))$)
$\wedge$ (($(x \not\simeq 0) \wedge (y \not\simeq 0) \wedge (x < y)$)
$\rightarrow$ ord-lessp (cons $(1 + x,$ fix $(y - x))$, cons $(1 + x,$ fix $(y))$))
$\wedge$ (($(x \not\simeq 0) \wedge (y \not\simeq 0) \wedge (x \not< y)$)
$\rightarrow$ ord-lessp (cons $(1 + (x - y),$ fix $(y))$, cons $(1 + x,$ fix $(y))$))

DEFINITION:
gcd-factors $(x,\ y)$
= **if** $x \simeq 0$ **then** cons $(0,\ 1)$
elseif $y \simeq 0$ **then** cons $(1,\ 0)$
elseif $x < y$
then let *factors* **be** gcd-factors $(x,\ y - x)$
in
cons (idifference (car (*factors*), cdr (*factors*)), cdr (*factors*)) **endlet**
else let *factors* **be** gcd-factors $(x - y,\ y)$
in
cons (car (*factors*),
idifference (cdr (*factors*), car (*factors*))) **endlet endif**

THEOREM: gcd-factors-gives-linear-combination

let *factors* **be** gcd-factors $(x,\ y)$
in
let a **be** car $(factors)$,
b **be** cdr $(factors)$
in
$((x \in \mathbf{N}) \wedge (y \in \mathbf{N}))$
$\rightarrow$ (iplus (itimes $(a,\ x)$, itimes $(b,\ y)$) = gcd $(x,\ y)$) **endlet endlet**

THEOREM: gcd-factors-gives-linear-combination-rewrite
let *factors* **be** gcd-factors $(x,\ y)$
in
let a **be** car $(factors)$,
b **be** cdr $(factors)$
in
$((x \in \mathbf{N}) \wedge (y \in \mathbf{N}))$
$\rightarrow$ (gcd $(x,\ y)$ = iplus (itimes $(a,\ x)$, itimes $(b,\ y)$)) **endlet endlet**

THEOREM: remainder-0-sufficiency
$((x \in \mathbf{N}) \wedge (c \in \mathbf{N}) \wedge$ (itimes $(x,\ p) = c)$)
$\rightarrow$ $(((c$ **mod** $x) = 0) = \mathbf{t})$

THEOREM: itimes-iquotient
(iremainder $(a,\ x) = 0) \rightarrow$ (itimes $(x,$ iquotient $(a,\ x)) =$ fix-int (a))

THEOREM: iquotient-0
iquotient $(0,\ x) = 0$

THEOREM: iremainder-0
(iremainder $(0,\ x) = 0) \wedge$ (iremainder $(x,\ 0) =$ fix-int (x))

THEOREM: itimes-iplus-hack
$((x \in \mathbf{N}) \wedge (y \in \mathbf{N}) \wedge (c \in \mathbf{N}) \wedge$ (iremainder (itimes $(c,\ y),\ x) = 0$))
$\rightarrow$ (itimes $(x,$ iplus (itimes $(c,\ a)$, itimes $(b,$ iquotient (itimes $(c,\ y),\ x)))$)
= itimes $(c,$ iplus (itimes $(a,\ x)$, itimes $(b,\ y)))$)

THEOREM: irem-0-iremainder-0-help1
(iremainder $(x,\ y) = 0) \rightarrow$ (irem $(x,\ y) = 0$)

THEOREM: irem-0-iremainder-0-help2
(irem $(x,\ y) = 0) \rightarrow$ (iremainder $(x,\ y) = 0$)

THEOREM: irem-0-iremainder-0
(iremainder $(x,\ y) = 0) =$ (irem $(x,\ y) = 0$)

THEOREM: equal-itimes-x-x
((itimes $(x,\ y) = x) =$ ((integerp $(x) \wedge (y = 1)) \vee (x = 0)$))
$\wedge$ ((itimes $(y,\ x) = x) =$ ((integerp $(x) \wedge (y = 1)) \vee (x = 0)$))

THEOREM: divides-product-reduction-helper-1
$((x \in \mathbf{N}) \wedge (y \in \mathbf{N}) \wedge (c \in \mathbf{N}) \wedge (((c * y)\ \mathbf{mod}\ x) = 0))$
$\rightarrow\ (\text{iremainder}\,(\text{itimes}\,(c,\ y),\ x) = 0)$

THEOREM: divides-product-reduction-helper
$((x \in \mathbf{N}) \wedge (y \in \mathbf{N}) \wedge (c \in \mathbf{N}) \wedge (\gcd\,(x,\ y) = 1) \wedge ((c\ \mathbf{mod}\ x) \neq 0))$
$\rightarrow\ (((c * y)\ \mathbf{mod}\ x) \neq 0)$

EVENT: Disable divides-product-reduction-helper-1.

THEOREM: divides-product-reduction
$((x \in \mathbf{N}) \wedge (y \in \mathbf{N}) \wedge (c \in \mathbf{N}) \wedge (\gcd\,(x,\ y) = 1) \wedge ((c\ \mathbf{mod}\ x) \neq 0))$
$\rightarrow\ ((((c * y)\ \mathbf{mod}\ x) \neq 0) \wedge (((y * c)\ \mathbf{mod}\ x) \neq 0))$

THEOREM: gcd-remainder-times-fact1-proof-non-numberp-case
$(((a \notin \mathbf{N}) \vee (b \notin \mathbf{N}) \vee (c \notin \mathbf{N})) \wedge (\gcd\,(a,\ b) = 1))$
$\rightarrow\ ((((b * c)\ \mathbf{mod}\ a) = 0) = ((c\ \mathbf{mod}\ a) = 0))$

THEOREM: gcd-remainder-times-fact1-proof-numberp-case
$((a \in \mathbf{N}) \wedge (b \in \mathbf{N}) \wedge (c \in \mathbf{N}) \wedge (\gcd\,(a,\ b) = 1))$
$\rightarrow\ ((((b * c)\ \mathbf{mod}\ a) = 0) = ((c\ \mathbf{mod}\ a) = 0))$

THEOREM: gcd-remainder-times-fact1-proof
$(\gcd\,(a,\ b) = 1) \rightarrow ((((b * c)\ \mathbf{mod}\ a) = 0) = ((c\ \mathbf{mod}\ a) = 0))$

THEOREM: divides-each-equality
$(((a\ \mathbf{mod}\ b) = 0) \wedge ((b\ \mathbf{mod}\ a) = 0)) = (\text{fix}\,(a) = \text{fix}\,(b))$

```
;;; Before we go on, prove, disable, and set up theory about
;;; naturals --> integers
```

THEOREM: times-to-itimes
$(a * b)$
$=\ \mathbf{if}\ \text{ilessp}\,(a,\ 0) \vee \text{ilessp}\,(b,\ 0)\ \mathbf{then}\ 0$
$\quad\ \mathbf{else}\ \text{itimes}\,(a,\ b)\ \mathbf{endif}$

EVENT: Disable times-to-itimes.

THEOREM: quotient-to-iquo
$(a \div b)$
$=\ \mathbf{if}\ \text{ilessp}\,(a,\ 0) \vee \text{ilessp}\,(b,\ 0)\ \mathbf{then}\ 0$
$\quad\ \mathbf{else}\ \text{iquo}\,(a,\ b)\ \mathbf{endif}$

EVENT: Disable quotient-to-iquo.

THEOREM: zerop-izerop
$(a \simeq 0)$
$=$ **if** ilessp $(a,\ 0)$ **then t**
else izerop (a) **endif**

EVENT: Disable zerop-izerop.

THEOREM: fix-to-fix-int
fix (a)
$=$ **if** ilessp $(a,\ 0)$ **then** 0
else fix-int (a) **endif**

EVENT: Disable fix-to-fix-int.

THEOREM: plus-iplus2
$(x + y)$
$=$ **if** ilessp $(x,\ 0)$
then if ilessp $(y,\ 0)$ **then** 0
else fix-int (y) **endif**
elseif ilessp $(y,\ 0)$ **then** fix-int (x)
else iplus $(x,\ y)$ **endif**

EVENT: Disable plus-iplus2.

THEOREM: ilessp-lessp
$(x < y)$
$=$ **if** ilessp $(x,\ 0)$
then if ilessp $(y,\ 0)$ **then f**
else ilessp $(0,\ y)$ **endif**
else ilessp $(x,\ y)$ **endif**

EVENT: Disable ilessp-lessp.

THEOREM: numberp-ilessp
$(x \in \mathbf{N}) = ((x = 0) \vee$ ilessp $(0,\ x))$

EVENT: Disable numberp-ilessp.

THEOREM: gcd-is-igcd
gcd $(x,\ y)$
$=$ **if** ilessp $(x,\ 0)$
then if ilessp $(y,\ 0)$ **then** 0

else fix-int (y) **endif**
elseif ilessp $(y,\ 0)$ **then** fix-int (x)
else igcd $(x,\ y)$ **endif**

EVENT: Disable gcd-is-igcd.

THEOREM: negativep-ilessp
integerp $(x) \rightarrow$ (negativep (x) = ilessp $(x,\ 0)$)

EVENT: Disable negativep-ilessp.

THEOREM: remainder-to-irem
$(x$ **mod** $y)$
= **if** ilessp $(x,\ 0)$ **then** 0
elseif ilessp $(y,\ 0)$ **then** fix (x)
else irem $(x,\ y)$ **endif**

EVENT: Disable remainder-to-irem.

THEOREM: difference-idifference2
$(x - y)$
= **if** ilessp $(x,\ 0)$ **then** 0
elseif ilessp $(y,\ 0)$ **then** fix-int (x)
elseif ilessp $(x,\ y)$ **then** 0
else idifference $(x,\ y)$ **endif**

EVENT: Disable difference-idifference2.

THEOREM: add1-iplus
$(1 + x)$
= **if** $x \in$ **N** **then** iplus $(1,\ x)$
else 1 **endif**

EVENT: Disable add1-iplus.

EVENT: Let us define the theory *nats-to-ints* to consist of the following events: add1-iplus, difference-idifference2, remainder-to-irem, negativep-ilessp, gcd-is-igcd, numberp-ilessp, ilessp-lessp, plus-iplus2, fix-to-fix-int, fix-to-fix-int, zerop-izerop, quotient-to-iquo, times-to-itimes.

THEOREM: times-gcd-fact-proof-1
$((\text{gcd}\ (a,\ c) = 1) \wedge (\text{gcd}\ (b,\ d) = 1))$

$\rightarrow \quad (((\text{fix}\,(a) = \text{fix}\,(d)) \wedge (\text{fix}\,(b) = \text{fix}\,(c)))$
$\quad\quad \rightarrow \quad ((a * b) = (c * d)))$

THEOREM: times-gcd-fact-proof-2-1
$((\text{gcd}\,(a,\ c) = 1) \wedge (\text{gcd}\,(b,\ d) = 1) \wedge ((d\ \textbf{mod}\ a) = 0))$
$\rightarrow \quad (((a * b) = (c * d))$
$\quad\quad \rightarrow \quad ((\text{fix}\,(a) = \text{fix}\,(d)) \wedge (\text{fix}\,(b) = \text{fix}\,(c))))$

THEOREM: times-gcd-fact-proof-2-2
$((a * b) = (c * d)) \rightarrow (((c * d)\ \textbf{mod}\ a) = 0)$

THEOREM: times-gcd-fact-proof-2-3
$((\text{gcd}\,(a,\ c) = 1) \wedge (((c * d)\ \textbf{mod}\ a) = 0)) \rightarrow ((d\ \textbf{mod}\ a) = 0)$

THEOREM: times-gcd-fact-proof-2
$((\text{gcd}\,(a,\ c) = 1) \wedge (\text{gcd}\,(b,\ d) = 1))$
$\rightarrow \quad (((a * b) = (c * d))$
$\quad\quad \rightarrow \quad ((\text{fix}\,(a) = \text{fix}\,(d)) \wedge (\text{fix}\,(b) = \text{fix}\,(c))))$

THEOREM: times-gcd-fact-proof
$((\text{gcd}\,(a,\ c) = 1) \wedge (\text{gcd}\,(b,\ d) = 1))$
$\rightarrow \quad (((a * b) = (c * d))$
$\quad\quad = \quad ((\text{fix}\,(a) = \text{fix}\,(d)) \wedge (\text{fix}\,(b) = \text{fix}\,(c))))$

THEOREM: times-gcd-fact
$((\text{gcd}\,(a,\ c) = 1) \wedge (\text{gcd}\,(b,\ d) = 1))$
$\rightarrow \quad ((((a * b) = (c * d))$
$\quad\quad = \quad ((\text{fix}\,(a) = \text{fix}\,(d)) \wedge (\text{fix}\,(b) = \text{fix}\,(c))))$
$\quad\quad \wedge \quad (((b * a) = (c * d))$
$\quad\quad\quad\quad = \quad ((\text{fix}\,(a) = \text{fix}\,(d)) \wedge (\text{fix}\,(b) = \text{fix}\,(c)))))$

```
;; poor choice of symbols a/c and d/b
```

THEOREM: itimes-igcd-fact-proof
$((\text{igcd}\,(a,\ c) = 1) \wedge (\text{igcd}\,(b,\ d) = 1) \wedge \text{ilessp}\,(0,\ b) \wedge \text{ilessp}\,(0,\ c))$
$\rightarrow \quad ((\text{itimes}\,(a,\ b) = \text{itimes}\,(c,\ d))$
$\quad\quad = \quad ((\text{fix-int}\,(a) = \text{fix-int}\,(d)) \wedge (\text{fix-int}\,(b) = \text{fix-int}\,(c))))$

THEOREM: itimes-igcd-fact
$((\text{igcd}\,(a,\ c) = 1) \wedge (\text{igcd}\,(b,\ d) = 1) \wedge \text{ilessp}\,(0,\ b) \wedge \text{ilessp}\,(0,\ c))$
$\rightarrow \quad (((\text{itimes}\,(a,\ b) = \text{itimes}\,(c,\ d))$
$\quad\quad = \quad ((\text{fix-int}\,(a) = \text{fix-int}\,(d)) \wedge (\text{fix-int}\,(b) = \text{fix-int}\,(c))))$
$\quad\quad \wedge \quad ((\text{itimes}\,(b,\ a) = \text{itimes}\,(c,\ d))$
$\quad\quad\quad\quad = \quad ((\text{fix-int}\,(a) = \text{fix-int}\,(d))$
$\quad\quad\quad\quad\quad\quad \wedge \quad (\text{fix-int}\,(b) = \text{fix-int}\,(c))))$
$\quad\quad \wedge \quad ((\text{itimes}\,(a,\ b) = \text{itimes}\,(d,\ c))$

$$
\begin{array}{lll}
 & = & ((\text{fix-int}\,(a) = \text{fix-int}\,(d)) \\
 & & \quad \wedge \quad (\text{fix-int}\,(b) = \text{fix-int}\,(c)))) \\
\wedge & & ((\text{itimes}\,(b,\ a) = \text{itimes}\,(d,\ c)) \\
 & = & ((\text{fix-int}\,(a) = \text{fix-int}\,(d)) \\
 & & \quad \wedge \quad (\text{fix-int}\,(b) = \text{fix-int}\,(c)))))
\end{array}
$$

THEOREM: itimes-iquo-general
$(\text{irem}\,(x,\ y) = 0)$
$\rightarrow \quad ((\text{itimes}\,(\text{iquo}\,(x,\ y),\ z) = \text{iquo}\,(\text{itimes}\,(x,\ z),\ y))$
$\quad \wedge \quad (\text{itimes}\,(z,\ \text{iquo}\,(x,\ y)) = \text{iquo}\,(\text{itimes}\,(x,\ z),\ y)))$

```
; another copy so that itimes-iquo-general doesn't get fired first
```

THEOREM: itimes-iquo-copy
$(\text{irem}\,(x,\ y) = 0) \rightarrow (\text{itimes}\,(y,\ \text{iquo}\,(x,\ y)) = \text{fix-int}\,(x))$

THEOREM: equal-iquo-iquo
$((\text{irem}\,(x,\ y) = 0) \wedge (\text{irem}\,(z,\ y) = 0))$
$\rightarrow \quad ((\text{iquo}\,(x,\ y) = \text{iquo}\,(z,\ y)) = (\text{fix-int}\,(x) = \text{fix-int}\,(z)))$

THEOREM: idifference-x-x
$\text{idifference}\,(x,\ x) = 0$

THEOREM: irem-iquo-itimes-proof
$((\text{irem}\,(a,\ y) = 0) \wedge (\text{irem}\,(b,\ z) = 0))$
$\rightarrow \quad (\text{irem}\,(\text{iquo}\,(\text{itimes}\,(a,\ b),\ y),\ z) = 0)$

THEOREM: irem-iquo-itimes
$((\text{irem}\,(a,\ y) = 0) \wedge (\text{irem}\,(b,\ z) = 0))$
$\rightarrow \quad ((\text{irem}\,(\text{iquo}\,(\text{itimes}\,(a,\ b),\ y),\ z) = 0)$
$\quad \wedge \quad (\text{irem}\,(\text{iquo}\,(\text{itimes}\,(b,\ a),\ y),\ z) = 0))$

THEOREM: equal-irem-itimes-0
$((\text{irem}\,(x,\ z) = 0) \vee (\text{irem}\,(y,\ z) = 0)) \rightarrow (\text{irem}\,(\text{itimes}\,(x,\ y),\ z) = 0)$

THEOREM: commutativity-of-iquo
$(\text{irem}\,(a,\ \text{itimes}\,(b,\ c)) = 0) \rightarrow (\text{iquo}\,(\text{iquo}\,(a,\ c),\ b) = \text{iquo}\,(\text{iquo}\,(a,\ b),\ c))$

THEOREM: irem-itimes
$((\text{irem}\,(x,\ y) = 0) \wedge (\text{irem}\,(\text{iquo}\,(x,\ y),\ z) = 0))$
$\rightarrow \quad (\text{irem}\,(x,\ \text{itimes}\,(y,\ z)) = 0)$

THEOREM: iquo-igcd-itimes-proof1
$(\text{ilessp}\,(0,\ b) \wedge \text{ilessp}\,(0,\ d) \wedge (\text{itimes}\,(a,\ d) = \text{itimes}\,(b,\ c)))$
$\rightarrow \quad ((\text{iquo}\,(a,\ \text{igcd}\,(a,\ b)) = \text{iquo}\,(c,\ \text{igcd}\,(c,\ d))) = \mathbf{t})$

THEOREM: iquo-igcd-itimes-proof2
$(\text{ilessp}(0,\ b) \wedge \text{ilessp}(0,\ d) \wedge (\text{itimes}(a,\ d) = \text{itimes}(b,\ c)))$
$\rightarrow\quad ((\text{iquo}(b,\ \text{igcd}(a,\ b)) = \text{iquo}(d,\ \text{igcd}(c,\ d))) = \mathbf{t})$

THEOREM: iquo-igcd-itimes1
$(\text{ilessp}(0,\ b) \wedge \text{ilessp}(0,\ d) \wedge (\text{itimes}(a,\ d) = \text{itimes}(b,\ c)))$
$\rightarrow\quad ((\text{iquo}(a,\ \text{igcd}(a,\ b)) = \text{iquo}(c,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(b,\ \text{igcd}(a,\ b)) = \text{iquo}(d,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(a,\ \text{igcd}(b,\ a)) = \text{iquo}(c,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(b,\ \text{igcd}(b,\ a)) = \text{iquo}(d,\ \text{igcd}(c,\ d))))$

THEOREM: iquo-igcd-itimes2
$(\text{ilessp}(0,\ b) \wedge \text{ilessp}(0,\ d) \wedge (\text{itimes}(d,\ a) = \text{itimes}(b,\ c)))$
$\rightarrow\quad ((\text{iquo}(a,\ \text{igcd}(a,\ b)) = \text{iquo}(c,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(b,\ \text{igcd}(a,\ b)) = \text{iquo}(d,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(a,\ \text{igcd}(b,\ a)) = \text{iquo}(c,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(b,\ \text{igcd}(b,\ a)) = \text{iquo}(d,\ \text{igcd}(c,\ d))))$

THEOREM: iquo-igcd-itimes3
$(\text{ilessp}(0,\ b) \wedge \text{ilessp}(0,\ d) \wedge (\text{itimes}(a,\ d) = \text{itimes}(c,\ b)))$
$\rightarrow\quad ((\text{iquo}(a,\ \text{igcd}(a,\ b)) = \text{iquo}(c,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(b,\ \text{igcd}(a,\ b)) = \text{iquo}(d,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(a,\ \text{igcd}(b,\ a)) = \text{iquo}(c,\ \text{igcd}(c,\ d)))$
$\wedge\quad (\text{iquo}(b,\ \text{igcd}(b,\ a)) = \text{iquo}(d,\ \text{igcd}(c,\ d))))$

THEOREM: equal-iquo-1
$(\text{irem}(x,\ y) = 0)$
$\rightarrow\quad ((\text{iquo}(x,\ y) = 1)$
$=\quad ((\text{fix-int}(x) = \text{fix-int}(y))$
$\wedge\quad (\text{fix-int}(x) \neq 0)$
$\wedge\quad (\text{fix-int}(y) \neq 0)))$

```
#| replaced by below
(prove-lemma equal-x-gcd-x-y (rewrite)
       (implies
        (numberp y)
       (equal
        (equal x (gcd x y))
        (and
         (numberp x)
         (equal (remainder y x) 0))))
       ((enable-theory naturals)))
|#
```

THEOREM: equal-x-igcd-x-y-proof
$(x = \text{igcd}\,(x,\ y))$
$= \quad ((\neg\ \text{ilessp}\,(x,\ 0)) \wedge \text{integerp}\,(x) \wedge (\text{irem}\,(y,\ x) = 0))$

THEOREM: equal-x-igcd-x-y
$((x = \text{igcd}\,(x,\ y))$
$= \quad ((\neg\ \text{ilessp}\,(x,\ 0)) \wedge \text{integerp}\,(x) \wedge (\text{irem}\,(y,\ x) = 0)))$
$\wedge \quad ((x = \text{igcd}\,(y,\ x))$
$= \quad ((\neg\ \text{ilessp}\,(x,\ 0)) \wedge \text{integerp}\,(x) \wedge (\text{irem}\,(y,\ x) = 0)))$

THEOREM: ilessp-iplus-igcd
$(\text{ilessp}\,(0,\ \text{iplus}\,(x,\ \text{igcd}\,(x,\ y)))$
$= \quad (\text{ilessp}\,(0,\ x) \vee ((\text{fix-int}\,(x) = 0) \wedge (\text{fix-int}\,(y) \neq 0))))$
$\wedge \quad (\text{ilessp}\,(0,\ \text{iplus}\,(x,\ \text{igcd}\,(y,\ x)))$
$= \quad (\text{ilessp}\,(0,\ x) \vee ((\text{fix-int}\,(x) = 0) \wedge (\text{fix-int}\,(y) \neq 0))))$

THEOREM: ilessp-iabs-arg1
$\text{ilessp}\,(\text{iabs}\,(x),\ y) = (\text{ilessp}\,(x,\ y) \wedge \text{ilessp}\,(\text{ineg}\,(x),\ y))$

THEOREM: ilessp-iabs-arg2
$\text{ilessp}\,(x,\ \text{iabs}\,(y)) = (\text{ilessp}\,(x,\ y) \vee \text{ilessp}\,(x,\ \text{ineg}\,(y)))$

THEOREM: igcd-fix-int
$(\text{igcd}\,(\text{fix-int}\,(x),\ y) = \text{igcd}\,(x,\ y)) \wedge (\text{igcd}\,(x,\ \text{fix-int}\,(y)) = \text{igcd}\,(x,\ y))$

THEOREM: iquo-iquo
$\text{iquo}\,(\text{iquo}\,(a,\ b),\ c) = \text{iquo}\,(a,\ \text{itimes}\,(b,\ c))$

THEOREM: iplus-iquo-iquo
$((\text{irem}\,(x,\ z) = 0) \wedge (\text{irem}\,(y,\ z) = 0))$
$\rightarrow \quad (\text{iplus}\,(\text{iquo}\,(x,\ z),\ \text{iquo}\,(y,\ z)) = \text{iquo}\,(\text{iplus}\,(x,\ y),\ z))$

THEOREM: igcd-iquo-iquo
$((\text{irem}\,(x,\ z) = 0) \wedge (\text{irem}\,(y,\ z) = 0))$
$\rightarrow \quad (\text{igcd}\,(\text{iquo}\,(x,\ z),\ \text{iquo}\,(y,\ z)) = \text{iquo}\,(\text{igcd}\,(x,\ y),\ \text{iabs}\,(z)))$

THEOREM: iabs-ineg
$\text{iabs}\,(\text{ineg}\,(x)) = \text{iabs}\,(x)$

THEOREM: iquo-ineg
$(\text{iquo}\,(\text{ineg}\,(x),\ y) = \text{ineg}\,(\text{iquo}\,(x,\ y)))$
$\wedge \quad (\text{iquo}\,(x,\ \text{ineg}\,(y)) = \text{ineg}\,(\text{iquo}\,(x,\ y)))$

THEOREM: igcd-ineg
$(\text{igcd}\,(\text{ineg}\,(x),\ y) = \text{igcd}\,(x,\ y)) \wedge (\text{igcd}\,(x,\ \text{ineg}\,(y)) = \text{igcd}\,(x,\ y))$

THEOREM: igcd-0-better
(fix-int $(x) = 0$)
$\rightarrow$ ((igcd $(x, y) =$ iabs $(y)) \wedge$ (igcd $(y, x) =$ iabs $(y)))$

THEOREM: not-integerp-means
($\neg$ integerp $(x)) \rightarrow$ (fix-int $(x) = 0$)

THEOREM: fix-int-on-non-0
(ilessp $(0, x) \vee$ ilessp $(x, 0)) \rightarrow$ (fix-int $(x) = x$)

EVENT: Disable fix-int-on-non-0.

THEOREM: ilessp-itimes-igcd-hack
ilessp (itimes (y, x), igcd (x, z))
$=$ (((fix-int $(x) = 0) \wedge$ (fix-int $(z) \neq 0))$
$\vee$ ((fix-int $(y) = 0$)
$\wedge$ ((fix-int $(x) \neq 0) \vee$ (fix-int $(y) \neq 0)))$
$\vee$ (ilessp $(0, x) \wedge$ ilessp $(y, 0))$
$\vee$ (ilessp $(0, y) \wedge$ ilessp $(x, 0)))$

```
;;;; a few rules to reduce terms like (irem (itimes ...) (itimes ...))
;;;; note that itimes commutativity rules makes our life simpler
```

THEOREM: irem-0-backchain
(irem $(b, c) = 0) \rightarrow$ (irem (itimes $(a, b), c) = 0$)

THEOREM: irem-itimes-cancel
irem (itimes (a, b), itimes $(a, c)) =$ itimes $(a,$ irem $(b, c))$

THEOREM: irem-itimes-base
(irem (itimes $(a, b), a) = 0) \wedge$ (irem (itimes $(b, a), a) = 0$)

THEOREM: fix-int-minus
fix-int $(-x)$
$=$ **if** $x \simeq 0$ **then** 0
else $-x$ **endif**

THEOREM: iquo-iplus
((irem $(x, z) = 0) \wedge$ (irem $(y, z) = 0))$
$\rightarrow$ (iquo (iplus $(x, y), z) =$ iplus (iquo (x, z), iquo $(y, z)))$

EVENT: Disable iplus-iquo-iquo.

THEOREM: ilessp-0-iplus-open
ilessp (0, iplus (x, y))
= ((ilessp (0, x) ∧ ilessp (0, y))
∨ (ilessp (0, x) ∧ ilessp (iabs (y), x))
∨ (ilessp (0, y) ∧ ilessp (iabs (x), y)))

THEOREM: equal-iquo-0
(iquo (x, y) = 0) = (izerop (y) ∨ ilessp (iabs (x), iabs (y)))

THEOREM: iabs-open-as-integers
iabs (x)
= **if** ilessp (x, 0) **then** ineg (x)
else fix-int (x) **endif**

```
;; doesn't work with correctness-of-cancel-ineg-terms-from-inequality!
```

EVENT: Disable iabs-open-as-integers.

THEOREM: ilessp-itimes-igcd-hack2
ilessp (itimes (x, y), igcd (x, z))
= (((fix-int (x) = 0) ∧ (fix-int (z) ≠ 0))
∨ ((fix-int (y) = 0)
∧ ((fix-int (x) ≠ 0) ∨ (fix-int (y) ≠ 0)))
∨ (ilessp (0, x) ∧ ilessp (y, 0))
∨ (ilessp (0, y) ∧ ilessp (x, 0)))

THEOREM: ilessp-ineg-igcd-hack
ilessp (ineg (itimes (c, y)), igcd (c, d))
= (ilessp (0, itimes (c, y))
∨ ((itimes (c, y) = 0) ∧ ilessp (0, igcd (c, d))))

THEOREM: ilessp-iquo
(ilessp (0, x) ∧ (irem (y, x) = 0) ∧ (irem (z, x) = 0))
→ (ilessp (iquo (y, x), iquo (z, x)) = ilessp (y, z))

EVENT: Disable ilessp-0-iplus-open.

THEOREM: ilessp-minus-0
ilessp (− x, 0) = ilessp (0, x)

THEOREM: equal-fix-int-y
(fix-int (y) ≠ 0)
→ (((fix-int (x) = y) = (x = y))
∧ ((y = fix-int (x)) = (y = x)))

THEOREM: iabs-fix-int
iabs (fix-int (x)) = iabs (x)

THEOREM: equal-x-iabs-x
(x = iabs (x)) = (integerp (x) $\wedge$ ($\neg$ ilessp (x, 0)))

THEOREM: equal-fix-int-iabs
(fix-int (x) = iabs (x)) = ($\neg$ ilessp (x, 0))

THEOREM: iabs-iabs
iabs (iabs (x)) = iabs (x)

THEOREM: fix-int-igcd
fix-int (igcd (x, y)) = igcd (x, y)

THEOREM: not-integerp
(($x \notin \mathbf{N}$) $\wedge$ ($\neg$ negativep (x))) $\rightarrow$ ($\neg$ integerp (x))

THEOREM: igcd-iplus-ineg
(igcd (iplus (x, ineg (y)), z) = igcd (iplus (y, ineg (x)), z))
$\wedge$ (igcd (z, iplus (x, ineg (y))) = igcd (z, iplus (y, ineg (x))))

THEOREM: negativep-iplus-ineg
($\neg$ negativep (iplus (x, ineg (y))))
$\rightarrow$ (negativep (iplus (y, ineg (x))) = (fix-int (x) $\neq$ fix-int (y)))

THEOREM: negativep-iplus-ineg2
negativep (iplus (x, ineg (y))) $\rightarrow$ ($\neg$ negativep (iplus (y, ineg (x))))

```
;;; some integer facts needed to prove the rational facts needed
;;; in Bill Young's challenge
```

THEOREM: igcd-iplus-itimes-hack
igcd (iplus (itimes (x, y), itimes (x, z)), itimes (x, p))
= itimes (iabs (x), igcd (iplus (y, z), p))

THEOREM: iquo-itimes-iabs
(irem (y, z) = 0)
$\rightarrow$ (iquo (itimes (x, y), itimes (iabs (x), z))
= **if** ilessp (x, 0) **then** ineg (iquo (y, z))
elseif izerop (x) **then** 0
else iquo (y, z) **endif**)

THEOREM: itimes-2
itimes (2, x) = iplus (x, x)

THEOREM: iquo-iplus-itimes-iabs-hack
(irem (iplus (y, z), p) = 0)
→ (iquo (iplus (itimes (x, y), itimes (x, z)), itimes (iabs (x), p))
= **if** ilessp (x, 0) **then** ineg (iquo (iplus (y, z), p))
elseif izerop (x) **then** 0
else iquo (iplus (y, z), p) **endif**)

THEOREM: iabs-0
((iabs (x) = 0) = (fix-int (x) = 0))
∧ ((fix-int (x) = 0) → (iabs (x) = 0))

THEOREM: ilessp-0-iabs
ilessp (0, iabs (x)) = (ilessp (0, x) ∨ ilessp (x, 0))

```
;; stupid rule
;;(lemma ilessp-neg-pos (rewrite)
;;        (and
;;       (implies
;;        (and
;;         (ilessp 0 x)
;;         (not (ilessp 0 y)))
;;        (ilessp y x))
;;       (implies
;;        (and
;;         (not (ilessp x 0))
;;         (ilessp y 0))
;;        (ilessp y x))
;;       (implies
;;        (and
;;         (not (ilessp x 0))
;;         (not (ilessp 0 y)))
;;        (not (ilessp x y))))
;;        ((enable-theory integer-defns naturals)))

;; should include ilessp-iplus-hacks2 below
```

THEOREM: ilessp-iplus-hacks
(((¬ ilessp (0, x)) ∧ (¬ ilessp (0, y))) → (¬ ilessp (0, iplus (x, y))))
∧ (((¬ ilessp (y, 0)) ∧ ilessp (x, z))
→ (ilessp (x, iplus (y, z)) ∧ ilessp (x, iplus (z, y))))
∧ (((¬ ilessp (x, 0)) ∧ (¬ ilessp (y, 0)))
→ (¬ ilessp (iplus (x, y), 0)))
∧ ((ilessp (0, x) ∧ (¬ ilessp (y, 0)))
→ (ilessp (0, iplus (x, y)) ∧ ilessp (0, iplus (y, x))))
∧ (((¬ ilessp (x, 0)) ∧ (¬ ilessp (y, z)))
→ ((¬ ilessp (iplus (y, x), z)) ∧ (¬ ilessp (iplus (x, y), z))))

THEOREM: ilessp-iplus-hacks2
(ilessp $(x, 0) \wedge (\neg$ ilessp $(0, y)))$
$\rightarrow$ (ilessp (iplus $(x, y), 0) \wedge$ ilessp (iplus $(y, x), 0))$

THEOREM: ilessp-iplus-hacks3
((ilessp $(x, 0) \wedge (\neg$ ilessp $(x, y)))$
$\rightarrow$ (ilessp (iplus $(x, y), 0) \wedge$ ilessp (iplus $(y, x), 0)))$
$\wedge$ ((ilessp $(0, x) \wedge (\neg$ ilessp $(y, x)))$
$\rightarrow$ (ilessp (0, iplus $(x, y)) \wedge$ ilessp (0, iplus $(y, x))))$
$\wedge$ ((ilessp $(x, y) \wedge (\neg$ ilessp $(0, y)))$
$\rightarrow$ (ilessp (iplus $(x, y), 0) \wedge$ ilessp (iplus $(y, x), 0)))$
$\wedge$ ((ilessp $(y, x) \wedge (\neg$ ilessp $(y, 0)))$
$\rightarrow$ (ilessp (0, iplus $(x, y)) \wedge$ ilessp (0, iplus $(y, x))))$

THEOREM: ilessp-itimes-itimes-instance
ilessp (itimes (x, z), itimes $(y, z))$
$=$ ((ilessp $(0, z) \wedge$ ilessp $(x, y)) \vee$ (ilessp $(z, 0) \wedge$ ilessp $(y, x)))$

```
; doesn't work yet (needed below?)
;(prove-lemma ilessp-itimes-iquo (rewrite)
;            (implies
;             (and
;              (equal (irem w vw) 0)
;              (equal (irem v vw) 0))
;            (equal
;             (ilessp (itimes d (iquo w vw))
;                     (itimes c (iquo v vw)))
;             (and
;              (not (equal (fix-int vw) 0))
;              (if (ilessp vw 0)
;                  (ilessp (itimes c v) (itimes d w))
;                (ilessp (itimes d w) (itimes c v))))))
;            ((disable ilessp-0-iplus irem-is-my-irem
;                      CORRECTNESS-OF-CANCEL-ITIMES-ILESSP-FACTORS
;                      CORRECTNESS-OF-CANCEL-ITIMES-ILESSP
;                      CORRECTNESS-OF-CANCEL-ITIMES-FACTORS)
;             (enable-theory integers)
;             (enable ilessp-trichotomy *1*fix-int iquo-0-arg-better
;                     itimes-iquo)
;             (use (ilessp-itimes-itimes-instance
;                   (z vw) (x (itimes d (iquo w vw)))
;                   (y (itimes c (iquo v vw)))))))
;
;; not working yet
;(prove-lemma rlessp-simple-rplus-reduce-proof (rewrite)
```

```
;       (equal
;       (rlessp x (simple-rplus (reduce y) z))
;       (rlessp x (simple-rplus y z)))
;       ((enable-theory rational-defns integers naturals)
;       (enable *1*itimes *1*ilessp *1*iplus *1*integerp
;               *1*fix-int *1*ilessp *1*integerp igcd-non-negative
;               ilessp-0-iquo ilessp-0-igcd iabs-igcd iabs-simplify
;               ilessp-igcd ilessp-trichotomy fix-int-igcd
;               equal-igcd-0
;               izerop negativep-ilessp fix-to-fix-int)
;       (disable ilessp-0-iplus)))
;
```

THEOREM: ilessp-0-iplus-x-x
ilessp (0, iplus (x, x)) = ilessp (0, x)

THEOREM: ilessp-iplus-x-x-0
ilessp (iplus (x, x), 0) = ilessp (x, 0)

THEOREM: iquo-x-iabs-x
(iquo (x, iabs (x))
 = **if** fix-int (x) = 0 **then** 0
   elseif ilessp (x, 0) **then** -1
   else 1 **endif**)
∧ (iquo (iabs (x), x)
   = **if** fix-int (x) = 0 **then** 0
     elseif ilessp (x, 0) **then** -1
     else 1 **endif**)

THEOREM: nintegerp-ilessp
(¬ integerp (x))
→ ((ilessp (x, y) = ilessp (0, y)) ∧ (ilessp (y, x) = ilessp (y, 0)))

THEOREM: ilessp-x-igcd-x
(ilessp (x, igcd (x, y))
 = (ilessp (x, 0) ∨ ((fix-int (x) = 0) ∧ (fix-int (y) ≠ 0))))
∧ (ilessp (x, igcd (y, x))
   = (ilessp (x, 0) ∨ ((fix-int (x) = 0) ∧ (fix-int (y) ≠ 0))))

THEOREM: ilessp-trans-hack
(fix-int (x) = y)
→ ((ilessp (x, z) = ilessp (y, z)) ∧ (ilessp (z, x) = ilessp (z, y)))

THEOREM: commutativity-of-itimes-iquo
((irem (w, x) = 0) ∧ (irem (d, x) = 0))
→ (itimes (d, iquo (w, x)) = itimes (w, iquo (d, x)))

THEOREM: ilessp-equal-trans-special-case
$((\text{fix-int}\,(y) = x) \wedge (\text{fix-int}\,(x) = 0))$
$\rightarrow \quad ((\text{ilessp}\,(y,\ z) = \text{ilessp}\,(0,\ z)) \wedge (\text{ilessp}\,(z,\ y) = \text{ilessp}\,(z,\ 0)))$

```
; ---------- Final DEFTHEORY event ----------

;; I'll go ahead and include iplus-list and itimes-list and lemmas
;; about them that were developed.

;; I've left out ILESSP-TRICHOTOMY because I'm scared it will slow
;; things down too much.  But it certainly represents useful
;; information.

;; MMW put ILESSP-TRICHOTOMY back because his experience with
;; rationals suggests that it gets used all the time. 1-10-91
;; We'll see how it goes.
```

EVENT: Let us define the theory *integers* to consist of the following events: ileq, idifference, integerp-fix-int, integerp-iplus, integerp-idifference, integerp-ineg, integerp-iabs, integerp-itimes, fix-int-remover, fix-int-fix-int, fix-int-iplus, fix-int-idifference, fix-int-ineg, fix-int-iabs, fix-int-itimes, ineg-iplus, ineg-ineg, ineg-fix-int, ineg-of-non-integerp, ineg-0, iplus-left-id, iplus-right-id, iplus-0-left, iplus-0-right, commutativity2-of-iplus, commutativity-of-iplus, associativity-of-iplus, iplus-cancellation-1, iplus-cancellation-2, iplus-ineg1, iplus-ineg2, iplus-fix-int1, iplus-fix-int2, idifference-fix-int1, idifference-fix-int2, iplus-list, eval$-list-append, iplus-list-append, iplus-ineg3, iplus-ineg4, correctness-of-cancel-iplus, ilessp-fix-int-1, ilessp-fix-int-2, iplus-cancellation-1-for-ilessp, iplus-cancellation-2-for-ilessp, correctness-of-cancel-iplus-ilessp, itimes-0-left, itimes-0-right, itimes-fix-int1, itimes-fix-int2, commutativity-of-itimes, itimes-distributes-over-iplus-proof, itimes-distributes-over-iplus, commutativity2-of-itimes, associativity-of-itimes, equal-itimes-0, equal-itimes-1, equal-itimes-minus-1, itimes-1-arg1, quotient-remainder-uniqueness, division-theorem, itimes-ineg-1, itimes-ineg-2, itimes-cancellation-1, itimes-cancellation-2, itimes-cancellation-3, integerp-iquotient, integerp-iremainder, integerp-idiv, integerp-imod, integerp-iquo, integerp-irem, iquotient-fix-int1, iquotient-fix-int2, iremainder-fix-int1, iremainder-fix-int2, idiv-fix-int1, idiv-fix-int2, imod-fix-int1, imod-fix-int2, iquo-fix-int1, iquo-fix-int2, irem-fix-int1, irem-fix-int2, fix-int-iquotient, fix-int-iremainder, fix-int-idiv, fix-int-imod, fix-int-iquo, fix-int-irem, itimes-list, itimes-list-append, member-append, equal-fix-int, subsetp, correctness-of-cancel-itimes, ilessp-trichotomy, correctness-of-cancel-itimes-ilessp, ilessp-strict, eval$-list-cons, eval$-list-nlistp, eval$-litatom, eval$-quote, eval$-other, iplus-x-y-ineg-x, correctness-of-cancel-ineg, integerp-iplus-list, eval$-iplus-list-delete, eval$-iplus-list-bagdiff, itimes-tree-ineg, itimes-factors, itimes–1, equal-ineg-ineg, ilessp-ineg-ineg, fix-int-eval$-itimes-tree-rec, eval$-itimes-tree-ineg, ineg-eval$-itimes-tree-ineg, iplus-eval$-itimes-tree-ineg, itimes-eval$-itimes-tree-ineg,

iplus-or-itimes-term, cancel-itimes-factors, cancel-itimes-factors-expanded, cancel-itimes-factors-expanded-cancel-itimes-factors, membership-of-0-implies-itimes-list-is-0, member-0-eval$-list, correctness-of-cancel-itimes-factors, cancel-itimes-ilessp-factors, bagint-singleton, ilessp-itimes-list-eval$-list-bagdiff, ilessp-itimes-list-eval$-list-bagdiff-corollary-1, member-0-itimes-factors-yields-0, member-0-itimes-factors-yields-0-ilessp-consequence-1, member-0-itimes-factors-yields-0-ilessp-consequence-2, ilessp-itimes-list-eval$-list-bagdiff-corollary-2, correctness-of-cancel-itimes-ilessp-factors, disjoin-equalities-with-0, cancel-factors-0, some-eval$s-to-0, eval$-disjoin-equalities-with-0, some-eval$s-to-0-append, some-eval$s-to-0-eliminator, correctness-of-cancel-factors-0, correctness-of-cancel-factors-ilessp-0, conjoin-inequalities-with-0, split-out-ineg-terms, correctness-of-cancel-ineg-terms-from-equality, correctness-of-cancel-ineg-terms-from-inequality, iplus-constants, cancel-constants-equal, ilessp-add1, ilessp-add1-iplus, cancel-constants-ilessp, ilessp-irem, irem-noop, irem-of-0, irem-iquo-elim, irem-iplus-0, integerp-igcd, commutativity-of-igcd, igcd-0, igcd-1, equal-igcd-0, igcd-non-negative, ilessp-igcd, igcd-iplus, irem-igcd, distributivity-of-itimes-over-igcd, common-divisor-divides-igcd, iabs-igcd, associativity-of-igcd, commutativity2-of-igcd, igcd-x-x, igcd-idempotence, iquo-0, ilessp-0-iquo, iabs-simplify, igcd-iquo-igcd-proof, ilessp-iquo-0, iquo-1, ilessp-0-igcd, igcd-minus, itimes-iquo, iquo-x-x, iquo-0-arg-better, itimes-iquotient, iquotient-0, iremainder-0, irem-0-iremainder-0, equal-itimes-x-x, itimes-igcd-fact, itimes-iquo-general, itimes-iquo-copy, equal-iquo-iquo, idifference-x-x, irem-iquo-itimes, equal-irem-itimes-0, commutativity-of-iquo, irem-itimes, iquo-igcd-itimes1, iquo-igcd-itimes2, iquo-igcd-itimes3, equal-iquo-1, equal-x-igcd-x-y, ilessp-iplus-igcd, ilessp-iabs-arg1, ilessp-iabs-arg2, igcd-fix-int, iquo-iquo, igcd-iquo-iquo, iabs-ineg, iquo-ineg, igcd-ineg, igcd-0-better, not-integerp-means, ilessp-itimes-igcd-hack, irem-0-backchain, irem-itimes-cancel, irem-itimes-base, fix-int-minus, iquo-iplus, equal-iquo-0, ilessp-iquo, ilessp-minus-0, equal-fix-int-y, iabs-fix-int, equal-x-iabs-x, equal-fix-int-iabs, iabs-iabs, fix-int-igcd, not-integerp, igcd-iplus-ineg, negativep-iplus-ineg, negativep-iplus-ineg2, igcd-iplus-itimes-hack, iquo-itimes-iabs, itimes-2, iquo-iplus-itimes-iabs-hack, iabs-0, ilessp-0-iabs, ilessp-iplus-hacks, ilessp-iplus-hacks2, ilessp-iplus-hacks3, ilessp-0-iplus-x-x, ilessp-iplus-x-x-0, iquo-x-iabs-x, nintegerp-ilessp, ilessp-x-igcd-x, commutativity-of-itimes-iquo, izerop, *1*integerp, *1*fix-int, *1*ilessp, *1*iplus, *1*ineg, *1*iabs, *1*itimes, *1*iquotient, *1*iremainder, *1*idiv, *1*imod, *1*iquo, *1*irem, *1*ileq, *1*idifference, *1*izerop, *1*igcd.

EVENT: Disable iplus-irem-itimes-iquo.

EVENT: Disable irem-is-my-irem.

EVENT: Disable iquo-0-arg.

EVENT: Disable itimes-hack1.

EVENT: Disable itimes-hack2.

EVENT: Disable gcd-factors-gives-linear-combination.

EVENT: Disable gcd-factors-gives-linear-combination-rewrite.

EVENT: Disable remainder-0-sufficiency.

EVENT: Disable itimes-iplus-hack.

EVENT: Disable irem-0-iremainder-0-help1.

EVENT: Disable irem-0-iremainder-0-help2.

EVENT: Disable divides-product-reduction-helper.

EVENT: Disable divides-product-reduction.

EVENT: Disable divides-each-equality.

EVENT: Disable times-gcd-fact.

EVENT: Disable iplus-iquo-iquo.

EVENT: Disable fix-int-on-non-0.

EVENT: Disable iabs-open-as-integers.

EVENT: Disable ilessp-itimes-igcd-hack2.

EVENT: Disable ilessp-ineg-igcd-hack.

EVENT: Disable ilessp-itimes-itimes-instance.

EVENT: Disable ilessp-trans-hack.

EVENT: Disable ilessp-equal-trans-special-case.

EVENT: Enable izerop.

EVENT: Make the library "`integers`" and compile it.

Index

add1-iplus, 87
associativity-of-igcd, 81
associativity-of-iplus, 10
associativity-of-itimes, 26

bagdiff, 19–21, 23–25, 34, 36, 37, 39–43, 47, 60, 61, 63
bagint, 18–20, 23–25, 35, 39–42, 47, 50, 61, 62, 64, 65
bagint-singleton, 62

cancel-constants-equal, 78
cancel-constants-equal-lemma, 78
cancel-constants-ilessp, 78
cancel-constants-ilessp-lemma-1, 78
cancel-constants-ilessp-lemma-2, 78
cancel-factors-0, 66, 67
cancel-factors-ilessp-0, 67, 68
cancel-ineg, 14, 16
cancel-ineg-aux, 12–16
cancel-ineg-terms-from-equality, 71, 74
  -cancel-ineg-terms-from-equality-expanded, 74
  -expanded, 71, 74, 75
cancel-ineg-terms-from-inequality, 75, 77
  y-cancel-ineg-terms-from-inequality-expanded, 77
  y-expanded, 75, 77
cancel-iplus, 18, 20, 22
cancel-iplus-ilessp, 25
cancel-iplus-ilessp-1, 23, 24
cancel-itimes, 35, 40
cancel-itimes-factors, 50, 60
cancel-itimes-factors-expanded, 60, 61
cancel-itimes-factors-expanded-cancel-itimes-factors, 60
cancel-itimes-ilessp, 41, 43
cancel-itimes-ilessp-factors, 61, 65
common-divisor-divides-igcd, 81
commutativity-of-igcd, 80
commutativity-of-iplus, 10
commutativity-of-iquo, 89
commutativity-of-itimes, 26
commutativity-of-itimes-iquo, 97
commutativity2-of-igcd, 81
commutativity2-of-iplus, 10
commutativity2-of-itimes, 26
conjoin-inequalities-with-0, 67, 68
conjoin-inequalities-with-0-eliminator, 68
correctness-of-cancel-factors-0, 67
correctness-of-cancel-factors-ilessp-0, 68
correctness-of-cancel-ineg, 16
correctness-of-cancel-ineg-aux, 16
correctness-of-cancel-ineg-terms-from-equality, 75
  s-from-inequality, 77
correctness-of-cancel-iplus, 22
correctness-of-cancel-iplus-ilessp, 25
  ssp-lemma, 24
correctness-of-cancel-itimes, 40
correctness-of-cancel-itimes-factors, 61
correctness-of-cancel-itimes-hack-1, 37
  ck-2, 39
  ck-3, 39
  ck-3-lemma, 39
correctness-of-cancel-itimes-ilessp, 43
  ssp-factors, 65
  ssp-hack-1, 42
  ssp-hack-2, 42
  ssp-hack-2-lemma, 42
  ssp-hack-3, 43
  ssp-hack-3-lemma-1, 42
  ssp-hack-3-lemma-2, 43
  ssp-hack-4, 43

delete, 19–21, 36–38, 60, 62
difference-idifference, 78
difference-idifference2, 87
disjoin-equalities-with-0, 65, 66
distributivity-of-itimes-over-i
gcd, 81
gcd-proof, 81
divides-each-equality, 85
divides-product-reduction, 85
divides-product-reduction-helpe
r, 85
r-1, 85
division-theorem, 27
division-theorem-for-truncate-t
o-neginf, 28
o-neginf-part1, 28
o-neginf-part2, 28
o-neginf-part3, 28
o-zero, 29
o-zero-part1, 29
o-zero-part2, 29
o-zero-part3, 29
division-theorem-part1, 27
division-theorem-part2, 27
division-theorem-part3, 27

equal-0-itimes-list-eval$-bagi
nt-1, 39
nt-2, 39
equal-fix-int, 38
equal-fix-int-iabs, 94
equal-fix-int-to-ilessp, 65
equal-fix-int-y, 93
equal-igcd-0, 80
equal-ineg-ineg, 48
equal-iquo-0, 93
equal-iquo-1, 90
equal-iquo-iquo, 89
equal-irem-itimes-0, 89
equal-itimes-0, 26
equal-itimes-1, 26
equal-itimes-list-eval$-list-b
agdiff, 60
equal-itimes-list-eval$-list-de
lete, 37
lete-new-1, 60
lete-new-2, 60
equal-itimes-minus-1, 26
equal-itimes-x-x, 84
equal-x-iabs-x, 94
equal-x-igcd-x-y, 91
equal-x-igcd-x-y-proof, 91
eval$-cancel-ineg-aux-fn, 15, 16
eval$-cancel-ineg-aux-is-its-f
n, 15
eval$-cancel-iplus, 20
eval$-disjoin-equalities-with-
0, 66
eval$-equal-itimes-tree-itimes
-fringe-0, 38
eval$-ilessp-iplus-tree-no-fix
-int, 24
eval$-iplus, 22
eval$-iplus-list-bagdiff, 21
eval$-iplus-list-car-remove-ine
gs, 74
eval$-iplus-list-cdr-remove-ine
gs, 74
eval$-iplus-list-delete, 21
eval$-iplus-tree, 17
eval$-iplus-tree-rec, 17
eval$-itimes-tree, 33
eval$-itimes-tree-ineg, 48
eval$-itimes-tree-no-fix-int-1, 40
eval$-itimes-tree-no-fix-int-2, 40
eval$-itimes-tree-rec, 33
eval$-list-append, 17
eval$-list-bagint-0, 61
eval$-list-bagint-0-for-ilessp, 64
eval$-list-bagint-0-implies-eq
ual, 61
ual-for-ilessp, 65
ual-for-ilessp-lemma, 65
eval$-list-cons, 14
eval$-list-nlistp, 14
eval$-litatom, 14
eval$-make-cancel-itimes-equalit
y, 37

y-1, 38
y-2, 38
eval$-make-cancel-itimes-inequ
ality, 41
eval$-other, 14

fix-int, 5–11, 15, 16, 21–23, 25, 26, 30–32, 36–39, 42, 43, 48, 60–62, 64–66, 78–84, 86–95, 97, 98
fix-int-eval$-itimes-tree-rec, 48
fix-int-fix-int, 9
fix-int-iabs, 9
fix-int-idifference, 9
fix-int-idiv, 31
fix-int-igcd, 94
fix-int-imod, 32
fix-int-ineg, 9
fix-int-iplus, 9
fix-int-iquo, 32
fix-int-iquotient, 31
fix-int-irem, 32
fix-int-iremainder, 31
fix-int-itimes, 9
fix-int-minus, 92
fix-int-on-non-0, 92
fix-int-remover, 9
fix-to-fix-int, 86

gcd, 80, 84–88
gcd-factors, 83, 84
gcd-factors-accept, 83
gcd-factors-gives-linear-combin
ation, 84
ation-rewrite, 84
gcd-is-igcd, 86
gcd-remainder-times-fact1-proof, 85
-non-numberp-case, 85
-numberp-case, 85

iabs, 6, 8, 9, 27–30, 79–82, 91–95, 97
iabs-0, 95
iabs-fix-int, 94
iabs-iabs, 94
iabs-igcd, 81
iabs-ineg, 91
iabs-open-as-integers, 93
iabs-simplify, 81
idifference, 6–9, 11, 21, 78, 83, 87, 89
idifference-fix-int1, 11
idifference-fix-int2, 11
idifference-x-x, 89
idiv, 7, 28–31
idiv-fix-int1, 31
idiv-fix-int2, 31
idiv-imod-uniqueness, 28
igcd, 80–83, 87–94, 97
igcd-0, 80
igcd-0-better, 92
igcd-1, 80
igcd-fix-int, 91
igcd-idempotence, 81
igcd-ineg, 91
igcd-iplus, 80
igcd-iplus-ineg, 94
igcd-iplus-instance-proof, 80
igcd-iplus-itimes-hack, 94
igcd-iquo-igcd-proof, 81
igcd-iquo-iquo, 91
igcd-minus, 82
igcd-non-negative, 80
igcd-x-x, 81
ileq, 6
ilessp, 6, 23, 24, 27–30, 40–43, 48, 62–65, 68, 78–82, 85–98
ilessp-0-iabs, 95
ilessp-0-igcd, 82
ilessp-0-iplus-open, 93
ilessp-0-iplus-x-x, 97
ilessp-0-iquo, 81
ilessp-0-itimes, 63
ilessp-add1, 78
ilessp-add1-iplus, 78
ilessp-equal-trans-special-case, 98
ilessp-fix-int-1, 23
ilessp-fix-int-2, 23

ilessp-iabs-arg1, 91
ilessp-iabs-arg2, 91
ilessp-igcd, 80
ilessp-ineg-igcd-hack, 93
ilessp-ineg-ineg, 48
ilessp-iplus-hacks, 95
ilessp-iplus-hacks2, 96
ilessp-iplus-hacks3, 96
ilessp-iplus-igcd, 91
ilessp-iplus-x-x-0, 97
ilessp-iquo, 93
ilessp-iquo-0, 82
ilessp-irem, 79
ilessp-itimes-0, 63
ilessp-itimes-igcd-hack, 92
ilessp-itimes-igcd-hack2, 93
ilessp-itimes-itimes-instance, 96
ilessp-itimes-list-eval$-list-
    bagdiff, 63
    bagdiff-corollary-1, 63
    bagdiff-corollary-2, 63
    delete, 62
    delete-helper-1, 62
    delete-helper-2, 62
    delete-prime, 62
    delete-prime-helper-1, 62
    delete-prime-helper-2, 62
ilessp-itimes-right-negative, 43
ilessp-itimes-right-positive, 42
ilessp-lessp, 86
ilessp-minus-0, 93
ilessp-strict, 43
ilessp-trans-hack, 97
ilessp-trichotomy, 42
ilessp-x-igcd-x, 97
ilessp-zero-implies-not-equal, 63
imod, 7, 28–32
imod-fix-int1, 31
imod-fix-int2, 31
ineg, 6, 8–11, 15, 16, 21, 22, 29, 30, 47, 48, 75, 79, 91, 93–95
ineg-0, 10
ineg-eval$-itimes-tree-ineg, 48
ineg-fix-int, 9
ineg-ineg, 9
ineg-iplus, 9
ineg-of-non-integerp, 9
integer-defns, 8
integerp, 5, 8–10, 17, 20–22, 27–31, 33, 36–38, 60, 61, 67, 74, 78–80, 82, 84, 87, 91, 92, 94, 97
integerp-eval$-iplus-or-ineg-te
    rm, 74
integerp-eval$-itimes, 36
integerp-fix-int, 8
integerp-iabs, 8
integerp-idifference, 8
integerp-idiv, 30
integerp-igcd, 80
integerp-imod, 30
integerp-ineg, 8
integerp-iplus, 8
integerp-iplus-list, 17
integerp-iquo, 30
integerp-iquotient, 30
integerp-irem, 31
integerp-iremainder, 30
integerp-itimes, 9
integerp-itimes-list, 33
integers, 99
iplus, 6, 8–11, 15–17, 21, 22, 24, 26–30, 48, 74, 75, 78–80, 84, 86, 87, 91–97
iplus-0-left, 10
iplus-0-right, 10
iplus-cancellation-1, 10
iplus-cancellation-1-for-ilessp, 24
iplus-cancellation-2, 10
iplus-cancellation-2-for-ilessp, 24
iplus-constants, 78
iplus-eval$-itimes-tree-ineg, 48
iplus-fix-int1, 11
iplus-fix-int2, 11
iplus-fringe, 16, 18–21, 23, 25, 70–77
iplus-ineg-promote, 15
iplus-ineg1, 11

iplus-ineg2, 11
iplus-ineg3, 15
iplus-ineg4, 15
iplus-ineg5, 22
iplus-ineg5-lemma-1, 21
iplus-ineg5-lemma-2, 22
iplus-ineg6, 22
iplus-ineg7, 22
iplus-iquo-iquo, 91
iplus-irem-itimes-iquo, 79
iplus-left-id, 10
iplus-list, 17, 20, 21, 74, 75
iplus-list-append, 21
iplus-list-eval$-car-split-out-ineg-terms, 75
iplus-list-eval$-fringe, 21
iplus-or-ineg-term, 70, 71, 74, 75
iplus-or-itimes-term, 49, 50, 61
iplus-or-itimes-term-integerp-eval$, 61
iplus-right-id, 10
iplus-tree, 17, 19, 20, 23, 24, 71–77
iplus-tree-no-fix-int, 24, 25
iplus-tree-rec, 17, 24
iplus-x-y-ineg-x, 16
iquo, 7, 29–32, 79, 81–83, 85, 89–95, 97
iquo-0, 81
iquo-0-arg, 82
iquo-0-arg-better, 83
iquo-1, 82
iquo-fix-int1, 31
iquo-fix-int2, 31
iquo-igcd-itimes-proof1, 89
iquo-igcd-itimes-proof2, 90
iquo-igcd-itimes1, 90
iquo-igcd-itimes2, 90
iquo-igcd-itimes3, 90
iquo-ineg, 91
iquo-iplus, 92
iquo-iplus-itimes-iabs-hack, 95
iquo-iquo, 91
iquo-irem-uniqueness, 29
iquo-itimes-iabs, 94
iquo-x-iabs-x, 97
iquo-x-x, 83
iquotient, 7, 27, 28, 30, 31, 84
iquotient-0, 84
iquotient-fix-int1, 31
iquotient-fix-int2, 31
iquotient-iremainder-uniqueness, 27
irem, 7, 29–32, 79–84, 87, 89–95, 97
irem-0-backchain, 92
irem-0-iremainder-0, 84
irem-0-iremainder-0-help1, 84
irem-0-iremainder-0-help2, 84
irem-fix-int1, 31
irem-fix-int2, 31
irem-igcd, 80
irem-iplus-0, 80
irem-iplus-0-proof, 79
irem-iquo-elim, 79
irem-iquo-itimes, 89
irem-iquo-itimes-proof, 89
irem-is-my-irem, 79
irem-itimes, 89
irem-itimes-base, 92
irem-itimes-cancel, 92
irem-noop, 79
irem-of-0, 79
iremainder, 7, 27, 28, 30, 31, 84, 85
iremainder-0, 84
iremainder-fix-int1, 31
iremainder-fix-int2, 31
itimes, 6, 7, 9, 25–30, 33, 36, 37, 39, 42, 43, 47, 48, 60–63, 79, 81–85, 88–97
itimes–1, 47
itimes-0-left, 25
itimes-0-right, 26
itimes-1-arg1, 26
itimes-2, 94
itimes-cancellation-1, 30
itimes-cancellation-2, 30
itimes-cancellation-3, 30
itimes-distributes-over-iplus, 26
itimes-distributes-over-iplus-proof, 26

itimes-eval$-itimes-tree-ineg, 48
itimes-factors, 47, 50, 61, 63–68
itimes-fix-int1, 26
itimes-fix-int2, 26
itimes-fringe, 33, 35–43
itimes-hack1, 82
itimes-hack1-1, 82
itimes-hack1-1-1, 82
itimes-hack1-2, 82
itimes-hack1-2-1, 82
itimes-hack2, 83
itimes-igcd-fact, 88
itimes-igcd-fact-proof, 88
itimes-ineg-1, 30
itimes-ineg-2, 30
itimes-iplus-hack, 84
itimes-iquo, 82
itimes-iquo-copy, 89
itimes-iquo-general, 89
itimes-iquotient, 84
itimes-itimes-list-eval$-list-delete, 60
itimes-list, 33, 36–40, 42, 43, 48, 60–66, 68
itimes-list-append, 36
itimes-list-bagdiff, 36
itimes-list-eval$-delete, 36
itimes-list-eval$-factors, 61
itimes-list-eval$-factors-lemma, 61
a-prime, 61
itimes-list-eval$-fringe, 36
itimes-list-eval$-list-0, 42
itimes-tree, 33, 34, 37–40
itimes-tree-ineg, 47, 48
itimes-tree-no-fix-int, 40–42
itimes-tree-rec, 33, 40, 47, 48
itimes-zero1, 25
itimes-zero2, 25
izerop, 5, 79, 82, 83, 86, 93–95
izerop-eval-of-member-implies-itimes-list-0, 38
izerop-ilessp-0-relationship, 62

lessp-count-listp-cdr, 17
lessp-difference-plus-arg1, 23
lessp-difference-plus-arg1-commuted, 23
listp-bagint-with-singleton-implies-member, 42
listp-bagint-with-singleton-member, 42
listp-cdr-factors-implies-integerp, 67

make-cancel-ineg-terms-equality, 70, 71
make-cancel-ineg-terms-inequality, 75
make-cancel-iplus-inequality-1, 23, 24
make-cancel-iplus-inequality-simplifier, 24
make-cancel-itimes-equality, 34–38, 50
make-cancel-itimes-inequality, 40, 41, 61
member-0-eval$-list, 60
member-0-itimes-factors-yields-0-ilessp-consequence-1, 64
0-ilessp-consequence-2, 64
0, 63
member-append, 37
member-izerop-itimes-fringe, 37
membership-of-0-implies-itimes-list-is-0, 60
minus-ineg, 75
my-irem, 79

nats-to-ints, 87
negativep-ilessp, 87
negativep-iplus-ineg, 94
negativep-iplus-ineg2, 94
nintegerp-ilessp, 97
not-integerp, 94
not-integerp-implies-not-equal-iplus, 21
not-integerp-implies-not-equal-itimes, 36

not-integerp-means, 92
numberp-ilessp, 86
numberp-is-integerp, 78

plus-iplus, 78
plus-iplus2, 86

quotient-difference-lessp-arg2, 27
quotient-remainder-uniqueness, 27
quotient-to-iquo, 85

remainder-0-sufficiency, 84
remainder-to-irem, 87
remove-inegs, 70–77

same-fix-int-implies-not-ilessp, 43
some-eval$s-to-0, 66
some-eval$s-to-0-append, 66
some-eval$s-to-0-eliminator, 66
split-out-ineg-terms, 70, 74, 75
subbagp, 21, 36, 38, 42, 43, 60, 63
subbagp-subsetp, 38
subsetp, 38, 42, 43
subsetp-implies-itimes-list-eva
    l$-equals-0, 38

times-gcd-fact, 88
times-gcd-fact-proof, 88
times-gcd-fact-proof-1, 87
times-gcd-fact-proof-2, 88
times-gcd-fact-proof-2-1, 88
times-gcd-fact-proof-2-2, 88
times-gcd-fact-proof-2-3, 88
times-to-itimes, 85

zero-ilessp-implies-not-equal, 63
zerop-izerop, 86