

Exception handling for the BLAS and LAPACK

Wesley da Silva Pereira, University of Colorado Denver

BLIS Retreat 2022

September 22, UT Austin

Examples of bad exception handling

- Ariane 501, 1996. “[An] exception was caused during execution of a data conversion from 64-bit floating point to 16-bit signed integer value.” ²
- Roborace, 2020. “the system somehow managed to produce a NaN (not a number) value and all verification logic was designed to work only with numbers.” ³



²<https://www-users.cse.umn.edu/~arnold/disasters/ariane.html>

³<https://www.reddit.com/r/formula1/comments/jk9jrg/comment/gai2951>

Agenda

- ① Inconsistencies in the Reference BLAS and LAPACK libraries
(Some also in BLIS)
- ② Proposed exception handling
- ③ Early tests for the proposed consistent standard
- ④ Concluding remarks

One of the goals of this talk:
Seek feedback

Inconsistencies in the Reference BLAS

l_xAMAX: Return the index of the largest entry.

- Inconsistency #1:

`isamax([0, NaN, 2]) = 3,`

`isamax([NaN, 0, 2]) = 1,`

- Inconsistency #2:

`icamax([OV+i*OV, Inf+i*0]) = 1,`

`icamax([.6*OV+i*.6*OV, .7*OV+i*.7*OV]) = 1,`

where OV is the overflow threshold.

- Proposed consistent fix:

**Return index to the first NaN,
else to the first Inf,
else to the first largest finite entry.**

Inconsistencies in the Reference BLAS

lxAMAX: Return the index of the largest entry.

- Inconsistency #1:

`isamax([0, NaN, 2]) = 3,`

`isamax([NaN, 0, 2]) = 1,`

- Inconsistency #2:

`icamax([0V+i*0V, Inf+i*0]) = 1,`

`icamax([.6*0V+i*.6*0V, .7*0V+i*.7*0V]) = 1,`

where 0V is the overflow threshold.

- Proposed consistent fix:

**Return index to the first NaN,
else to the first Inf,
else to the first largest finite entry.**

BLIS 0.9.0 has inconsistency #2 only.

Inconsistencies in the Reference BLAS

xGER: $A := A + \alpha xy^T$.

- Current Reference BLAS:

If $\alpha = 0$, return A .

If $y_j = 0$ then $A_{ij} := A_{ij}$. (What if $x_i = \text{Inf}$ or NaN ?)

There is no check for $x_i = 0$.

xTRSV: Solve $Tx = b$ for x .

- Current Reference BLAS:

Skip trailing 0s in b .

If $y_j = 0$ then skip update $x_i := x_i - T_{ij}x_j$.

No checks for 0s when solving $T^T x = b$.

Proposed consistent fix:

Keep check for $\alpha = 0$ but not for $x_i = 0$, $y_i = 0$ or $b_i = 0$.

Inconsistencies in LAPACK

xGETF2 + xGETRS: Solve $Ax = b$ for x .

- Example: $A = \begin{bmatrix} 1 & 0 \\ NaN & 2 \end{bmatrix}$ and $b = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$.
- Combination of inconsistencies in the Reference BLAS:
 - IxAMAX chooses $A_{11} = 1$, not $A_{21} = NaN$, as pivot.

$$A = \begin{bmatrix} 1 & 0 \\ NaN & 2 \end{bmatrix}$$

Inconsistencies in LAPACK

xGETF2 + xGETRS: Solve $Ax = b$ for x .

- Example: $A = \begin{bmatrix} 1 & 0 \\ NaN & 2 \end{bmatrix}$ and $b = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$.
- Combination of inconsistencies in the Reference BLAS:
 - IxAMAX chooses $A_{11} = 1$, not $A_{21} = NaN$, as pivot.
 - xGER finds 0 in A_{12} and does not use the NaN. (Also on BLIS 0.9.0)

$$A_{22} := A_{22} - NaN \cdot 0$$

Inconsistencies in LAPACK

xGETF2 + xGETRS: Solve $Ax = b$ for x .

- Example: $A = \begin{bmatrix} 1 & 0 \\ NaN & 2 \end{bmatrix}$ and $b = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$.
- Combination of inconsistencies in the Reference BLAS:
 - IxAMAX chooses $A_{11} = 1$, not $A_{21} = NaN$, as pivot.
 - xGER finds 0 in A_{12} and does not use the NaN.
 - LU factorization: $L = \begin{bmatrix} 1 & 0 \\ NaN & 1 \end{bmatrix}$, $U = \begin{bmatrix} 1 & 0 \\ 0 & 2 \end{bmatrix}$

Inconsistencies in LAPACK

xGETF2 + xGETRS: Solve $Ax = b$ for x .

- Example: $A = \begin{bmatrix} 1 & 0 \\ NaN & 2 \end{bmatrix}$ and $b = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$.
- Combination of inconsistencies in the Reference BLAS:
 - IxAMAX chooses $A_{11} = 1$, not $A_{21} = NaN$, as pivot.
 - xGER finds 0 in A_{12} and does not use the NaN.
 - LU factorization: $L = \begin{bmatrix} 1 & 0 \\ NaN & 1 \end{bmatrix}$, $U = \begin{bmatrix} 1 & 0 \\ 0 & 2 \end{bmatrix}$
 - The first call for xTRSV solves $Ly = b$ and finds $y = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$. In the second iteration, $y_2 := 1 - NaN \cdot y_1$ and $y_1 = 0$.

Inconsistencies in LAPACK

xGETF2 + xGETRS: Solve $Ax = b$ for x .

- Example: $A = \begin{bmatrix} 1 & 0 \\ NaN & 2 \end{bmatrix}$ and $b = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$.
- Combination of inconsistencies in the Reference BLAS:
 - IxAMAX chooses $A_{11} = 1$, not $A_{21} = NaN$, as pivot.
 - xGER finds 0 in A_{12} and does not use the NaN.
 - LU factorization: $L = \begin{bmatrix} 1 & 0 \\ NaN & 1 \end{bmatrix}$, $U = \begin{bmatrix} 1 & 0 \\ 0 & 2 \end{bmatrix}$
 - The first call for xTRSV solves $Ly = b$ and finds $y = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$.
 - The final solution is $x = \begin{bmatrix} 0 \\ 0.5 \end{bmatrix}$
- **NaN does not propagate!**

BLIS 0.9.0 propagates NaNs in this example.

Examples of unavoidable inconsistencies

Summation order: $\text{sum}([0V, 0V, -0V, -0V])$ can be NaN, Inf, -Inf or 0, where 0V is the overflow threshold.

IEEE 754-2019 defines min and max that propagate NaNs. Compilers need time to adopt those rules. ⁴

```
1 min( qNaN, 1.0 ) = qNaN ! gfortran 12.2
2 min( 1.0, qNaN ) = 1.0 ! gfortran 12.2
```

Absolute value, product, and quotient of complex numbers:

- They are not specified by IEEE 754-2019.
- There is space for inconsistencies, e.g., ⁵

```
1 cmplx(Inf,0.0)*cmplx(Inf,Inf) = cmplx(Inf,Inf) ! ifort 2021
2 cmplx(Inf,0.0)*cmplx(Inf,Inf) = cmplx(NaN,NaN) ! gfortran 12
3
4 abs(subNormal) = subNormal ! ifort 2021
5 abs(cmplx(0.0,subNormal)) = subNormal ! ifort 2021 (-00)
6 abs(cmplx(0.0,subNormal)) = 0.0 ! ifort 2021 (-03)
```

⁴<https://www.godbolt.org/z/1sfceYbao>

⁵<https://www.godbolt.org/z/nvWWeToY6>

Proposed exception handling

"If NaNs or Infs won't just disappear!"

- 1 The program will still complete.
- 2 Moreover, either:
 - NaNs and Infs propagate to the output.
 - NaNs and Infs are dealt with internally.
 - NaNs and Infs **do not propagate** to the output **in special cases**, e.g., $C := 0 \cdot AB + 0 \cdot C$ in GEMM.
- 3 LAPACK routines will report (using INFO and more).

Current design ⁶ takes into account:

- Several user requests.
- Different stakeholders.
- Relevant xSDK Community Policies for Library Development.

⁶<https://www.arxiv.org/abs/2207.09281>

The EC (Error Checking) interfaces

- Example:
SGESV_EC(N, NRHS, A, LDA, IPIV, B, LDB, INFO,
FLAG_REPORT, INFO_ARRAY, CONTEXT)
- 3 more arguments at end:
 - FLAG_REPORT(1:2)
FLAG_REPORT(1): WHAT to report.
FLAG_REPORT(2): HOW to report.
 - INFO_ARRAY(FIXED_SIZE) - can report INFO + details on
Infs and NaNs on input, output and internal calls.
 - CONTEXT - pointer to opaque data. Can report, for example,
exceptions on different threads.
- Legacy interface will be maintained as a wrapper.

Some early testBLAS⁹ results

Expected output from IxAMAX: Return index to the first NaN, else to the first Inf, else to the first largest finite entry.

BLAS library ⁷	I{S,D}AMAX	I{C,Z}AMAX
Apple Accelerate 12.2.1	X ⁸	X
BLIS 0.9.0	Pass	X
IBM ESSL 6.3.0	X	X
Intel MKL 2022.1.0	Pass	X
LAPACK 3.9.1	X	X
LAPACK 3.10.1	X	X
LAPACK 3.11-beta	Pass	Pass
OpenBLAS 0.3.8	X	X

⁷Apple Accelerate on macOS Monterey 12.2.1 using Apple clang version 13.1.6. IBM ESSL on Summit node using GNU compiler v9.1.0. Others on Ubuntu 20.04.4 LTS using GNU compiler v9.4.0.

⁸X: Does not follow proposed standard.

⁹<https://www.github.com/tlapack/testBLAS>

Some early testBLAS¹² results

Expected output from xNRM2: NaN if in input, else Inf if in input, else “accurate answer” (possibly Inf).

BLAS library ¹⁰	{S,D}NRM2 (finite input)	{S,D}NRM2
Apple Accelerate 12.2.1	X ¹¹	X
BLIS 0.9.0	X	X
IBM ESSL 6.3.0	Pass	Pass
Intel MKL 2022.1.0	Pass	Pass
LAPACK 3.9.1	X	X
LAPACK 3.10.1	Pass	Pass
LAPACK 3.11-beta	Pass	Pass
OpenBLAS 0.3.8	Pass	Pass

¹⁰Apple Accelerate on macOS Monterey 12.2.1 using Apple clang version 13.1.6. IBM ESSL on Summit node using GNU compiler v9.1.0. Others on Ubuntu 20.04.4 LTS using GNU compiler v9.4.0.

¹¹X: Does not follow proposed standard.

¹²<https://www.github.com/tlapack/testBLAS>

Proposed tasks

- 1 During installation of LAPACK, check `abs`, multiplication and division of complex, and `min` and `max` behave as expected.
(Partially done in LAPACK 3.10.1)
- 2 Modify LAPACKE drivers, so that they return an error flag if input has NaNs or Infs.
- 3 Modify LAPACK, so that routines that compute norms of complex matrices signal NaNs and Infs on input.
- 4 Fix Reference BLAS and implement test code.
(The new `lxAMAX` is planned to be in LAPACK 3.11)
- 5 Validate the EC interfaces for a few LAPACK routines.
- 6 Design more general test code.
- 7 Implement the EC interfaces to the rest of LAPACK.

Thank you!

Questions?

wesley.pereira@ucdenver.edu

Proposed Exception Handling for the BLAS and LAPACK:

<https://www.arxiv.org/abs/2207.09281>

(Shorter version will be available in the SC'22)

Funded by:

NSF under the project Basic ALgebra Libraries for Sustainable Technology with Interdisciplinary Collaboration (BALLISTIC).



National
Science
Foundation